PolvOne

### MATERIAL SAFETY DATA SHEET 11007GNS WHITE

Version Number 1.3 Revision Date 10/08/2009

Page 1 of 7 Print Date 1/9/2012

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	11007GNS WHITE
Product code	:	FO00000523
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight percent
Silica, amorphous	7631-86-9	1 - 5
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye and skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

PolyOne.

# MATERIAL SAFETY DATA SHEET 11007GNS WHITE

Version Number 1.3 Revision Date 10/08/2009 Page 2 of 7 Print Date 1/9/2012

Medical Conditions       : None known.         Aggravated by Exposure:			
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: no data available		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>no data available</li> <li>no data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.		
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		

PolyOne.

# MATERIAL SAFETY DATA SHEET 11007GNS WHITE

ersion Number 1.3 evision Date 10/08/2009		Page 3 of 7 Print Date 1/9/2012
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXI	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

<u>PolyOne</u>.

# **MATERIAL SAFETY DATA SHEET** 11007GNS WHITE

Version Number 1.3 Revision Date 10/08/2009 Page 4 of 7 Print Date 1/9/2012

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Silica, amorphous	6 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility

#### : liquid : viscous, liquid WHITE very faint not applicable

:

:

:

:

not applicable

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

- : Not established Not determined :
- Not applicable :
- Not determined :
- : Not determined
- Not applicable :

# : immiscible

	-	
Stability	:	Stable
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and

**10. STABILITY AND REACTIVITY** 

### MATERIAL SAFETY DATA SHEET 11007GNS WHITE

Version Number 1.3 Revision Date 10/08/2009 Page 5 of 7 Print Date 1/9/2012

smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
<b>Bioaccumulation Potential</b>	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The

PolyOne.

# MATERIAL SAFETY DATA SHEET 11007GNS WHITE

sion Number 1.3 /ision Date 10/08/2009	Page 6 of Print Date 1/9/201
	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
not applicable	
California Proposition 65	a : Not applicable
65	a : Not applicable Extremely Hazardous Substance
65 SARA Title III Section 302 E	Extremely Hazardous Substance
65 SARA Title III Section 302 E	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulation
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulation Yoxic Chemicals:
65 SARA Title III Section 302 E Unless specific chemicals are SARA Title III Section 313 T	Extremely Hazardous Substance identified under this section, this product is Not Applicable under this regulation

PolvOne

# MATERIAL SAFETY DATA SHEET 11007GNS WHITE

Version Number 1.3 Revision Date 10/08/2009 Page 7 of 7 Print Date 1/9/2012

not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

Γ	CAS-No.
	7631-86-9

DSL

All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS		:	Not determined
China	a IECS	:	Not determined
Europe EINECS		:	Listed
Japan ENCS		:	Not determined
Korea KECI		:	Not determined
Philippines PICCS		:	Not determined

:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.