

MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 7 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	11150FSC NYW WHITE MB # 8222
Product code	:	FO00000541
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Arsenic	7440-38-2	0.1 - 1
Antimony trioxide	1309-64-4	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: May cause eye/skin irritation.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	



MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

Medical Conditions	: None known.
Aggravated by Exposure:	. None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature	 No data available. No data available. Not applicable.
Suitable extinguishing media Special Fire Fighting Procedures	 Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

				Print	Page 3 Date 11/4/2
	P		ls, ducts,	ombustible or toxic res and other surfaces to n	
Storage		eep containers dry an ad contamination. Sto		closed to avoid moistur	re absorption
8. 1	EXPOSURE	CONTROLS / PER	SONAL I	PROTECTION	
Respiratory protection	: 0	nder normal handling	conditio	ns a respirator is not re	quired.
Eye/Face Protection	: S	afety glasses with side	e-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations				industrial hygiene and t the end of workday.	safety practice
Engineering measures Exposure limit(s)		eat only in areas with ppropriate exhaust ver		ate exhaust ventilation. It machinery.	Provide
a	Value	Exposure tim	e	Exposure type	
Components				og Sh	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb	OSHA Z1
	0.5 mg/m3 0.01	PEL: Time Weighted Av	verage	as As	
Antimony trioxide	0.5 mg/m3	PEL:	U		OSHA Z1
Antimony trioxide Arsenic	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3	PEL: Time Weighted Av (TWA): Time Weighted Av	verage	as As	OSHA Z1 ACGIH
Antimony trioxide Arsenic	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC	verage	as As PERTIES	OSHA Z1 ACGIH
Antimony trioxide Arsenic Arsenic	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3 9. PHYSIC : Liqui	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC	rerage AL PRO Evapor	as As PERTIES ation rate : No	OSHA Z1 ACGIH OSHA
Antimony trioxide Arsenic Arsenic Form Appearance Color	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3 9. PHYSIC : Liqui : Visco : WHI	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC id Dus, Liquid TE	verage AL PRO Evapor Specifi Bulk de	as As PERTIES ation rate : No c Gravity : No ensity : No	OSHA Z1 ACGIH OSHA t established t determined t applicable.
Antimony trioxide Arsenic Arsenic Form Appearance Color Odor	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3 9. PHYSIC : Liqui : Visco : WHI : Very	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC id pus, Liquid TE faint	AL PRO Evapor Specifi Bulk de Vapor	as As PERTIES ation rate : No c Gravity : No ensity : No pressure : No	t established t determined t determined t determined
Antimony trioxide Arsenic Arsenic Form Appearance Color Odor Melting point/range	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3 9. PHYSIC : Liqui : Visco : WHI : Very : Not a	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC id ous, Liquid TE faint applicable	verage AL PRO Evapor Specifi Bulk de Vapor Vapor	as As PERTIES ation rate : No c Gravity : No ensity : No pressure : No density : No	t established t determined t determined t determined t determined
Antimony trioxide Arsenic Arsenic Form Appearance Color Odor	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3 9. PHYSIC : Liqui : Visco : WHI : Very : Not a	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC id pus, Liquid TE faint applicable applicable	AL PRO Evapor Specifi Bulk de Vapor	as As PERTIES ation rate : No c Gravity : No ensity : No pressure : No density : No	t established t determined t determined t determined
Antimony trioxide Arsenic Arsenic Form Appearance Color Odor Melting point/range Boiling Point:	0.5 mg/m3 0.01 mg/m3 0.01 mg/m3 9. PHYSIC : Liqui : Visco : WHI : Very : Not a : Imm	PEL: Time Weighted Av (TWA): Time Weighted Av (TWA): CAL AND CHEMIC id pus, Liquid TE faint applicable applicable	AL PRO Evapor Specifi Bulk de Vapor Vapor pH	as As PERTIES ation rate : No c Gravity : No ensity : No pressure : No density : No : No	t established t determined t determined t determined t determined



MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

Version Number 1.0 Revision Date 06/10/2002		Page 4 of 7 Print Date <i>11/4/2011</i>
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7440-38-2	Arsenic	Systemic effects	Skin, Respiratory system,
			Liver, Kidney, heart or
			circulatory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7440-38-2	Arsenic	Oral LD50	763 mg/kg	rat
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
7440-38-2	Arsenic	yes	1	1
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.



MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

Version Number 1.0 Revision Date 06/10/2002 Page 5 of 7 Print Date 11/4/2011

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Arsenic 7440-38-2 Trivalent compounds are corrosive to skin. Acute effects are due to severe inflammation of mucous membrane while chronic effects include peripheral neuritis, perforation for the nasal septum and mild tracheobronchitis.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.			
Bioaccumulation Potential	: No data available.			
Additional advice	: No data available.			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
	14. TRANSPORT INFORMATION			
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.			
ICAO/IATA	: Not regulated for transportation.			
IMO / IMDG	: Not regulated for transportation.			
	15. REGULATORY INFORMATION			
US Regulations:				



MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

Version Number 1.0 Revision Date 06/10/2002 Page 6 of 7 Print Date 11/4/2011

OSHA Status

: Classified as hazardous based on components.

TSCA Status

: All components of this product are listed on the TSCA inventory or are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
				Mixture/Product
Arsenic	7440-38-2	0.10	11bs	922 LB

California Proposition 65

: WARNING! This product contains a chemical known in the State of California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	35.99
ARSENIC	7440-38-2	0.10
ZINC COMPOUNDS	1314-98-3	41.99

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-64-4	
7440-38-2	
8052-41-3	

DSL

: Listed.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Listed.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.



MATERIAL SAFETY DATA SHEET

11150FSC NYW WHITE MB # 8222

Version Number 1.0 Revision Date 06/10/2002 Page 7 of 7 Print Date 11/4/2011

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.