

MATERIAL SAFETY DATA SHEET

STAN-TONE 12PC02 YELLOW

Version Number 1.0 Page 1 of 6
Revision Date 10/14/2002 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : STAN-TONE 12PC02 YELLOW

Product code : FO00000577 Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Di(2-ethylhexyl)phthalate	117-81-7	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions : None known.

Aggravated by Exposure:

1/6



MATERIAL SAFETY DATA SHEET

STAN-TONE 12PC02 YELLOW

 Version Number 1.0
 Page 2 of 6

 Revision Date 10/14/2002
 Print Date 11/6/2011

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist, or in all cases of

doubt, seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Seek medical

attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available.

Flammable Limits

Upper explosion limit : No data available.

Lower explosion limit : No data available.

Autoignition temperature : Not applicable.

Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: None

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper

disposal methods.

7. HANDLING AND STORAGE

Handling : Heat only in areas with appropriate exhaust ventilation. Prolonged

heating may result in product degradation.



MATERIAL SAFETY DATA SHEET

STAN-TONE 12PC02 YELLOW

Page 3 of 6 Version Number 1.0 Print Date 11/6/2011 Revision Date 10/14/2002

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection Under normal handling conditions a respirator may not be required.

Eye/Face Protection Safety glasses with side-shields.

Hand protection Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene : Handle in accordance with good industrial hygiene and safety practice.

Considerations Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Di(2-ethylhexyl)phthal	5 mg/m3	Time Weighted Average	Vapor.	ACGIH
ate		(TWA):		
Di(2-ethylhexyl)phthal	5 mg/m3	PEL:	Vapor.	OSHA Z1
ate				

9. PHYSICAL AND CHEMICAL PROPERTIES

: Liquid Not established Form Evaporation rate Not determined

: Liquid, Viscous liquid Appearance Specific Gravity

dispersion

Color : YELLOW Bulk density Not applicable. Odor : Very faint Vapor pressure : Not determined Melting point/range : Not applicable Vapor density : Heavier than air. Boiling Point: : Not applicable : Not determined pН

Water solubility : Immiscible

10. STABILITY AND REACTIVITY

Stability Stable.

Hazardous Polymerization Will not occur.

Keep away from oxidizing agents and open flame. To avoid thermal Conditions to avoid

decomposition, do not overheat.



MATERIAL SAFETY DATA SHEET

STAN-TONE 12PC02 YELLOW

 Version Number 1.0
 Page 4 of 6

 Revision Date 10/14/2002
 Print Date 11/6/2011

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system, Liver, central nervous system, Skin, digestive system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
117-81-7	Di(2-ethylhexyl)phthalate	no	no	2

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

STAN-TONE 12PC02 YELLOW

 Version Number 1.0
 Page 5 of 6

 Revision Date 10/14/2002
 Print Date 11/6/2011

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO / IMDG : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
				Mixture/Product
Di(2-ethylhexyl)ph	117-81-7	68.8000	100 lbs	145 LB
thalate				

California Proposition : WARNING! This product contains a chemical known in the State of



MATERIAL SAFETY DATA SHEET

STAN-TONE 12PC02 YELLOW

 Version Number 1.0
 Page 6 of 6

 Revision Date 10/14/2002
 Print Date 11/6/2011

65

California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
DI(2-ETHYLHEXYL)PHTHALATE	117-81-7	68.80
(DEHP)		

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No. 117-81-7

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.