

MATERIAL SAFETY DATA SHEET

15325FLIS REFLECT PREMIUM MET PLATINUM

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	15325FLIS REFLECT PREMIUM MET PLATINUM
Product code	:	FO0000636
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET

15325FLIS REFLECT PREMIUM MET PLATINUM

Version Number 1.0 Revision Date 06/10/2002 Page 2 of 6 Print Date 11/4/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases o doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize



MATERIAL SAFETY DATA SHEET

15325FLIS REFLECT PREMIUM MET PLATINUM

sion Date 06/10/2002			Print [Page 3 2/4/2	
	ac	ccumulation of these material	s.		
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.			absorption	
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: Under normal handling conditions a respirator is not required.				
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: P:	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.				
	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Engineering measures				FIOVIDE	
Engineering measures Exposure limit(s)				riovide	
Exposure limit(s)		ppropriate exhaust ventilation	at machinery.	List:	
	aı	ppropriate exhaust ventilation Exposure time Time Weighted Average			
Exposure limit(s) Components	ar Value	ppropriate exhaust ventilation Exposure time	at machinery.	List:	
Exposure limit(s) Components	ap Value 10 mg/m3	Exposure time Time Weighted Average (TWA): Time Weighted Average	at machinery. Exposure type Dust.	List: ACGIH ACGIH	
Exposure limit(s) Components Aluminum	ar Value 10 mg/m3 5 mg/m3	ppropriate exhaust ventilation Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA):	Exposure type Dust. Welding fume. as Al	List: ACGIH ACGIH OSHA Z1	
Exposure limit(s) Components Aluminum	ar Value 10 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	ppropriate exhaust ventilation Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	 at machinery. Exposure type Dust. Welding fume. as Al Total dust. as Al Respirable dust. as Al 	List: ACGIH ACGIH OSHA Z1	
Exposure limit(s) Components Aluminum	ap Value 10 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3 9. PHYSIC : Liqui : Visco : GRE : Very : Not a	Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: PEL: PEL: Value Y Bulk / faint Vapo applicable pH	Exposure type Dust. Welding fume. as Al Total dust. as Al Respirable dust. as Al OPERTIES oration rate : Not a fic Gravity : Not a r pressure : Not a r density : Not a r density : Not a	List: ACGIH ACGIH OSHA Z1	
Exposure limit(s) Components Aluminum Aluminum Form Appearance Color Odor Melting point/range Boiling Point:	ap Value 10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : GRE : Very : Not a : Not a : Immi	Exposure time Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: PEL: PEL: Value Y Bulk / faint Vapo applicable pH	Exposure type Dust. Welding fume. as Al Total dust. as Al Respirable dust. as Al OPERTIES oration rate : Not a fic Gravity : Not a r pressure : Not a : Not a : Not a	List: ACGIH ACGIH OSHA Z1 OSHA Z1 OSHA Z1 determined applicable. determined determined	



MATERIAL SAFETY DATA SHEET

15325FLIS REFLECT PREMIUM MET PLATINUM

Version Number 1.0 Revision Date 06/10/2002		Page 4 of 6 Print Date 11/4/2011
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
	11. '	TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	e Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system
	12 ECOLO	GICAL INFORMATIO	N
	12. ECOLU	GICAL INFORMATIO	1
Persistence and degrad	ability : Not read	ily biodegradable.	
Environmental Toxicity : Environmental t whole.		nental toxicity has not bee	n established for this mixture as a
Bioaccumulation Poten	paccumulation Potential : No data available.		
Additional advice : No data avai		available.	
	13. DISPOS	SAL CONSIDERATION	IS
Product	generator classifica	r of waste material has the	red to disposal or incineration. The responsibility for proper waste sposal in accordance with and local regulations.
Contaminated packagin	packaging : Recycling is preferred when possible. The generator of waste mathematical has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincia and local regulations.		aste classification, transportation
	14 TRAN	SPORT INFORMATION	N



MATERIAL SAFETY DATA SHEET

15325FLIS REFLECT PREMIUM MET PLATINUM

sion Number 1.0 ision Date 06/10/2002			Page 5 Print Date 11/4/2
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated	for transportation.	
ICAO/IATA	: Not regulated	for transportation.	
IMO / IMDG	: Not regulated	for transportation.	
	15. REGULATO	RY INFORMATIC	DN
US Regulations:			
OSHA Status	: Classified as h	azardous based on co	omponents.
TSCA Status	: All component exempt.	ts of this product are	listed on the TSCA inventory or ar
US. EPA CERCLA Hazardou	s Substances (40 CFR	302)	
Not applicable			
Not applicable California Proposition 65 SARA Title III Section 313 T	California to c		s a chemical known in the State of
California Proposition 65 SARA Title III Section 313 T	California to c oxic Chemicals:	ause cancer.	
California Proposition 65 SARA Title III Section 313 T Chemical Nan	California to c oxic Chemicals:		s a chemical known in the State of Weight % 3.23
California Proposition 65 SARA Title III Section 313 T Chemical Nan	California to c oxic Chemicals:	ause cancer.	Weight %
California Proposition 65 SARA Title III Section 313 T Chemical Nan ALUMINUM	California to c Foxic Chemicals: ne (FUME OR DUST)	ause cancer.	Weight %
California Proposition 65 SARA Title III Section 313 T <u>Chemical Nan</u> <u>ALUMINUM</u> Canadian Regulations:	California to c foxic Chemicals: ne (FUME OR DUST)	ause cancer.	Weight %
California Proposition 65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classification	California to c foxic Chemicals: ne (FUME OR DUST)	ause cancer.	Weight %
California Proposition 65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7429-90-5	California to c foxic Chemicals: ne (FUME OR DUST)	ause cancer.	Weight %
California Proposition 65 SARA Title III Section 313 T Chemical Nan ALUMINUM Canadian Regulations: WHMIS Classificatio WHMIS Ingredient Di CAS-No. 7429-90-5 75-01-4	California to c foxic Chemicals: ne (FUME OR DUST) n : D2B sclosure List	ause cancer.	Weight %



MATERIAL SAFETY DATA SHEET

15325FLIS REFLECT PREMIUM MET PLATINUM

Version Number 1.0 Revision Date 06/10/2002 Page 6 of 6 Print Date 11/4/2011

China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.