PolvOne

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014 Page 1 of 8 Print Date 3/13/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE 15PEP02 ORANGE
Product code	:	FO00000658
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	•	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Aluminum oxide	1344-28-1	1 - 5
Antimony trioxide	1309-64-4	1 - 5
Barium	7440-39-3	1 - 5
Molybdate orange (Lead chromate pigment)	12656-85-8	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion Eyes Skin	 May be harmful if swallowed. May cause eye and skin irritation. Experience shows no unusual dermatitis hazard from routine handling.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014 Page 2 of 8 Print Date 3/13/2014

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014

Page 3 of 8 Print Date 3/13/2014

Handling	:	Heat only in areas with appropriate exhaust ventilation. Prolonged heating may result in product degradation.	
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.	
8. EXPOS	SUI	RE CONTROLS/PERSONAL PROTECTION	
Respiratory protection	:	Under normal handling conditions a respirator may not be required.	
Eye/Face Protection	:	Safety glasses with side-shields	
Hand protection	:	Protective gloves	
Skin and body protection	:	Long sleeved clothing	
Additional Protective Measures	:	Safety shoes	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	
Exposure limit(s)			

PolyOne

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014 Page 4 of 8 Print Date 3/13/2014

Components	Value	Exposure time	Exposure type	List:
Aluminum oxide	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
Antimony trioxide	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3	Recommended exposure limit (REL):	as Sb	NIOSH
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	OSHA Z1A
Barium	0.5 mg/m3	Time Weighted Average (TWA):	as Ba	ACGIH
Molybdate orange (Lead chromate pigment)	0.5 mg/m3	Recommended exposure limit (REL):	as Cr	NIOSH
	0.5 mg/m3	PEL:	as Cr	OSHA Z1
	0.005 mg/m3	Time Weighted Average (TWA):		OSHA
	0.0025 mg/m3	OSHA Action level:		OSHA
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	ACGIH
	0.05 mg/m3	Time Weighted Average (TWA):		OSHA
	0.03 mg/m3	OSHA Action level:		OSHA
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	OSHA Z1A
	0.15 mg/m3	Time Weighted Average (TWA):	Dust and fume. as Pb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility liquid
liquid, Viscous liquid dispersion
ORANGE
very faint
not applicable
not applicable
immiscible Evapouration rate Specific Gravity

Bulk density Vapour pressure Vapour density pH Not establishedNot determined

: Not applicable

Not determinedHeavier than air.

: Not determined

PolvOne

MATERIAL SAFETY DATA SHEET STAN-TONE 15PEP02 ORANGE

Version Number 1.4 Revision Date 03/11/2014

Page 5 of 8 Print Date 3/13/2014

	10. STABILITY AND REACTIVITY	
Stability	: The product is stable if stored and handled as prescribed.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.	
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1344-28-1	Aluminum oxide	Systemic effects	Eyes, Skin, Respiratory
			system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.
7440-39-3	Barium	Irritant	Skin.
12656-85-8	Molybdate orange (Lead	Irritant	Eyes, Skin.
	chromate pigment)		
		Systemic effects	central nervous system (CNS),
			reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat
12656-85-8	Molybdate orange (Lead chromate pigment)	Oral LD50	5,000 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no
12656-85-8	Molybdate orange (Lead	yes	1	no
	chromate pigment)			

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014

Page 6 of 8 Print Date 3/13/2014

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

Additional Health Hazard Information:

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product Contaminated packaging	 Where possible recycling is preferred to disposal or incineration. Th generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014

Page 7 of 8 Print Date 3/13/2014

	15. RE	GULATORY INFO	ORMATIO	N		
JS Regulations:						
OSHA Status	: Cla	sified as hazardous	based on co	mponents.		
TSCA Status		components of this A Inventory.	product are	listed on or	r exempt	from the
JS. EPA CERCLA Hazardou	s Substanc	es (40 CFR 302)				
not applicable						
California Proposition 65	Cal che	RNING! This prod fornia to cause canc nical known to the S r reproductive harm	er., WARN	ING! This	product of	contains a
ARA Title III Section 302 E Inless specific chemicals are	-		is product is	s Not Appli	cable und	der this regu
SARA Title III Section 313 T Jnless specific chemicals are Chemical Name			is product is		cable und leight per	
ALUMINUM OXIDE (FIE	ROUS FO	RMS)	1344-28-1		.00 - 5.00	
ANTIMONY COMPOUNI			1309-64-4	4 1.	.00 - 5.00	0
BARIUM			7440-39-3		.00 - 5.00	
CHROMIUM III COMPOU COMPOUNDSLEAD COM		OMIUM III	12656-85	-8 30	0.00 - 60	0.00
Canadian Regulations:						
National Pollutant Rel	ease Invent					
Chemical Name		CAS-		Weight percent	N	PRI ID#
Aluminum oxide		1344-		1.00 - 5.0		
Antimony trioxide		1309-		1.00 - 5.0	<u>^</u>	

12656-85-8

30.00 - 60.00

Molybdate orange (Lead chromate pigment)

MATERIAL SAFETY DATA SHEET **STAN-TONE 15PEP02 ORANGE**

Version Number 1.4 Revision Date 03/11/2014 Page 8 of 8 Print Date 3/13/2014

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1344-28-1
1309-64-4
7440-39-3
12656-85-8

÷

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.