

MATERIAL SAFETY DATA SHEET

18870SLNS ANSP-TAN-HB

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	18870SLNS ANSP-TAN-HB
Product code	:	FO00000736
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion				
Acute exposure					
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.				
Ingestion	: May be harmful if swallowed.				
Eyes	: May cause eye/skin irritation.				
Skin	: Experience shows no unusual dermatitis hazard from routine handling.				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				
Medical Conditions Aggravated by Exposure:	: None known.				



MATERIAL SAFETY DATA SHEET

18870SLNS ANSP-TAN-HB

Version Number 1.0 Revision Date 06/10/2002 Page 2 of 6 Print Date 11/4/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases doubt, seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If en irritation persists, seek medical attention.	ye
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	эk
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. 	
	. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	νt
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize	



MATERIAL SAFETY DATA SHEET

18870SLNS ANSP-TAN-HB

and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator is not required. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety pr Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : As Sb OSH ORE Form : Liquid Evaporation rate : Not establis Appearance Form : Liquid Specific Gravity : Not determin Color Color : TAN Bulk density : Not applicable								
8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator is not required. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety pr Considerations : Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Adue Exposure time Exposure type Li Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determi Golor <		a	ccumulation of the	se materials	5.			
Respiratory protection : Under normal handling conditions a respirator is not required. Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety pr Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Measures Components Value Exposure time Exposure type Li Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH Orgen : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not establis Odor : TAN Bulk density : Not applicable Melting point/range : Not applicable Vapor density : Not applicable Vapor ressure : Not applicable PH : Not applic	Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.					
Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety pr Considerations : Handle in accordance with good industrial hygiene and safety pr Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : As Sb OSH Operation risk Value Exposure time Exposure type Li Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determi Color : TAN Bulk density : Not applicable Odor : Ver	8. H	XPOSURE	CONTROLS / PI	ERSONAL	PROTECTION			
Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety pr Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH OSH PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not applica Odor : TAN Bulk density : Not applica Boiling Point: : Not applicable pH : Not applicable Water solubility : Immiscible : Not applicable pH <td>Respiratory protection</td> <td>: U</td> <td>nder normal hand</td> <td>ing condition</td> <td>ons a respirator is</td> <td>not rec</td> <td>quired.</td>	Respiratory protection	: U	nder normal hand	ing condition	ons a respirator is	not rec	quired.	
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety pr Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Engineering 0.5 mg/m3 PEL: as Sb OSH Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH Odor : TAN Appearance : Viscous, Liquid Specific Gravity : Not explicable Value Not applicable Valor : Not applicable Boiling Point: : Not applicable Valor : Not applicable Valor : Not applicable Valor : Not applicable Apport : Not applicable Apport : Not applicable PHYSICAL AND CHEMICAL PROPERTIES Not applicable Vapor pressure </td <td>Eye/Face Protection</td> <td>: S</td> <td>afety glasses with</td> <td>side-shields</td> <td>i.</td> <td></td> <td></td>	Eye/Face Protection	: S	afety glasses with	side-shields	i.			
Additional Protective Measures : Safety shoes. General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety pr Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : At the exposure type Li Matimony trioxide 0.5 mg/m3 PEL: as Sb OSH Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determit Color : TAN Bulk density : Not applicable Odor : Very faint Vapor pressure : Not applicable Water solubility : Immiscible <t< td=""><td>Hand protection</td><td>: P</td><td>rotective gloves.</td><td></td><td></td><td></td><td></td></t<>	Hand protection	: P	rotective gloves.					
Measures General Hygiene : Handle in accordance with good industrial hygiene and safety pr Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Keapson in the exposure time Exposure type Li Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH OPHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance Color : TAN Bulk density : Not applica Odor : Very faint Vapor pressure : Not determi Melting point/range : Not applicable Vapor density : Not applica Water solubility : Immiscible : Not applica Heat only explore could be explored to the explored to thexplored to the explored to the explored to	Skin and body protection	: L	ong sleeved clothi	ng.				
Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) 		: S	afety shoes.					
appropriate exhaust ventilation at machinery. Exposure limit(s) Image: Components Value Exposure time Exposure type Li Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determinication of the example is the e							safety practice	
Components Value Exposure time Exposure type Li Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determi Color : TAN Bulk density : Not applica Odor : Very faint Vapor pressure : Not determi Melting point/range : Not applicable Vapor density : Not determi Boiling Point: : Not applicable pH : Not applica Water solubility : Immiscible Immiscible Immiscible Immiscible Itality : Stable. Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the	Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determi Color : TAN Bulk density : Not applica Odor : Very faint Vapor pressure : Not determi Melting point/range : Not applicable Vapor density : Not determi Boiling Point: : Not applicable pH : Not applica Water solubility : Immiscible Immiscible Immiscible Io. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. : Keep away from oxidizing agents and open flame. To avoid the	Exposure limit(s)							
Antimony trioxide 0.5 mg/m3 PEL: as Sb OSH 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determi Color : TAN Bulk density : Not applica Odor : Very faint Vapor pressure : Not determi Melting point/range : Not applicable Vapor density : Not determi Boiling Point: : Not applicable pH : Not applica Water solubility : Immiscible Immiscible Immiscible Io. STABILITY AND REACTIVITY Stability : Stable. Immiscible Katardous Polymerization : Will not occur. : Keep away from oxidizing agents and open flame. To avoid the	Components	Value	Exposure	time	Exposure ty	me	List:	
Form : Liquid Evaporation rate : Not establis Appearance : Viscous, Liquid Specific Gravity : Not determi Color : TAN Bulk density : Not applica Odor : Very faint Vapor pressure : Not determi Melting point/range : Not applicable Vapor density : Not determi Boiling Point: : Not applicable pH : Not applica Water solubility : Immiscible Immiscible Immiscible Stability : Stable. Hazardous Polymerization : Will not occur. : Weep away from oxidizing agents and open flame. To avoid the						<u> </u>	OSHA Z1	
Appearance:Viscous, LiquidSpecific Gravity:Not determitColor:TANBulk density:Not applicaOdor:Very faintVapor pressure:Not determitMelting point/range:Not applicableVapor density:Not determitBoiling Point::Not applicablepH:Not applicaWater solubility:ImmiscibleStability:Stable.:Will not occur.Conditions to avoid:Keep away from oxidizing agents and open flame. To avoid the		9. PHYSIC	CAL AND CHEM	IICAL PRO	OPERTIES			
Appearance:Viscous, LiquidSpecific Gravity:Not determitColor:TANBulk density:Not applicaOdor:Very faintVapor pressure:Not determitMelting point/range:Not applicableVapor density:Not determitBoiling Point::Not applicablepH:Not applicaWater solubility:ImmiscibleStability:Stable.:Will not occur.Conditions to avoid:Keep away from oxidizing agents and open flame. To avoid the	Form	· Liau	id	Evon	ration rata	· Not	astablished	
Color : TAN Bulk density : Not applicad Odor : Very faint Vapor pressure : Not determi Melting point/range : Not applicable Vapor density : Not determi Boiling Point: : Not applicable pH : Not applicable Water solubility : Immiscible								
Odor : Very faint Vapor pressure : Not determine Melting point/range : Not applicable Vapor density : Not determine Boiling Point: : Not applicable pH : Not applicable Water solubility : Immiscible			-					
Melting point/range : Not applicable Vapor density : Not determine Boiling Point: : Not applicable pH : Not applicable Water solubility : Immiscible Immiscible : Not applicable 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the								
Boiling Point: : Not applicable pH : Not applica Water solubility : Immiscible 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the								
Water solubility : Immiscible 10. STABILITY AND REACTIVITY Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the				-	defisity			
Stability : Stable. Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the								
Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the		10. 8	STABILITY AND	REACTIV	VITY			
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid the	Stability	: S	table.					
	Hazardous Polymerizatio	n : V	Vill not occur.					
	Conditions to avoid					e. To a	avoid thermal	
Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid con	Incompatible Materials	: Iı	ncompatible with s	trong acids	and oxidizing age	ents. A	void contact	



MATERIAL SAFETY DATA SHEET

18870SLNS ANSP-TAN-HB

Version Number 1.0 Revision Date 06/10/2002 Page 4 of 6 Print Date 11/4/2011

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products
Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

18870SLNS ANSP-TAN-HB

Persistence and degradability Environmental Toxicity	: N	lot read						
Environmental Toxicity			ily biodegradabl	e.				
		: Environmental toxicity has not been established for this mixture as a whole.						
Bioaccumulation Potential	: N	lo data a	available.					
Additional advice	: N	: No data available.						
	13. I	DISPO	SAL CONSIDE	RATIONS				
Product	g cl	enerator lassifica	r of waste mater ation, transportation	g is preferred to dispo ial has the responsibi ion and disposal in a provincial and local r	ccordance with			
Contaminated packaging	h: ai	as the rend dispo	esponsibility for	proper waste classifi	nerator of waste materi cation, transportation deral, state/provincial			
	14.	TRAN	SPORT INFOR	RMATION				
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: N	lot regu	lated for transpo	ortation.				
ICAO/IATA	: Not regulated for transportation.							
IMO / IMDG	: Not regulated for transportation.							
	15. R	EGUL	ATORY INFO	RMATION				
US Regulations:								
OSHA Status	: C	lassifie	d as hazardous ł	based on components				
TSCA Status		.ll comp xempt.	ponents of this p	roduct are listed on th	e TSCA inventory or a			
US. EPA CERCLA Hazardous	Substa	nces (40	0 CFR 302)					
Chemical Name C	AS-No.		% in Product	RQ for component	RQ for Mixture/Product			
Arsenic 74	140-38-2	2	0.00	11bs	19,608 LB			

California Proposition : WARNING! This product contains a chemical known in the State of



MATERIAL SAFETY DATA SHEET

18870SLNS ANSP-TAN-HB

Version Number 1.0 Revision Date 06/10/2002 Page 6 of 6 Print Date 11/4/2011

65

California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	1.70

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1309-64-4
7440-38-2
1333-86-4
14808-60-7
75-01-4

DSL

: Listed.

National Inventories:

Australia AICS	:	Not determined.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.