PolvOne

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007

Product Use

Page 1 of 7 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	19000MCVFF BLACK
Product code	:	FO00000743
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Alkenes, C12-24, chloro	68527-02-6	10 - 30
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30 - 60
phenylmethylester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007 Page 2 of 7 Print Date 11/27/2011

	No. 1 and a			
Medical Conditions : None known. Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: no data available			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. 			
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all 			
	possible. 6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.			
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007 Page 3 of 7 Print Date 11/27/2011

	7.	HANDLING AND STORAG	JE	
Handling	ft P	Heat only in areas with appropr ume condensates may contain Periodically clean hoods, ducts, ccumulation of these materials	combustible or toxic resid and other surfaces to min	due.
Storage		Keep containers dry and tightly nd contamination. Store in a c		absorption
8.]	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	to personal respiratory protection	ive equipment normally r	equired.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		afety practice
Engineering measures		Ieat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1

	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Silica, amorphous,	0.8 mg/m3	Time Weighted Average		Z3
fumed, crystal-free		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
	_	(TWA):	_	
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):	-	

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color liquidViscous, liquidBLACK

Evaporation rate Specific Gravity Bulk density Not establishedNot determinedNot applicable

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007

.

Odour Melting point/range Boiling Point: Water solubility	: Very faint: Not applicable: Not applicable: Immiscible	Vapour pressure Vapour density pH	Not determinedNot determinedNot applicable
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from ox decomposition, do n	idizing agents and open f not overheat.	lame. To avoid thermal
Incompatible Materials		trong acids and oxidizing lymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen ch smoke are all possib degradation. As a g after one hour at 17	D2), carbon monoxide (C0 loride (HCl), other hazar ble. Prolonged heating m eneral rule of thumb, deg 7 °C (350 °F), after 10 mi s at 232 °C (450 °F).	dous materials, and ay result in product

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

Page 4 o

Page 4 of 7 Print Date 11/27/2011

PolyOne

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007 Page 5 of 7 Print Date 11/27/2011

85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	> 10 gm/kg	rabbit
	phenylmethylester			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical Name OSHA IARC NTP				
	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: no data available
Additional advice	: no data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007			Page 6 of 7 Print Date <i>11/27/2011</i>			
Contaminated packaging	has th and d	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
14. TRANSPORT INFORMATION						
U.S. DOT Classification Proper Shipping Name: Technical Name: Hazard Class / Division UN Number Packing Group Label Required Hazardous Substance Reportable quantity:	9 UN3082 III 9	entally hazardous substar zyl phthalate	nces, liquid, n.o.s.			
ICAO/IATA (air) IMO / IMDG (maritime)		Refer to specific regulation. Refer to specific regulation.				
	15. REG	ULATORY INFORMA	TION			
US Regulations: OSHA Status TSCA Status	: Classi	fied as hazardous based o				
US. EPA CERCLA Hazar	dous Substances	(40 CFR 302)				
Chemical Name	CAS-No.	RQ for component	RQ for Mixture/Product			
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	100 lbs	308 LB			

California Proposition 65

: WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

MATERIAL SAFETY DATA SHEET 19000MCVFF BLACK

Version Number 1.2 Revision Date 04/05/2007 Page 7 of 7 Print Date 11/27/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30.00 - 60.00	37
phenylmethylester			

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1333-86-4	
112945-52-5	
85-68-7	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.