PolvOne

MATERIAL SAFETY DATA SHEET 19854GNS PRO MATCH 1 BLACK

Version Number 1.4 Revision Date 03/11/2014 Page 1 of 6 Print Date 3/13/2014

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152				
Telephone	:	1 (440) 930-1000 or 1 (866) POLYONE		
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	19854GNS PRO MATCH 1 BLACK		
Product code	:	FO0000822		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

Components	CAS-No.	Weight percent
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye and skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne

MATERIAL SAFETY DATA SHEET **19854GNS PRO MATCH 1 BLACK**

Version Number 1.4 Revision Date 03/11/2014 Page 2 of 6 Print Date 3/13/2014

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: no data available
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 no data available no data available Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET 19854GNS PRO MATCH 1 BLACK

sion Date 03/11/2014				Prin	Page 3 t Date 3/13/2		
Handling	fu P	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.					
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.					
8.	EXPOSURE	CONTROLS/P	ERSONAL	PROTECTION			
Respiratory protection	: N	o personal respire	atory protect	ive equipment normally	required.		
Eye/Face Protection	: S	afety glasses with	n side-shields	3			
Hand protection	: P	rotective gloves					
Skin and body protectior	n : L	ong sleeved cloth	iing				
Additional Protective Measures	: S	afety shoes					
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures Exposure limit(s)		eat only in areas ppropriate exhaus		iate exhaust ventilation at machinery.	. Provide		
Componente	Value	Europauro	time	Exposure type	List:		
Components Silica, amorphous,	0.8 mg/m3	Exposure Time Weighte		Exposure type	Z3		
fumed, crystal-free	-	(TWA	A):		_		
	10 mg/m3	Time Weighte (TWA		Inhalable particulate.	MX OEL		
	3 mg/m3	Time Weighte (TWA	0	Respirable dust.	MX OEL		
	9. PHYSIC	CAL AND CHEN	MICAL PRO	OPERTIES			
Forma	, liani	4	Euopo	ouration rate : No	t actablished		
Form Appearance	: liquio · visco	us, liquid	1		ot established ot determined		
Colour	: BLA			-	ot applicable		
Odour	: very				ot determined		
Melting point/range		pplicable			ot determined		
Boiling Point: Water solubility	: not a : immi	pplicable scible	pH	: No	ot applicable		
	10. S	TABILITY AN	D REACTIV	VITY			

PolvOne

MATERIAL SAFETY DATA SHEET 19854GNS PRO MATCH 1 BLACK

Version Number 1.4 Revision Date 03/11/2014 Page 4 of 6 Print Date 3/13/2014

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Environmental toxicity has not been established for this mixture as a whole.
: no data available
: no data available
13. DISPOSAL CONSIDERATIONS
: Where possible recycling is preferred to disposal or incineration. The

PolyOne.

MATERIAL SAFETY DATA SHEET 19854GNS PRO MATCH 1 BLACK

sion Number 1.4 vision Date 03/11/2014	Page 5 c Print Date 3/13/20
	generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO/IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat
SARA Title III Section 313 To	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulat
Canadian Regulations:	

PolyOne

MATERIAL SAFETY DATA SHEET 19854GNS PRO MATCH 1 BLACK

Version Number 1.4 Revision Date 03/11/2014 Page 6 of 6 Print Date 3/13/2014

not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.