

MATERIAL SAFETY DATA SHEET

249CGNS PANTONE(R) 249 C SIMULATION

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	249CGNS PANTONE(R) 249 C SIMULATION
Product code	:	FO0000966
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl phenylmethylester	85-68-7	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET

249CGNS PANTONE(R) 249 C SIMULATION

Version Number 1.0 Revision Date 06/10/2002 Page 2 of 6 Print Date 11/4/2011

Aggravated by Exposure:		
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	:	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	::	No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Contaminants.Unusual Fire/Explosion: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.		
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

249CGNS PANTONE(R) 249 C SIMULATION

ersion Number 1.0 evision Date 06/10/2002			Print	Page 3 of Date 11/4/201		
Handling	fı P	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.				
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: U	Inder normal handling conditio	ns a respirator is not rec	uired.		
		-	-	L		
Eye/Face Protection	: 5	afety glasses with side-shields.				
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	Long sleeved clothing.				
Additional Protective Measures	: S	Safety shoes.				
General Hygiene Considerations		Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Liquid
 Viscous, Liquid
 PURPLE
 Very faint
 Not applicable
 Not applicable
 Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not established
 Not determined
 Not applicable.
 Not determined
 Not determined
 Not applicable.
- 10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET

249CGNS PANTONE(R) 249 C SIMULATION

Version Number 1.0 Revision Date 06/10/2002 Page 4 of 6 Print Date 11/4/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic	Irritant	Eyes, Skin.
	acid, butyl		
	phenylmethylester		
		Systemic effects	Liver, reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.



MATERIAL SAFETY DATA SHEET

249CGNS PANTONE(R) 249 C SIMULATION

Bioaccumulation Potential	: No data	: No data available.			
Additional advice	: No data	a available.			
	13. DISPO	OSAL CONSIDE	ERATIONS		
Product	generat classifie	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	kaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRAN	NSPORT INFOR	RMATION		
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not reg	ulated for transpo	ortation.		
ICAO/IATA	: Not reg	ulated for transpo	ortation.		
IMO / IMDG	: Not reg	ulated for transpo	ortation.		
	15. REGU	LATORY INFO	RMATION		
US Regulations:					
OSHA Status	: Classifi	ed as hazardous l	based on components		
TSCA Status	: All com exempt		roduct are listed on th	e TSCA inventory or a	
US. EPA CERCLA Hazard	ous Substances (4	40 CFR 302)			
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product	
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	3.29	100lbs	3,037 LB	
California Propositi 65	Californ	nia to cause cance	er., WARNING! Thi tate of California to c		



MATERIAL SAFETY DATA SHEET

249CGNS PANTONE(R) 249 C SIMULATION

Version Number 1.0 Revision Date 06/10/2002 Page 6 of 6 Print Date 11/4/2011

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
7440-38-2
1333-86-4
7439-92-1
7631-86-9
85-68-7
75-01-4

DSL

: Listed.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.