

## 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 1 of 21 Print Date 09/03/2019

# SAFETY DATA SHEET

#### **2530-HH-11 CRANBERRY TOUCH UP PAINT**

Section 1. Identification	on	
GHS product identifier Chemical name CAS number Other means of identification Product type	::	2530-HH-11 CRANBERRY TOUCH UP PAINT Mixture Mixture FO00000986 liquid
<u>Relevant identified uses of the subs</u> Product use	tance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

#### **GHS label elements**



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6	Page 2 of 21
Revision Date 08/30/2019	Print Date 09/03/2019

Hazard pictograms	:	
Signal word Hazard statements	:	Warning Causes serious eye irritation. Causes skin irritation. Suspected of causing cancer.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.
Response	:	IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local,
		regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO0000986

#### CAS number/other identifiers

Ingredient name	%	CAS number
Methyl ethyl ketone	25 - 50	78-93-3
Tetrahydrofuran	5 - 10	109-99-9



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 3 of 21 Print Date 09/03/2019

Xylenes (o-, m-, p- isomers)	1 - 3	1330-20-7
Ethyl benzene	0 - 0.3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

**Description of necessary first aid measures** 

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 4 of 21 Print Date 09/03/2019

person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: Adverse symptoms may include the following:
	pain or irritation
	watering
	redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following:
	irritation
	redness
Ingestion	: No specific data.
Indication of immediate medica	l attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Specific in catilities	• No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Firefighting measures

#### Extinguishing media

Suitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $CO_2$ .
Unsuitable extinguishing media	:	None known.



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6	Page 5 of 21
Revision Date 08/30/2019	Print Date 09/03/2019

Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses,
		5/21



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Numbe	er 1.6
Revision Date	08/30/2019

Page 6 of 21 Print Date 09/03/2019

basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# **Section 7. Handling and storage**

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 7 of 21 Print Date 09/03/2019

Ingredient name	Exposure limits
Ethyl benzene	OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm OSHA PEL (1993-06-30) TWA 435 mg/m3 100 ppm NIOSH REL (1994-06-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm ACGIH TLV (2010-12-06) TWA 20 ppm
Xylenes (o-, m-, p- isomers)	OSHA PEL (1993-06-30)           TWA 435 mg/m3 100 ppm           OSHA PEL 1989 (1989-03-01)           TWA 435 mg/m3 100 ppm           STEL 655 mg/m3 150 ppm           ACGIH TLV (1996-05-18)           TWA 434 mg/m3 100 ppm           STEL 651 mg/m3 150 ppm
Tetrahydrofuran	OSHA PEL 1989 (1989-03-01)           TWA 590 mg/m3 200 ppm           STEL 735 mg/m3 250 ppm           OSHA PEL (1993-06-30)           TWA 590 mg/m3 200 ppm           NIOSH REL (1994-06-01)           TWA 590 mg/m3 200 ppm           STEL 735 mg/m3 250 ppm           STEL 700 ppm           STEL 100 ppm
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01)           TWA 590 mg/m3 200 ppm           STEL 885 mg/m3 300 ppm           OSHA PEL (1993-06-30)           TWA 590 mg/m3 200 ppm           NIOSH REL (1994-06-01)           TWA 590 mg/m3 200 ppm           STEL 885 mg/m3 300 ppm           STEL 885 mg/m3 200 ppm           STEL 885 mg/m3 200 ppm           STEL 885 mg/m3 300 ppm           ACGIH TLV (1994-09-01)           TWA 590 mg/m3 200 ppm           STEL 885 mg/m3 300 ppm



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6	Page 8 of 21
Revision Date 08/30/2019	Print Date 09/03/2019

Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper
		8/21



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 9 of 21 Print Date 09/03/2019

fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### Appearance

Physical state	:	liquid [liquid]
Color	-	RED
Odor	-	Not available.
Odor threshold	-	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
	•	
(flammable) limits		Upper: Not available.
	:	<b>Upper:</b> Not available. Not available.
(flammable) limits		
(flammable) limits Vapor pressure		Not available.
(flammable) limits Vapor pressure Vapor density		Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density		Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility		Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water		Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n-		Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water	:	Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature	:	Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature	:	Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available.
(flammable) limits Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n-		Not available. Not available. Not available. Not available. Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid Incompatible materials	:	Keep away from extreme heat and oxidizing agents. Avoid contact with acetal homopolymers and acetyl homopolymers during processing.



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019

Page 10 of 21 Print Date 09/03/2019

Hazardous decomposition	:	Under normal conditions of storage and use, hazardous decomposition
products		products should not be produced.

# Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure			
Ethyl benzene							
	LD50 Oral	Rat	3,500 mg/kg	-			
<b>Remarks - Inhalation:</b>	No applicable toxicity data						
	LD50 Dermal	Rabbit	5,000 mg/kg	-			
Xylenes (o-, m-, p- isomers)							
	LD50 Oral	Rat	4,300 mg/kg	-			
	LC50 Inhalation	Rat	5,000 ppm	4 h			
<b>Remarks - Dermal:</b>	No applicable toxicity data						
Tetrahydrofuran							
	LD50 Oral	Rat	1,650 mg/kg	-			
<b>Remarks - Inhalation:</b>	No applicable toxicity data						
<b>Remarks - Dermal:</b>	No applicable toxicity data						
Methyl ethyl ketone							
	LD50 Oral	Rat	2,737 mg/kg	-			
<b>Remarks - Inhalation:</b>							
	LD50 Dermal	Rabbit	6,480 mg/kg	-			
Conclusion/Summary	: Mixture.Not fully tested.						

**Conclusion/Summary** 

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl benzene	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
Xylenes (o-, m-, p- isomers)	Skin - Mild	Rat		8 hrs	-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 11 of 21 Print Date 09/03/2019

	Q1_1	D-11.1		241	
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
	Eyes - Severe	Rabbit		24 hrs	-
	irritant				
Methyl ethyl ketone	Skin - Mild	Rabbit		24 hrs	-
	irritant				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant				
Conclusion/Summary		•		•	
Skin	: M	ixture.Not full	y tested.		
Eyes		ixture.Not full			
Respiratory		ixture.Not full			
<b>1 0</b>					
<u>Sensitization</u>					
Conclusion/Summary					
Skin	• M	ivture Not full	v tastad		
Respiratory	<ul> <li>Mixture.Not fully tested.</li> <li>Mixture.Not fully tested.</li> </ul>				
Respiratory	• 141	ixture.rvot tun	y tested.		
<b>Mutagenicity</b>					
Conclusion/Summary	: M	ixture.Not full	y tested.		
<b>Carcinogenicity</b>					
Conclusion/Summary	: M	ixture.Not full	v tested.		
Classification					
Product/ingredient	OSHA	IARC	NTP		
name					
Ethyl benzene		2B			
Xylenes (o-, m-, p-		3			
isomers)		5			
Tetrahydrofuran		2B			
<b>-</b>		20			
<u>Reproductive toxicity</u>					
Conclusion/Summary	: M	ixture.Not full	y tested.		
<b>Teratogenicity</b>					



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 12 of 21 Print Date 09/03/2019

Conclusion/Summary :	Mixture.Not fully tested.		
Specific target organ toxicity (single exp	posure)		
Not available.			
<u>Specific target organ toxicity (repeated</u> Not available.	<u>exposure)</u>		
Aspiration hazard			
Product/ingredient name	Result		
Ethyl benzene	ASPIRATION HAZARD - Category 1		
Information on likely routes of exposure	Not available.		
Potential acute health effects			
Eye contact:Inhalation:Skin contact:Ingestion:	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. No known significant effects or critical hazards.		
Symptoms related to the physical, chem	ical and toxicological characteristics		
Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness		
Inhalation :	No specific data.		
Skin contact :	Adverse symptoms may include the following: irritation		
Ingestion :	redness No specific data.		
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Short term exposure			
Potential immediate effects:Potential delayed effects:	Not available. Not available.		
Long term exposure			
Potential immediate effects:Potential delayed effects:	Not available. Not available. 12/21		



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019

Page 13 of 21 Print Date 09/03/2019

#### **Potential chronic health effects**

Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
<b>Developmental effects</b>	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5,242.8 mg/kg
Route	ATE value
Inhalation (gases)	255,493.1 ppm

# Section 12. Ecological information

**Toxicity** 

Product/ingredient name	Result	Species	Exposure
Ethyl benzene			
	Acute LC50 4.2 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute EC50 6.53 Mg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute EC50 2.93 Mg/l Fresh water	Aquatic invertebrates.	48 h
		Daphnia	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
	Acute EC50 4.6 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic	Acute		
plants:			
	Acute EC50 3.6 Mg/l Fresh water	Aquatic plants - Algae	96 h



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 14 of 21 Print Date 09/03/2019

Remarks - Acute - Aquatic plants:	Acute			
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:	Tto applicable toxicity data			
Xylenes (o-, m-, p- isomers)				
	Acute LC50 13.4 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute			
	Acute LC50 8.5 Mg/l Marine water	Aquatic invertebrates.	48 h	
		Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.: Tetrahydrofuran				
	Acute LC50 2,160 Mg/l Fresh	Fish - Fish	96 h	
	water		<b>70</b> II	
Remarks - Acute - Fish:	Acute			
Remarks - Acute - Aquatic	No applicable toxicity data			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:		1	1	
	Chronic NOEC 367 Mg/l Fresh	Fish - Fish	33 d	
	water			
Remarks - Chronic - Fish:	Chronic			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.: Methyl ethyl ketone				
	Acute LC50 3,220 Mg/l Fresh	Fish - Fish	96 h	
	water		>0 II	
Remarks - Acute - Fish:	Acute			
	Acute EC50 5.091 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:		1		
	Acute EC50 > 500 Mg/l Marine	Aquatic plants - Algae	96 h	
	water			
Remarks - Acute - Aquatic	Acute			
plants:	No applicable toxicity date			
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 15 of 21 Print Date 09/03/2019

 Aquatic invertebrates.:
 Image: Conclusion/Summary
 Image: Not available.

 Persistence and degradability
 Image: Not available.
 Image: Not available.

 Conclusion/Summary
 Image: Not available.
 Image: Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Ethyl benzene	3.6	-	low
Xylenes (o-, m-, p- isomers)	3.15	8.10 - 25.90	low
Tetrahydrofuran	0.45	-	low
Methyl ethyl ketone	0.29	-	low

#### Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 16 of 21 Print Date 09/03/2019

Ingredient	CAS #	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	
Tetrahydrofuran	109-99-9	Listed	
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water Proper Shipping Name: Technical Name:	Paint
Hazard Class / Division	3
UN Number	UN1263
Packing Group	II
Label Required	3
International Air ICAO/IATA	Consult mode specific transport rules
International Water IMO/IMDG	Consult mode specific transport rules

# Section 15. Regulatory information

U.S. Federal regulations	:	<ul> <li>United States - TSCA 12(b) - Chemical export notification: None of the components are listed.</li> <li>United States - TSCA 4(a) - Final Test Rules: Not listed</li> <li>United States - TSCA 4(a) - ITC Priority list: Not listed</li> <li>United States - TSCA 4(a) - Proposed test rules: Not listed</li> <li>United States - TSCA 4(f) - Priority risk review: Not listed</li> <li>United States - TSCA 4(f) - Priority risk review: Not listed</li> <li>United States - TSCA 5(a)2 - Final significant new use rules: Not listed</li> <li>United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed</li> <li>United States - TSCA 5(e) - Substances consent order: Not listed</li> <li>United States - TSCA 6 - Final risk management: Not listed</li> <li>United States - TSCA 6 - Proposed risk management: Not listed</li> <li>United States - TSCA 8(a) - Chemical risk rules: Not listed</li> </ul>
--------------------------	---	--



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6	Page 17 of 21
Revision Date 08/30/2019	Print Date 09/03/2019

		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Tetrahydrofuran Quinacridone (C.I. Pigment Violet 19) United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Ethyl benzene Benzene, methyl-
		United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential Chemicals)	:	Listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Tetrahydrofuran	109-99-9	1,000 lb(s) 454 kg
Methyl ethyl ketone	78-93-3	5,000 lb(s) 2,270 kg 2,270 kg 5,000 lb(s)

#### SARA 311/312

**Chemicals**)



## 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 18 of 21 Print Date 09/03/2019

Classification

#### : SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

#### **Composition/information on ingredients**

Name	%	Classification
Methyl ethyl ketone	>= 25 - <= 50	FLAMMABLE LIQUIDS - Category 2
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
Tetrahydrofuran	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 2
		ACUTE TOXICITY - oral - Category 4
		CARCINOGENICITY - Category 2
Xylenes (o-, m-, p- isomers)	>= 1 - <= 3	FLAMMABLE LIQUIDS - Category 2
		ACUTE TOXICITY - inhalation - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
Ethyl benzene	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3
		EYE IRRITATION - Category 2A
		CARCINOGENICITY - Category 2
		ASPIRATION HAZARD - Category 1

#### SARA 313

	Product name	CAS number	%
Form R - Reporting	Ethyl benzene	100-41-4	0 - 0.3
requirements			
	Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3
Supplier notification	Ethyl benzene	100-41-4	0 - 0.3
	Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

:

#### State regulations Massachusetts

None of the components are listed.

18/21



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6	Page 19 of 21
Revision Date 08/30/2019	Print Date 09/03/2019

New York	:	The following components are listed: Ethyl benzene Xylenes (o-, m-, p- isomers) Tetrahydrofuran Methyl ethyl ketone
New Jersey	:	The following components are listed: Methyl ethyl ketone Tetrahydrofuran Xylenes (o-, m-, p- isomers) Ethyl benzene Isopropanol
Pennsylvania	:	The following components are listed: Tetrahydrofuran
		Methyl ethyl ketone
		Ethyl benzene
		Isopropanol
		Xylenes (o-, m-, p- isomers)
		Silica gel

#### California Prop. 65

**WARNING:** This product can expose you to chemicals including Ethyl benzene, which is known to the State of California to cause cancer, and Benzene, methyl-, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Ethyl benzene	No.	No.
Benzene, methyl-	No.	No.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
Inventory list		
Australia	:	Not determined.
Canada	:	All components are listed or exempted.
China	:	Not determined.
		19/21



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 20 of 21 Print Date 09/03/2019

Europe inventory	:	Not determined.
Japan	:	Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

# Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

of Classification and Labelling of
C C
ssociation
erous Goods
ater partition coefficient
for the Prevention of Pollution From
ol of 1978. ("Marpol" = marine
_
1



# 2530-HH-11 CRANBERRY TOUCH UP PAINT

Version Number 1.6 Revision Date 08/30/2019 Page 21 of 21 Print Date 09/03/2019

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.