

MATERIAL SAFETY DATA SHEET

36651MSH 1665 I.K.

Version Number 1.0 Revision Date 06/12/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	36651MSH 1665 I.K.
Product code	:	FO00001173
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5
Diatomaceous earth	61790-53-2	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

36651MSH 1665 I.K.

ion Number 1.0 sion Date 06/12/2002	Page 2 Print Date 11/5/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing





36651MSH 1665 I.K. Page 3 of 6 Version Number 1.0 Print Date 11/5/2011 Revision Date 06/12/2002 fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator may not be required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Diatomaceous earth	10 mg/m3	Time Weighted Average	Inhalable dust.	ACGIH
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	ACGIH
		(TWA):		
Diatomaceous earth	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range : Liquid
: Viscous, Liquid
: ORANGE
: Very faint
: Not applicable

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density Not establishedNot determinedNot applicable.

- : Not determined
- : Not determined



MATERIAL SAFETY DATA SHEET

36651MSH 1665 I.K.

vision Date 06/12/2002			Print Date 11/5/2
Boiling Point: Water solubility	: Not applicable : Immiscible	рН	: Not applicable.
	10. STABILITY AND	REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxi decomposition, do n		open flame. To avoid thermal
Incompatible Materials			idizing agents. Avoid contact copolymers during processing.
Hazardous decomposition products	(NOx), hydrogen ch smoke are all possib degradation. As a g	loride (HCl), other le. Prolonged hea eneral rule of thun 7 °C (350 °F), after	tide (CO), oxides of nitrogen r hazardous materials, and ting may result in product hb, degradation begins to occur r 10 minutes at 204 °C (400 °F) F)

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
61790-53-2	Diatomaceous earth	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The



MATERIAL SAFETY DATA SHEET

36651MS	H 16	65 I	Κ
30031110	II IV	UU I .	/ \.

rsion Number 1.0 vision Date 06/12/2002				Page 5 (Print Date 11/5/2)
	(classification, transport	erial has the responsibil ation and disposal in ac e/provincial and local re	cordance with
Contaminated packaging	1	has the responsibility for	when possible. The gen or proper waste classific nce with applicable fed	
	14	. TRANSPORT INFO	RMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:]	Not regulated for trans	portation.	
ICAO/IATA	:]	Not regulated for trans	portation.	
IMO / IMDG	: 1	Not regulated for trans	portation.	
	15.	REGULATORY INF	ORMATION	
US Regulations:				
OSHA Status	. (Classified as hazardous	based on components.	
			1	
TSCA Status		All components of this exempt.	product are listed on the	e TSCA inventory or are
TSCA Status US. EPA CERCLA Hazard	(exempt.	product are listed on the	TSCA inventory or are
	(exempt. ances (40 CFR 302)	-	RQ for Mixture/Product
US. EPA CERCLA Hazard	ous Substa	exempt. ances (40 CFR 302)	- 	RQ for
US. EPA CERCLA Hazard Chemical Name 1,2-Benzenedicarb oxylic acid, butyl	ous Substa CAS-No 85-68-7	exempt. ances (40 CFR 302) . % in Product 0.20 WARNING! This product California to cause can	RQ for component 100lbs	RQ for Mixture/Product 48,876 LB

MATERIAL SAFETY DATA SHEET





Version Number 1.0 Revision Date 06/12/2002 Print Date 11/5/2011 1333-86-4 7631-86-9 101-02-0 108-05-4 71-36-3 85-68-7 75-01-4 DSL : Listed. National Inventories: Australia AICS Not determined. ÷ China IECS Not determined. · **Europe EINECS** Not determined. : Japan ENCS Not determined. ÷ Korea KECI Not determined. : **Philippines PICCS** : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Page 6 of 6