

MATERIAL SAFETY DATA SHEET

# 40162SPF SOCK RED

Version Number 1.0 Revision Date 06/12/2002 Page 1 of 6 Print Date 11/5/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	40162SPF SOCK RED
Product code	:	FO00001229
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	10 - 30

# **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

## POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# 40162SPF SOCK RED

ion Number 1.0 sion Date 06/12/2002	Page 2 Print Date 11/5/
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing





# 40162SPF SOCK RED

rsion Number 1.0 vision Date 06/12/2002			Print	Page 3 of Date 11/5/201
	Р	ume condensates may contain c eriodically clean hoods, ducts, ccumulation of these materials.	and other surfaces to m	
Storage		Leep containers dry and tightly nd contamination. Store in a co		e absorption
8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: U	Under normal handling conditio	ons a respirator may not	be required.
Eye/Face Protection	: Safety glasses with side-shields.			
Hand protection	: P	: Protective gloves.		
Skin and body protection	: L	: Long sleeved clothing.		
Additional Protective Measures	: Safety shoes.			
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
				0.0771.004

Quartz 0.05 Time Wo	eighted Average R (TWA):	espirable dust.	ACGIH
mg/m3	$(\mathbf{T}\mathbf{W}, \mathbf{A})$ .		
ing/ins	$(\mathbf{I} \mathbf{W} \mathbf{A})$ :		
Quartz 0.1 mg/m3	PEL: R	espirable dust.	OSHA
0.3 mg/m3	PEL:	Total dust.	OSHA

# 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
  : Viscous, Liquid
  : RED
  : Very faint
  : Not applicable
  : Not applicable
  : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not established
  Not determined
  Not applicable.
  Not determined
  Not determined
  Not applicable.

## **10. STABILITY AND REACTIVITY**

3/6



#### MATERIAL SAFETY DATA SHEET

# 40162SPF SOCK RED

Version Number 1.0 Revision Date 06/12/2002 Page 4 of 6 Print Date 11/5/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.



MATERIAL SAFETY DATA SHEET

# 40162SPF SOCK RED

ICAL INFORMATION biodegradable. ntal toxicity has not been established for this mixture as a ilable.
biodegradable. ntal toxicity has not been established for this mixture as a ilable.
ntal toxicity has not been established for this mixture as a
ilable.
L CONSIDERATIONS
ible, recycling is preferred to disposal or incineration. The fwaste material has the responsibility for proper waste on, transportation and disposal in accordance with rederal, state/provincial and local regulations.
s preferred when possible. The generator of waste materionsibility for proper waste classification, transportation 1 in accordance with applicable federal, state/provincial gulations.
ORT INFORMATION
ed for transportation.
ed for transportation.
ed for transportation.
TORY INFORMATION
s hazardous based on components.
ents of this product are listed on the TSCA inventory or a
FR 302)



### MATERIAL SAFETY DATA SHEET

# 40162SPF SOCK RED

Version Number 1.0 Revision Date 06/12/2002	Page 6 of 6 Print Date 11/5/2011			
California Proposition : 65	WARNING! This product contains a chemical known in the State of California to cause cancer.			
Not applicable Canadian Regulations:				
WHMIS Classification :	D2A			
WHMIS Ingredient Disclos	WHMIS Ingredient Disclosure List			
CAS-No. 117-81-7 14808-60-7 107-13-1 75-01-4				
DSL :	Listed.			
National Inventories:				
Australia AICS :	Listed.			
China IECS :	Listed.			
Europe EINECS :	Not determined.			
Japan ENCS :	Not determined.			
Korea KECI :	Listed.			
Philippines PICCS :	Not determined.			
	16. OTHER INFORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.