

MATERIAL SAFETY DATA SHEET

41335GNS NEW MAGENTA

Version Number 1.0 Revision Date 06/12/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	41335GNS NEW MAGENTA
Product code	:	FO00001280
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1 - 5
phenylmethylester		
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye/skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			



MATERIAL SAFETY DATA SHEET

41335GNS NEW MAGENTA

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET

41335GNS NEW MAGENTA

sion Number 1.0 sion Date 06/12/2002			Print	Page 3 Date 11/5/2
	P	ume condensates may contain eriodically clean hoods, ducts ccumulation of these materials	, and other surfaces to m	
Storage		Leep containers dry and tightly nd contamination. Store in a contamination.		e absorption
8. 1		CONTROLS / PERSONAL		
				he required
Respiratory protection	: U	Inder normal handling condition	ons a respirator may not	be required.
Eye/Face Protection	: Sa	afety glasses with side-shields	s.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and		afety practic
Engineering measures		leat only in areas with appropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z
	15 mg/m3	PEL:	Total dust.	OSHA ZI
	9. PHYSI(CAL AND CHEMICAL PRO	OPERTIES	
Form	: Liqui	id Evapo	oration rate : Not	t established
Appearance				t determined
Color	: RED		-	t applicable.
Odor	: Very faint Vapor pressure : Not determin			
Melting point/range	: Not applicable Vapor density : Not determine			
Boiling Point:	Boiling Point:: Not applicablepH: Not applicable			t applicable.
Water solubility	: Imm ³	iscible		
	10. 8	STABILITY AND REACTIV	VITY	
	: S	table.		
Stability				
Stability Hazardous Polymerization		Vill not occur.		



MATERIAL SAFETY DATA SHEET

41335GNS NEW MAGENTA

 Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition products Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), 	Version Number 1.0 Revision Date 06/12/2002		Page 4 of 6 Print Date <i>11/5/2011</i>
 With acetal homopolymers and acetal copolymers during processing. Hazardous decomposition products Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur 	Conditions to avoid	:	
products (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur	Incompatible Materials	:	
and within 5 minutes at 232 °C (450 °F).	1	:	(NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit
	phenylmethylester			

	12	2. ECOLOGICAL INFORMATION
Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available.
Additional advice	:	No data available.
	1	3. DISPOSAL CONSIDERATIONS



MATERIAL SAFETY DATA SHEET

41335GNS NEW MAGENTA

sion Number 1.0 ision Date 06/12/2002				Page 5 Print Date 11/5/2		
Product	generat classifi	tor of waste mater cation, transportat	g is preferred to dispo ial has the responsibil ion and disposal in ac provincial and local re	cordance with		
Contaminated packaging	has the and dis	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRA	NSPORT INFOR	RMATION			
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not reg	gulated for transpo	ortation.			
ICAO/IATA	: Not reg	gulated for transpo	ortation.			
IMO / IMDG	: Not reg	gulated for transpo	ortation.			
	15. REGU	LATORY INFO	RMATION			
OSHA Status TSCA Status US. EPA CERCLA Hazardo	: All con exempt	nponents of this pi t.	based on components.	TSCA inventory or are		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product		
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	3.04	100lbs	3,284 LB		
California Propositio 65	Califor chemic	nia to cause cance	er., WARNING! This tate of California to ca			
_	Califor chemic	nia to cause cance al known in the S	er., WARNING! This tate of California to ca	product contains a		



MATERIAL SAFETY DATA SHEET

41335GNS NEW MAGENTA

Version Number 1.0 Revision Date 06/12/2002 Page 6 of 6 Print Date 11/5/2011

WHMIS Ingredient Disclosure List				
CAS-No. 7440-38-2 1333-86-4 7439-92-1 7631-86-9 85-68-7 75-01-4				
DSL	:	Listed.		
National Inventories:				
Australia AICS	:	Listed.		
China IECS	:	Not determined.		
Europe EINECS	:	Not determined.		
Japan ENCS	:	Not determined.		
Korea KECI	:	Listed.		
Philippines PICCS	:	Listed.		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.