

MATERIAL SAFETY DATA SHEET

# 64616GNS SOFFE NAVY

Version Number 1.1 Revision Date 08/01/2002 Page 1 of 6 Print Date 11/5/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	64616GNS SOFFE NAVY
Product code	:	FO00001774
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1 - 5
phenylmethylester		
Calcium carbonate	1317-65-3	10 - 30

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# 64616GNS SOFFE NAVY

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If exirct irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



## MATERIAL SAFETY DATA SHEET

# 64616GNS SOFFE NAVY

ion Number 1.1 sion Date 08/01/2002				Pri	Page 3 int Date <u>11/5/</u>
	Р	ume condensates may of eriodically clean hoods ccumulation of these m	s, ducts, and		
Storage		Leep containers dry and nd contamination. Sto			ture absorption
8. E	XPOSURE	CONTROLS / PERS	ONAL PR	OTECTION	
Respiratory protection	: U	Inder normal handling	conditions	a respirator may n	ot be required.
Eye/Face Protection	: S	afety glasses with side	-shields.		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance w Vash hands before brea			
Engineering measures		leat only in areas with ppropriate exhaust ven			on. Provide
Exposure limit(s)				·	
Components	Value	Exposure time		Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Ave (TWA):		Total dust.	ACGIH
Calcium carbonate	5 mg/m3 15 mg/m3	PEL: PEL:		Respirable dust. Total dust.	OSHA Z1 OSHA Z1
		CAL AND CHEMICA		DTIES	
	<i><b>7.1115</b></i>				
Form	: Liqu		Evaporati		Not established
Appearance		ous, Liquid	Specific C	•	Not determined
Color	: BLU				Not applicable.
Odor Malting gaint (magazi		faint	Vapor pressure : Not determined		
Melting point/range		applicable	Vapor dei	•	Not determined
Boiling Point: Water solubility	: Not a : Imm	applicable iscible	рН	: 1	Not applicable.
	10. 8	STABILITY AND RE	CACTIVIT	Y	
Stability	: S	table.			



### MATERIAL SAFETY DATA SHEET

# 64616GNS SOFFE NAVY

Version Number 1.1 Revision Date 08/01/2002		Page 4 of 6 Print Date 11/5/2011
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
	11. '	TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit
	phenylmethylester			

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS



## MATERIAL SAFETY DATA SHEET

# 64616GNS SOFFE NAVY

sion Number 1.1 ision Date 08/01/2002				Page 5 Print Date 11/5/2		
Product	genera classif	tor of waste mater ication, transporta	g is preferred to dispo ial has the responsibil tion and disposal in ac provincial and local re	cordance with		
Contaminated packaging	has the and dis	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRA	NSPORT INFOR	RMATION			
U.S. DOT / CA TDG Classification	: Not re	gulated for transpo	ortation.			
ICAO/IATA	: Not reg	gulated for transpo	ortation.			
IMO / IMDG	: Not re	gulated for transpo	ortation.			
	15. REGU	JLATORY INFO	RMATION			
US Regulations:						
OSHA Status	: Classif	fied as hazardous t	based on components.			
TSCA Status	: All con exemp		roduct are listed on the	TSCA inventory or are		
US. EPA CERCLA Hazard	ous Substances (	(40 CFR 302)				
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product		
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	3.39	100 lbs	2,943 LB		
California Propositi 65	Califor chemic	rnia to cause cance	er., WARNING! This tate of California to ca			
Canadian Regulations:						



MATERIAL SAFETY DATA SHEET

# 64616GNS SOFFE NAVY

Page 6 of 6 Version Number 1.1 Revision Date 08/01/2002 Print Date 11/5/2011 WHMIS Classification : D2A WHMIS Ingredient Disclosure List CAS-No. 85-68-7 DSL : Listed. National Inventories: Australia AICS : Listed. China IECS Not determined. : Europe EINECS Not determined. : Japan ENCS Not determined. : Korea KECI : Listed. **Philippines PICCS** : Listed. **16. OTHER INFORMATION** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.