

### MATERIAL SAFETY DATA SHEET

# 714CGNSPL PANTONE(R) 714 C SIMULATION

Version Number 1.1 Revision Date 08/02/2002 Page 1 of 6 Print Date 11/5/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	714CGNSPL PANTONE(R) 714 C SIMULATION
Product code	:	FO00001955
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
1,2-Benzenedicarboxylic acid, butyl	85-68-7	1 - 5
phenylmethylester		
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET

# 714CGNSPL PANTONE(R) 714 C SIMULATION

Version Number 1.1 Revision Date 08/02/2002 Page 2 of 6 Print Date 11/5/2011

Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.		
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: No data available.		
Flammable Limits Upper explosion limit Lower explosion limit	<ul><li>No data available.</li><li>No data available.</li></ul>		
Autoignition temperature Suitable extinguishing media	<ul><li>Not applicable.</li><li>Carbon dioxide blanket, dry powder, foam, Water spray.</li></ul>		
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.		
Unusual Fire/Explosion:May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) uHazards:ire conditions.			
	5. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		



### MATERIAL SAFETY DATA SHEET

# 714CGNSPL PANTONE(R) 714 C SIMULATION

sion Number 1.1 /ision Date 08/02/2002			Print	Page 3 o Date 11/5/20		
Handling	fı P	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.				
Storage		: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8. H	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: U	nder normal handling conditio	ns a respirator may not	be required.		
Eye/Face Protection	: S	afety glasses with side-shields.				
Hand protection	: P	Protective gloves.				
Skin and body protection	: L	: Long sleeved clothing.				
Additional Protective Measures	: S	: Safety shoes.				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1		
	15 mg/m3	PEL:	Total dust.	OSHA Z1		
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
  : Viscous, Liquid
  : ORANGE
  : Very faint
  : Not applicable
  : Not applicable
  : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not establishedNot determinedNot applicable.Not determinedNot determined
- : Not applicable.

#### **10. STABILITY AND REACTIVITY**

3/6



#### MATERIAL SAFETY DATA SHEET

# 714CGNSPL PANTONE(R) 714 C SIMULATION

Version Number 1.1 Revision Date 08/02/2002 Page 4 of 6 Print Date 11/5/2011

Stabilit	у	:	Stable.
Hazard	ous Polymerization	:	Will not occur.
Conditi	ons to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incomp	atible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazard product	ous decomposition ts	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

# 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.



# MATERIAL SAFETY DATA SHEET

# 714CGNSPL PANTONE(R) 714 C SIMULATION

Bioaccumulation Potential	: No data	a available.			
Additional advice	: No data	a available.			
	13. DISPO	DSAL CONSIDE	ERATIONS		
Product	generat classifi	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	<ul> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> </ul>				
	14. TRAN	NSPORT INFOR	RMATION		
U.S. DOT / CA TDG Classification	: Not reg	ulated for transpo	ortation.		
ICAO/IATA	: Not regulated for transportation.				
IMO / IMDG	: Not regulated for transportation.				
	15. REGU	LATORY INFO	RMATION		
US Regulations:					
OSHA Status	: Classifi	ed as hazardous h	based on components.		
TSCA Status		ponents of this p	-	TSCA inventory or ar	
US. EPA CERCLA Hazard	ous Substances (4	40 CFR 302)			
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product	
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	3.30	100 lbs	3,026 LB	
California Propositi 65	Califor	nia to cause cance	er., WARNING! This tate of California to ca		



MATERIAL SAFETY DATA SHEET

# 714CGNSPL PANTONE(R) 714 C SIMULATION

Version Number 1.1 Revision Date 08/02/2002 Page 6 of 6 Print Date 11/5/2011

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

	CAS-No. 85-68-7		
DSL		:	Listed.
National Inver	ntories:		
Austra	lia AICS	:	Listed.
China	IECS	:	Not determined.
Europe	e EINECS	:	Not determined.
Japan	ENCS	:	Not determined.

Korea KECI : Listed.

Philippines PICCS : Not determined.

# **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.