

MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

Version Number 1.0 Revision Date 06/12/2002 Page 1 of 7 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	72136SPC TEAL 322/42
Product code	:	FO00001972
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Diatomaceous earth	61790-53-2	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion	
Acute exposure		
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.	
Ingestion	: May be harmful if swallowed.	
Eyes	: May cause eye/skin irritation.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	



MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde
Hazards	fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

Version Number 1.0 Revision Date 06/12/2002	Page 3 of 7 Print Date <i>11/5/2011</i>
Storage :	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	Under normal handling conditions a respirator may not be required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Diatomaceous earth	10 mg/m3	Time Weighted Average	Inhalable dust.	ACGIH
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	ACGIH
		(TWA):		
Diatomaceous earth	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range

: Liquid : Viscous, Liquid : AQUA : Very faint : Not applicable

Evaporation rate Evaporation rateImage: Specific GravityNot determinedBulk densityNot applicable. Bulk density:Not applicable.Vapor pressure:Not determinedVapor density:Not determined

: Not established



MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

Version Number 1.0 Revision Date 06/12/2002			Page 4 of 7 Print Date 11/5/2011
Boiling Point: Water solubility	: Not applicable : Immiscible	рН	: Not applicable.
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from o decomposition, do		open flame. To avoid thermal
Incompatible Materials			dizing agents. Avoid contact opolymers during processing.
Hazardous decomposition products	(NOx), hydrogen of smoke are all poss degradation. As a after one hour at 1	chloride (HCl), other ible. Prolonged heat general rule of thum	ide (CO), oxides of nitrogen hazardous materials, and ting may result in product b, degradation begins to occur 10 minutes at 204 °C (400 °F), F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
61790-53-2	Diatomaceous earth	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:



MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

Version Number 1.0 Revision Date 06/12/2002 Page 5 of 7 Print Date 11/5/2011

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Environmental Toxicity : Envi whol Bioaccumulation Potential : No d Additional advice : No d 13. DIS Product : Whe gene class appli Contaminated packaging : Recy has t and c and l	eadily biodegradable. conmental toxicity has not been established for this mixture as a e. ata available. ata available. POSAL CONSIDERATIONS re possible, recycling is preferred to disposal or incineration. The
whole Bioaccumulation Potential : No de Additional advice : No de 13. DIS Product : When gene class appli Contaminated packaging : Recy has t and de and le 14. TR	e. ata available. ata available. POSAL CONSIDERATIONS
Additional advice : No d I3. DIS Product : Whe gene class appli Contaminated packaging : Recy has t and c and l I11. In the second se	ata available. POSAL CONSIDERATIONS
13. DIS Product : Whe gene class appli Contaminated packaging : Recy has t and c and l 14. TR	POSAL CONSIDERATIONS
Product : Whe gene class appli Contaminated packaging : Recy has t and c and l 14. TR	
gene class appli Contaminated packaging : Recy has t and c and l 14. TR	e possible, recycling is preferred to disposal or incineration. The
has t and c and l 14. TR	ator of waste material has the responsibility for proper waste fication, transportation and disposal in accordance with cable federal, state/provincial and local regulations.
	cling is preferred when possible. The generator of waste material ne responsibility for proper waste classification, transportation isposal in accordance with applicable federal, state/provincial pcal regulations.
	ANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. : Not a Classification (Non-bulk ground)	egulated for transportation.
ICAO/IATA : Not a	egulated for transportation.



MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

sion Date 06/12/2002	Print Date 11/5/2
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or ar exempt.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Proposition 65	n : WARNING! This product contains a chemical known in the State of California to cause cancer.
Not applicable Canadian Regulations:	
WHMIS Classification	on : D2A
WHMIS Ingredient D	isclosure List
CAS-No. 1333-86-4 7631-86-9 101-02-0 108-05-4 75-01-4	
DSL	: Listed.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.



MATERIAL SAFETY DATA SHEET

72136SPC TEAL 322/42

Version Number 1.0 Revision Date 06/12/2002 Page 7 of 7 Print Date 11/5/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.