# MATERIAL SAFETY DATA SHEET 73750SLNS YOGA MAT-PMS 3288C

Version Number 1.1 Revision Date 09/02/2003 Page 1 of 6 Print Date 11/12/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	73750SLNS YOGA MAT-PMS 3288C
Product code	:	FO00002007
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



# MATERIAL SAFETY DATA SHEET 73750SLNS YOGA MAT-PMS 3288C

Version Number 1.1 Revision Date 09/02/2003 Page 2 of 6 Print Date 11/12/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, water spray.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	<ul> <li>Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.</li> </ul>
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



# MATERIAL SAFETY DATA SHEET 73750SLNS YOGA MAT-PMS 3288C

Version Number 1.1 Revision Date 09/02/2003 Page 3 of 6 Print Date 11/12/2011

Storage	:	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPO	<b>)</b> SUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

# : Liquid : Viscous, Liquid : GREEN : Very faint : Not applicable : Not applicable : Immiscible

#### Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH

# Not established Not determined Not applicable. Not determined Not determined Not determined Not applicable.

### **10. STABILITY AND REACTIVITY**

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact



# MATERIAL SAFETY DATA SHEET 73750SLNS YOGA MAT-PMS 3288C

Version Number 1.1 Revision Date 09/02/2003 Page 4 of 6 Print Date 11/12/2011

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition<br/>products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen<br/>(NOx), hydrogen chloride (HCl), other hazardous materials, and<br/>smoke are all possible. Prolonged heating may result in product<br/>degradation. As a general rule of thumb, degradation begins to occur<br/>after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),<br/>and within 5 minutes at 232 °C (450 °F).

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit

### Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Environmental toxicity has not been established for this mixture as a whole.
: No data available.
: No data available.
13. DISPOSAL CONSIDERATIONS
: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
-

PolyOne

# MATERIAL SAFETY DATA SHEET 73750SLNS YOGA MAT-PMS 3288C

Version Number 1.1 Revision Date 09/02/2003 Page 5 of 6 Print Date 11/12/2011

Contaminated packaging	:	Recycling is preferred has the responsibility and disposal in accor and local regulations	for proper waster dance with applie	e classification,	transportation
	1	4. TRANSPORT INF	FORMATION		
U.S. DOT Classification	:	Refer to specific regu	ilation.		
ICAO/IATA	:	Refer to specific regu	ulation.		
IMO / IMDG	:	Refer to specific regu	ulation.		
	15	. REGULATORY IN	FORMATION		
US Regulations:					
OSHA Status	:	Classified as hazardo	ous based on com	ponents.	
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)			
Not applicable					
California Proposition 65	:	WARNING! This pr California to cause ca		chemical know	n to the State of
SARA Title III Section 302 Ex	trem	ely Hazardous Substar	ice		
Not applicable					
SARA Title III Section 313 To	xic (	Chemicals:			
Not applicable Canadian Regulations:					
National Pollutant Relea	ase I:	ventory (NPRI)			
Chemical Name			CAS-No.	Weight %	NPRI ID#
Aluminum oxide			1344-28-1	0.13	13

*PolyOne* 

## MATERIAL SAFETY DATA SHEET 73750SLNS YOGA MAT-PMS 3288C

Version Number 1.1 Revision Date 09/02/2003 Page 6 of 6 Print Date 11/12/2011

	WHMIS Classification	:	D2A	
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
Natio	onal Inventories:			
	Australia AICS	:	Listed.	
	China IECS	:	Listed.	
	Europe EINECS	:	Not determined.	
	Japan ENCS	:	Not determined.	
	Korea KECI	:	Not determined.	
	Philippines PICCS	:	Listed.	
			16. OTHER INFORMATION	1

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.