

MATERIAL SAFETY DATA SHEET

### 78660MP GREEN 5

Version Number 1.0 Revision Date 06/12/2002 Page 1 of 6 Print Date 11/5/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	78660MP GREEN 5
Product code	:	FO00002106
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Calcium carbonate	471-34-1	5 - 10
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# 78660MP GREEN 5

sion Number 1.0 ision Date 06/12/2002	Page 2 Print Date 11/5/2
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive</li> </ul>
Procedures Unusual Fire/Explosion Hazards	<ul><li>pressure mode should be worn to prevent inhalation of airborne contaminants.</li><li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.</li></ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET

# **78660MP GREEN 5**

Version Number 1.0 Revision Date 06/12/2002		Page 3 of 6 Print Date 11/5/2011
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOS	UR	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

#### Exposure limit(s)

Components	Value	Exposure time Exposure type		List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color

: Liquid : Viscous, Liquid : GREEN

Bulk density

Evaporation rate:Not establishedSpecific Gravity:Not determined : Not applicable.

### MATERIAL SAFETY DATA SHEET

## **78660MP GREEN 5**

PolyOne.

10000MI GILLING			
Version Number 1.0 Revision Date 06/12/2002			Page 4 of 6 Print Date <i>11/5/2011</i>
Odor Melting point/range Boiling Point: Water solubility	<ul> <li>Very faint Vapor pressure</li> <li>Not applicable Vapor density</li> <li>Not applicable pH</li> <li>Immiscible</li> </ul>		<ul><li>Not determined</li><li>Not determined</li><li>Not applicable.</li></ul>
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open a not overheat.	flame. To avoid thermal
Incompatible Materials		strong acids and oxidizing olymers and acetal copoly	
Hazardous decomposition products	(NOx), hydrogen c smoke are all possi degradation. As a after one hour at 17		rdous materials, and

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
471-34-1		Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability

: Not readily biodegradable.

**Environmental Toxicity** 

: Environmental toxicity has not been established for this mixture as a



### MATERIAL SAFETY DATA SHEET

# 78660MP GREEN 5

	whole					
Bioaccumulation Potential	: No dat	ta available.				
Additional advice	: No dat	ta available.				
	13. DISP	OSAL CONSIDE	ERATIONS			
Product	genera classif	tor of waste mater ication, transporta	g is preferred to dispo ial has the responsibil tion and disposal in ac provincial and local re	cordance with		
Contaminated packaging	has the and di	e responsibility for	hen possible. The gen proper waste classific ce with applicable fed			
	14. TRA	NSPORT INFOR	RMATION			
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not re	gulated for transpo	ortation.			
ICAO/IATA	: Not re	: Not regulated for transportation.				
IMO / IMDG	: Not re	gulated for transpo	ortation.			
	15. REGU	JLATORY INFO	RMATION			
US Regulations:						
OSHA Status	: Classi	fied as hazardous l	based on components.			
TSCA Status	: All con exemp		roduct are listed on the	TSCA inventory or ar		
US. EPA CERCLA Hazard	ous Substances	(40 CFR 302)				
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product		
1,2-Benzenedicarb oxylic acid, butyl phenylmethylester	85-68-7	0.22	100lbs	43,687 LB		
California Propositi	on · WAR	NING! This produ	act contains a chemica	l known in the State of		

MATERIAL SAFETY DATA SHEET

## 78660MP GREEN 5

Version Number 1.0 Revision Date 06/12/2002 PolyOne

Page 6 of 6 Print Date 11/5/2011

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
7631-86-9
85-68-7
75-01-4
00 00 1

DSL

: Listed.

National Inventories:

Australia AICS	: Not determined.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Not determined.

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.