

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****STAN-TONE 82SP00 RED**Version Number 1.3
Revision Date 01/23/2008Page 1 of 8
Print Date 12/3/2011**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
8155 Cobb Center Drive, Kennesaw, GA 30152Telephone : Product Stewardship (770) 590-3500 x.3563
Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).Product name : STAN-TONE 82SP00 RED
Product code : FO00002207
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

Components	CAS-No.	Weight %
Ethyl benzene	100-41-4	0.1 - 1
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Iron oxide	1309-37-1	60 - 100

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Skin contact, Ingestion**Acute exposure**Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion : May be harmful if swallowed.
Eyes : May cause eye/skin irritation.
Skin : Experience shows no unusual dermatitis hazard from routine handling.**Chronic exposure** : Refer to Section 11 for Toxicological Information.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3
Revision Date 01/23/2008

Page 2 of 8
Print Date 12/3/2011

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. Seek medical attention if necessary.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available

Flammable Limits
Upper explosion limit : No data available
Lower explosion limit : No data available

Autoignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Heat only in areas with appropriate exhaust ventilation. Prolonged

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3
Revision Date 01/23/2008

Page 3 of 8
Print Date 12/3/2011

heating may result in product degradation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3

Revision Date 01/23/2008

Page 4 of 8

Print Date 12/3/2011

Components	Value	Exposure time	Exposure type	List:
Ethyl benzene	100 ppm	Time Weighted Average (TWA):		ACGIH
	125 ppm	Short Term Exposure Limit (STEL):		ACGIH
	100 ppm 435 mg/m3	PEL:		OSHA Z1
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		MX OEL
	125 ppm 545 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
Xylenes (o-, m-, p-isomers)	100 ppm	Time Weighted Average (TWA):		ACGIH
	150 ppm	Short Term Exposure Limit (STEL):		ACGIH
	100 ppm 435 mg/m3	PEL:		OSHA Z1
	100 ppm 435 mg/m3	Time Weighted Average (TWA):		MX OEL
	150 ppm 655 mg/m3	Short Term Exposure Limit (STEL):		MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid	Evaporation rate	: Not established
Appearance	: liquid, Viscous liquid dispersion	Specific Gravity	: Not determined
Color	: RED	Bulk density	: Not applicable
Odour	: Very faint	Vapour pressure	: Not determined
Melting point/range	: Not applicable	Vapour density	: Heavier than air.
Boiling Point:	: Not applicable	pH	: Not determined
Water solubility	: Immiscible		

10. STABILITY AND REACTIVITY

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3

Revision Date 01/23/2008

Page 5 of 8

Print Date 12/3/2011

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
100-41-4	Ethyl benzene	Irritant	Eyes, Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, central nervous system (CNS).
1330-20-7	Xylenes (o-, m-, p-isomers)	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, blood and blood forming system, Liver, Kidney, central nervous system (CNS), digestive system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-41-4	Ethyl benzene	Oral LD50	3,500 mg/kg	rat
		Dermal LD50	17800 ul/kg	rabbit
1330-20-7	Xylenes (o-, m-, p-isomers)	LC50	5000 ppm/4H	rat
		Oral LD50	4,300 mg/kg	rat
		Dermal LD50	> 1,700 mg/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
100-41-4	Ethyl benzene	no	2B	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3
Revision Date 01/23/2008

Page 6 of 8
Print Date 12/3/2011

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

- Persistence and degradability : Not readily biodegradable.
- Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
- Bioaccumulation Potential : No data available
- Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

- Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
- Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

- U.S. DOT Classification : Refer to specific regulation.
- ICAO/IATA (air) : Refer to specific regulation.
- IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

- OSHA Status : Classified as hazardous based on components.
- TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3
Revision Date 01/23/2008

Page 7 of 8
Print Date 12/3/2011

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
ETHYLBENZENE	100-41-4	0.10 - 1.00
XYLENE (MIXED ISOMERS)	1330-20-7	1.00 - 5.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Ethyl benzene	100-41-4	0.10 - 1.00	111
Xylenes (o-, m-, p- isomers)	1330-20-7	1.00 - 5.00	230

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
100-41-4
1309-37-1
1330-20-7

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Listed

Japan ENCS : Not determined



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

STAN-TONE 82SP00 RED

Version Number 1.3
Revision Date 01/23/2008

Page 8 of 8
Print Date 12/3/2011

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.