

#### MATERIAL SAFETY DATA SHEET

## 83200MRT MICHIGAN GOLD

 Version Number 1.2
 Page 1 of 7

 Revision Date 05/02/2007
 Print Date 11/28/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Product Stewardship (770) 590-3500 x.3563

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : 83200MRT MICHIGAN GOLD

Product code : FO00002211
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	471-34-1	5 - 10
Diatomaceous earth	61790-53-2	10 - 30

## 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



#### MATERIAL SAFETY DATA SHEET

#### 83200MRT MICHIGAN GOLD

 Version Number 1.2
 Page 2 of 7

 Revision Date 05/02/2007
 Print Date 11/28/2011

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available

Flammable Limits

Upper explosion limit : No data available Lower explosion limit : No data available Autoignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

Unusual Fire/Explosion

Hazards

contaminants.

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all

possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the

soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper

disposal methods.



## MATERIAL SAFETY DATA SHEET

## 83200MRT MICHIGAN GOLD

 Version Number 1.2
 Page 3 of 7

 Revision Date 05/02/2007
 Print Date 11/28/2011

7. HANDLING AND STORAGE

Handling : Heat only in areas with appropriate exhaust ventilation. Processing

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

: Safety shoes

General Hygiene

Considerations

: Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



#### MATERIAL SAFETY DATA SHEET

## 83200MRT MICHIGAN GOLD

 Version Number 1.2
 Page 4 of 7

 Revision Date 05/02/2007
 Print Date 11/28/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate 10 mg/m3 Time V		Time Weighted Average (TWA):		ACGIH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Diatomaceous earth	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.8 mg/m3	Time Weighted Average (TWA):		Z3
Silica, amorphous, fumed, crystal-free	0.8 mg/m3	Time Weighted Average (TWA):		Z3
	10 mg/m3	Time Weighted Average (TWA):	Inhalable particulate.	MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Respirable dust.	MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid Evaporation rate Not established Viscous, liquid Appearance Specific Gravity Not determined Color YELLOW Bulk density : Not applicable Odour : Very faint Vapour pressure : Not determined Not applicable Vapour density Melting point/range : Not determined Boiling Point: : Not applicable : Not applicable pН

Water solubility : Immiscible

#### 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact

with acetal homopolymers and acetal copolymers during processing.



#### MATERIAL SAFETY DATA SHEET

## 83200MRT MICHIGAN GOLD

Version Number 1.2 Page 5 of 7
Revision Date 05/02/2007 Print Date 11/28/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
61790-53-2	Diatomaceous earth	Irritant	Eyes, Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed,	Oral LD50	3,160 mg/kg	rat
	crystal-free			
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

#### Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

#### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

#### NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

## 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.



#### MATERIAL SAFETY DATA SHEET

## 83200MRT MICHIGAN GOLD

Version Number 1.2 Page 6 of 7 Print Date 11/28/2011 Revision Date 05/02/2007

**Environmental Toxicity** : Environmental toxicity has not been established for this mixture as a

whole.

**Bioaccumulation Potential** No data available

Additional advice No data available

13. DISPOSAL CONSIDERATIONS

Product Where possible recycling is preferred to disposal or incineration. The

> generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA (air) Refer to specific regulation.

IMO / IMDG (maritime) Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

**OSHA Status** Classified as hazardous based on components.

**TSCA Status** All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

65

: Not applicable

SARA Title III Section 302 Extremely Hazardous Substance

# PolyOne

## POLYONE CORPORATION

# MATERIAL SAFETY DATA SHEET

## 83200MRT MICHIGAN GOLD

 Version Number 1.2
 Page 7 of 7

 Revision Date 05/02/2007
 Print Date 11/28/2011

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No. 61790-53-2 112945-52-5

DSL : DSL status has not been determined. Quantity use in Canada may be

restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Listed

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

#### 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.