MATERIAL SAFETY DATA SHEET 83701599 BLU 308C PANTONE TEX

Version Number 1.0 Revision Date 01/30/2004

Page 1 of 6 Print Date 11/13/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	83701599 BLU 308C PANTONE TEX
Product code	:	FO00002388
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Petroleum distillates, hydrotreated light	64742-53-6	1 - 5
naphthenic		
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.		
Ingestion	: May be harmful if swallowed.		
Eyes	: May cause eye/skin irritation.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 83701599 BLU 308C PANTONE TEX

Version Number 1.0 Revision Date 01/30/2004 Page 2 of 6 Print Date 11/13/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxider of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET 83701599 BLU 308C PANTONE TEX

ion Number 1.0 sion Date 01/30/2004				Print D	Page : ate 11/13/
Handling	fı P	ime condensates	may contain of hoods, ducts,	iate exhaust ventilation. combustible or toxic resi and other surfaces to mi	due.
Storage	: Keep containers dry and tightly closed to avoid moisture absorpt and contamination. Store in a cool dry place.			e absorption	
8. F	XPOSURE	CONTROLS / I	PERSONAL	PROTECTION	
Respiratory protection	: U	nder normal han	dling conditio	ons a respirator may not l	be required.
Eye/Face Protection	: S	afety glasses witl	n side-shields		
Hand protection	: P	rotective gloves.			
Skin and body protection	: L	ong sleeved cloth	ning.		
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations				industrial hygiene and s at the end of workday.	afety practic
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure	e time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL		Respirable fraction.	OSHA Z
	15 mg/m3	PEL		Total dust.	OSHA Z
Petroleum distillates,	500 ppm	PEL		Vapor.	OSHA Z
hydrotreated light	2,000				
naphthenic	mg/m3				
	9. PHYSIC	CAL AND CHE	MICAL PRO	PERTIES	
Form	, liqui	a	Evene	Not	actablished
Form Appearance	: liquio				established determined
Color	: Viscous, liquid : BLUE		Specific Gravity::Not determinedBulk density:Not applicable		
Odor	: Very faint		Vapor pressure : Not determined		
Melting point/range	: Not applicable				determined
Boiling Point:	: Not applicable		рН	-	applicable
Water solubility	: Imm		*		
	10. 8	STABILITY AN	D REACTIV	VITY	



MATERIAL SAFETY DATA SHEET 83701599 BLU 308C PANTONE TEX

Version Number 1.0 Revision Date 01/30/2004 Page 4 of 6 Print Date *11/13/2011*

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
64742-53-6	Petroleum distillates,	Irritant	Eyes, Skin.
	hydrotreated light		
	naphthenic		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

MATERIAL SAFETY DATA SHEET 83701599 BLU 308C PANTONE TEX

sion Date 01/30/2004		Page 5 Print Date 11/13/2
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 302)
Not applicable		
California Dronosition	. :	WARNING! This product contains a chemical known to the State of
California Proposition 65		California to cause cancer.
	xtrem	California to cause cancer.
65	xtrem	California to cause cancer.
65 SARA Title III Section 302 E		California to cause cancer. ely Hazardous Substance
65 SARA Title III Section 302 E Not applicable		California to cause cancer. ely Hazardous Substance
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Not applicable	oxic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Not applicable Canadian Regulations:	oxic C	California to cause cancer. ely Hazardous Substance Chemicals:
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Not applicable Canadian Regulations: National Pollutant Rele	oxic C ease Ir	California to cause cancer. ely Hazardous Substance Chemicals:



MATERIAL SAFETY DATA SHEET 83701599 BLU 308C PANTONE TEX

Version Number 1.0 Revision Date 01/30/2004 Page 6 of 6 Print Date *11/13/2011*

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.