## MATERIAL SAFETY DATA SHEET **8370353D RED HOT DIP**

Version Number 1.2 Revision Date 05/18/2005

Page 1 of 7 Print Date 11/18/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number		Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	8370353D RED HOT DIP
Product code	:	FO00002426
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Misc00032 - Miscellaneous Irritant	Not Available	1 - 5
Di(2-ethylhexyl)phthalate	117-81-7	0.1 - 1

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **8370353D RED HOT DIP**

Version Number 1.2 Revision Date 05/18/2005 Page 2 of 7 Print Date 11/18/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ol> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ol>
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing

PolyOne.

## MATERIAL SAFETY DATA SHEET 8370353D RED HOT DIP

sion Date 05/18/2005				F	Print Da	Page 3 te 11/18/2
	P	me condensates may eriodically clean hood ccumulation of these r	ls, ducts, ai			
Storage		eep containers dry and dontamination. Sto			oisture	absorption
8. E	XPOSURE	CONTROLS / PERS	SONAL PI	ROTECTION		
Respiratory protection	: N	o personal respiratory	<sup>,</sup> protective	equipment nor	mally re	quired.
Eye/Face Protection	: Sa	afety glasses with side	e-shields.			
Hand protection	: P:	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: Sa	afety shoes.				
General Hygiene Considerations		andle in accordance w ash hands before brea				fety practic
Engineering measures		eat only in areas with propriate exhaust ver			ation. F	Provide
Exposure limit(s)						
Components	Value	Exposure time	e	Exposure typ	be	List:
Di(2-ethylhexyl)phthal ate	5 mg/m3	PEL:		Vapor.		OSHA Z
	9. PHYSIC	CAL AND CHEMIC	AL PROP	ERTIES		
Form	: liquio	1	Evaporat	tion rate :		stablished
Appearance	: liquio : Visco		Evaporat Specific	tion rate : Gravity: :	Not d	etermined
Appearance Color	: liquio : Visco : RED	ł ous, liquid	Evaporat Specific Bulk den	tion rate : Gravity: : isity :	Not d Not a	etermined pplicable
Appearance Color Odor	: liquio : Visco : RED : Very	l ous, liquid faint	Evaporat Specific Bulk den Vapor pr	tion rate : Gravity: : Isity : ressure :	Not d Not a Not d	etermined pplicable etermined
Appearance Color Odor Melting point/range	: liquio : Visco : RED : Very : Not a	l ous, liquid faint upplicable	Evaporat Specific Bulk den Vapor pr Vapour c	tion rate : Gravity: : Isity : ressure :	Not d Not a Not d Not d	etermined pplicable etermined etermined
Appearance Color Odor	: liquio : Visco : RED : Very : Not a	l ous, liquid faint upplicable upplicable	Evaporat Specific Bulk den Vapor pr	tion rate : Gravity: : Isity : ressure :	Not d Not a Not d Not d	etermined pplicable etermined
Appearance Color Odor Melting point/range Boiling Point:	: liquid : Visco : RED : Very : Not a : Not a : Immi	l ous, liquid faint upplicable upplicable	Evaporat Specific Bulk den Vapor pr Vapour o pH	tion rate : Gravity: : Isity : ressure : lensity :	Not d Not a Not d Not d	etermined pplicable etermined etermined
Appearance Color Odor Melting point/range Boiling Point:	: liquid : Visco : RED : Very : Not a : Not a : Immi <b>10. S</b>	l ous, liquid faint applicable applicable ascible	Evaporat Specific Bulk den Vapor pr Vapour o pH	tion rate : Gravity: : Isity : ressure : lensity :	Not d Not a Not d Not d	etermined pplicable etermined etermined
Appearance Color Odor Melting point/range Boiling Point: Water solubility	: liquid : Visco : RED : Very : Not a : Not a : Immi <b>10. S</b>	l pus, liquid faint upplicable upplicable iscible TABILITY AND RI	Evaporat Specific Bulk den Vapor pr Vapour o pH	tion rate : Gravity: : Isity : ressure : lensity :	Not d Not a Not d Not d	etermined pplicable etermined etermined
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	: liquid : Visco : RED : Very : Not a : Not a : Immi <b>10. S</b> : St	l pus, liquid faint upplicable upplicable scible <b>TABILITY AND RI</b> table.	Evaporat Specific Bulk den Vapor pr Vapour o pH	tion rate : Gravity: : isity : ressure : lensity : <b>FY</b>	Not d Not a Not d Not d Not a	etermined pplicable letermined letermined pplicable
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	: liquid : Visco : RED : Very : Not a : Not a : Immi <b>10. S</b> : St	l ous, liquid faint applicable applicable scible <b>TABILITY AND RI</b> able.	Evaporat Specific Bulk den Vapor pr Vapour o pH	tion rate : Gravity: : isity : ressure : lensity : <b>FY</b>	Not d Not a Not d Not d Not a	etermined pplicable letermined letermined pplicable



## MATERIAL SAFETY DATA SHEET 8370353D RED HOT DIP

Version Number 1.2 Page 4 of 7 Revision Date 05/18/2005 Print Date 11/18/2011 decomposition, do not overheat. **Incompatible Materials** : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : products (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
Not Available	Misc00032 -	sensitizer	Skin.
	Miscellaneous Irritant		
		Irritant	Eyes, Skin.
117-81-7	Di(2-ethylhexyl)phthalate	Systemic effects	Eyes, Respiratory system,
			Liver, central nervous system
			(CNS), Skin, digestive system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
117-81-7	Di(2-ethylhexyl)phthalate	Oral LD50	30 gm/kg	rat
		Dermal LD50	25 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
---------	---------------	------	------	-----

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

PolyOne.

## MATERIAL SAFETY DATA SHEET 8370353D RED HOT DIP

Version Number 1.2 Revision Date 05/18/2005 Page 5 of 7 Print Date 11/18/2011

#### Additional Health Hazard Information:

Di(2-ethylhexyl)phthalate 117-81-7 There is sufficient evidence for the carcinogenicity of di (2-ethylhexyl) phthalate in experimental animals. Administered in the feed this chemical caused an increase incidence of liver cancer in male and female rats and mice. The relevance of this finding to humans is uncertain.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OS Regulations.	
OSHA Status	: Classified as hazardous based on components.
-	<ul> <li>Classified as hazardous based on components.</li> <li>All components of this product are listed on or exempt from the TSC Inventory.</li> </ul>
OSHA Status	: All components of this product are listed on or exempt from the TSC Inventory.

5/7

PolyOne.

# MATERIAL SAFETY DATA SHEET **8370353D RED HOT DIP**

Version Number 1.2 Revision Date 05/18/2005

\_\_\_\_\_

Page 6 of 7 Print Date 11/18/2011

California Proposition 65	ı :	WARNING! This pu California to cause ca chemical known to the other reproductive ha	ancer., WARNIN ne State of Califo	IG! Th	nis produ	ct contains a
SARA Title III Section 302 E Not applicable	xtrem	ely Hazardous Substar	nce			
SARA Title III Section 313 T	oxic C	Chemicals:				
Chemical Name			CAS-No.		Weight	%
DI(2-ETHYLHEXYL	L)PHT	HALATE (DEHP)	117-81-7		0.41	
Canadian Regulations: <u>National Pollutant Rele</u>	ease I	nventory (NPRI)				
Chemical Name Di(2-ethylhexyl)phthalat			CAS-No. 117-81-7	0.4	eight %	NPRI ID# 25
WHMIS Classification WHMIS Ingredient Dis		2				
			his product are o	n the C	anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7 DSL		rre List			anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7		The List All components of the second s			anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7 DSL		The List All components of the second s			anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7 DSL National Inventories: Australia AICS China IECS		All components of the Substances List (DSI) Not determined			anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7 DSL National Inventories: Australia AICS China IECS Europe EINECS		All components of the Substances List (DSI) Not determined Not determined Not determined			anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7 DSL National Inventories: Australia AICS China IECS Europe EINECS Japan ENCS		All components of the Substances List (DSI) Not determined Not determined Not determined Not determined Not determined			anadian	Domestic
WHMIS Ingredient Dis CAS-No. 117-81-7 DSL National Inventories: Australia AICS China IECS Europe EINECS		All components of the Substances List (DSI) Not determined Not determined Not determined			anadian	Domestic



## MATERIAL SAFETY DATA SHEET **8370353D RED HOT DIP**

Version Number 1.2 Revision Date 05/18/2005 Page 7 of 7 Print Date 11/18/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.