

MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

Version Number 1.0 Revision Date 06/12/2002 Page 1 of 8 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

| NON-EMERGENCY TELEPHONE | : | Product Stewardship, (314) 771-1800 |
|-------------------------------|---|--|
| Emergency telephone number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name | : | 9265-3 DARK GREY PLASTISOL |
| Product code | : | FO00002710 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|---------------------------------|------------|----------|
| Carbon black | 1333-86-4 | 0.1 - 1 |
| Calcium oxide | 1305-78-8 | 1 - 5 |
| Lead oxide sulfate (Pb4O3(SO4)) | 12202-17-4 | 1 - 5 |
| Sodium hydroxide (Na(OH)) | 1310-73-2 | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion | |
|----------------------------|--|--|
| Acute exposure | | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. | |
| Ingestion | : May be harmful if swallowed. | |
| Eyes | : May cause eye/skin irritation. | |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. | |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. | |



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

Version Number 1.0 Revision Date 06/12/2002 Page 2 of 8 Print Date 11/5/2011

| Aggravated by Exposure: | | |
|--|---|--------|
| | 4. FIRST AID MEASURES | |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all ca doubt, seek medical advice. | ses of |
| Ingestion | : Do not induce vomiting without medical advice. When symptor persist, or in all cases of doubt, seek medical advice. | ns |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. irritation persists, seek medical attention. | If eye |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists medical attention. | s seek |
| | 5. FIRE-FIGHTING MEASURES | |
| Flash point | : No data available. | |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in posi pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) of fire conditions. | |
| | ACCIDENTAL RELEASE MEASURES | |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. | |
| Environmental precautions | : Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil. | d not |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid b universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for pro- disposal methods. | |
| | 7. HANDLING AND STORAGE | |



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

| Version Number 1.0 Revision Date 06/12/2002 | | Page 3 of 8 Print Date 11/5/2011 |
|--|-------|--|
| Handling | : | Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place. |
| 8. EX | POSUF | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | Under normal handling conditions a respirator may not be required. |
| Eye/Face Protection | : | Safety glasses with side-shields. |
| Hand protection | : | Protective gloves. |
| Skin and body protection | : | Long sleeved clothing. |
| Additional Protective Measures | : | Safety shoes. |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

Version Number 1.0 Revision Date 06/12/2002 Page 4 of 8 Print Date 11/5/2011

| Components | Value | Exposure time | Exposure type | List: |
|------------------------------------|---------------|-----------------------------------|--------------------------------|---------|
| Calcium oxide | 2 mg/m3 | Time Weighted Average (TWA): | Dust. | ACGIH |
| Calcium oxide | 5 mg/m3 | PEL: | Dust. | OSHA Z1 |
| Carbon black | 3.5 mg/m3 | Time Weighted Average (TWA): | Total dust. as carbon black | ACGIH |
| Carbon black | 3.5 mg/m3 | PEL: | Total dust. as carbon black | OSHA Z1 |
| Lead oxide sulfate (Pb4O3(SO4)) | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | ACGIH |
| Lead oxide sulfate (Pb4O3(SO4)) | 0.05 mg/m3 | Time Weighted Average (TWA): | as Pb | OSHA |
| | 0.03 mg/m3 | OSHA Action level: | as Pb | OSHA |
| Lead oxide sulfate (Pb4O3(SO4)) | 0.15 mg/m3 | Time Weighted Average (TWA): | Dust and fume. as Pb | MX OEL |
| | 0.45 mg/m3 | Short Term Exposure Limit (STEL): | Dust and fume. as Pb | MX OEL |
| Sodium hydroxide (Na(OH)) | 2 mg/m3 | Ceiling Limit Value: | Total dust. | ACGIH |
| Sodium hydroxide (Na(OH)) | 2 mg/m3 | PEL: | Total dust. | OSHA Z1 |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
 : Viscous, Liquid
 : GREY
 : Very faint
 : Not applicable
 : Not applicable
 : Immiscible

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH

- : Not established
- : Not determined
- : Not applicable.
- : Not determined
- : Not determined
- : Not applicable.

| | 10. STABILITY AND REACTIVITY |
|----------------------------------|---|
| Stability | : Stable. |
| Hazardous Polymerization | : Will not occur. |
| Conditions to avoid | : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing. |
| Hazardous decomposition products | : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F) |



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

Version Number 1.0 Revision Date 06/12/2002 Page 5 of 8 Print Date 11/5/2011

and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|--------------------|------------------|---------------------------------|
| 1333-86-4 | Carbon black | Systemic effects | Eyes, Respiratory system. |
| 1305-78-8 | Calcium oxide | Irritant | Skin. |
| | | Systemic effects | Eyes, Skin, Respiratory system. |
| | | Corrosive | Skin. |
| 12202-17-4 | Lead oxide sulfate | Systemic effects | reproductive system, central |
| | (Pb4O3(SO4)) | | nervous system. |
| 1310-73-2 | Sodium hydroxide | Irritant | Respiratory system. |
| | (Na(OH)) | | |
| | | Systemic effects | Respiratory system. |
| | | Corrosive | Skin. |

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|---------------|-------------|---------------|---------|
| 1333-86-4 | Carbon black | Oral LD50 | >15,400 mg/kg | rat |
| | | Dermal LD50 | > 3 gm/kg | rabbit |

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|------------------------------------|------|------|-----|
| 1333-86-4 | Carbon black | no | 2B | no |
| 12202-17-4 | Lead oxide sulfate (Pb4O3(SO4)) | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

Version Number 1.0 Revision Date 06/12/2002 Page 6 of 8 Print Date 11/5/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Lead oxide sulfate (Pb4O3(SO4)) 12202-17-4 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

| Persistence and degradability | : Not readily biodegradable. |
|--|--|
| Environmental Toxicity | : Environmental toxicity has not been established for this mixture as a whole. |
| Bioaccumulation Potential | : No data available. |
| Additional advice | : No data available. |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground) | : Not regulated for transportation. |
| ICAO/IATA | : Not regulated for transportation. |
| IMO / IMDG | : Not regulated for transportation. |
| | 15. REGULATORY INFORMATION |

6/8



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

| Version Number 1.0 | Page 7 of 8 |
|--------------------------|----------------------|
| Revision Date 06/12/2002 | Print Date 11/5/2011 |
| | |

US Regulations:

 OSHA Status
 : Classified as hazardous based on components.

 TSCA Status
 : All components of this product are listed on the TSCA inventory or are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name | CAS-No. | % in Product | RQ for component | RQ for |
|------------------|-----------|--------------|------------------|-----------------|
| | | | | Mixture/Product |
| Sodium hydroxide | 1310-73-2 | 0.95 | 1,000lbs | 104,866 LB |
| (Na(OH)) | | | | |

California Proposition 65

: WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name | CAS-No. | Weight % |
|---------------------------|------------|----------|
| LEAD COMPOUNDS, INORGANIC | 12202-17-4 | 2.32 |

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

: Listed.

National Inventories:

DSL

| Australia AICS | : | Listed. |
|----------------|---|-----------------|
| China IECS | : | Listed. |
| Europe EINECS | : | Not determined. |



MATERIAL SAFETY DATA SHEET

9265-3 DARK GREY PLASTISOL

Version Number 1.0 Revision Date 06/12/2002 Page 8 of 8 Print Date 11/5/2011

| Japan ENCS | : | Not determined. |
|------------|---|-----------------|
|------------|---|-----------------|

Korea KECI : Not determined.

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.