

MATERIAL SAFETY DATA SHEET

M1426M NEUT II 195A P599848

Version Number 1.1 Revision Date 02/12/2003 Page 1 of 6 Print Date *11/10/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	M1426M NEUT II 195A P599848
Product code	:	FO00002989
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

M1426M NEUT II 195A P599848

Version Number 1.1 Revision Date 02/12/2003 Page 2 of 6 Print Date 11/10/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention.	eye
Skin	: Wash off with soap and plenty of water. If skin irritation persists so medical attention.	eek
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. 	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	iot
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for prope disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize	5



MATERIAL SAFETY DATA SHEET

M1426M NEUT II 195A P599848

sion Date 02/12/2003				Print	Date 11/10/2
	ac	cumulation of these	materials		
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8. E	XPOSURE	CONTROLS / PE	RSONAL	PROTECTION	
Respiratory protection	: U	nder normal handlin	g conditio	ons a respirator may no	ot be required.
Eye/Face Protection	: Sa	afety glasses with si	de-shields		
Hand protection	: Pr	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing	<i>.</i>		
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations				industrial hygiene and at the end of workday.	l safety practice
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure ti	ne	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb	OSHA Z1
	9. PHYSIC	CAL AND CHEMI	CAL PRO	PERTIES	
Form	: Liqui	d	Evano	ration rate : N	ot established
Appearance		ous, Liquid			ot determined
Color	: TAN	· •	Bulk d	-	ot applicable.
Odor	: Very				ot determined
Melting point/range	•	pplicable		1	ot determined
Boiling Point:			pH		ot applicable.
Water solubility	: Not applicable pH : Not applicable. : Immiscible				
	10. S	TABILITY AND I	REACTIV	ITY	
Stability	: St	able.			
Hazardous Polymerization	1 : W	ill not occur.			
Conditions to avoid		eep away from oxid		ts and open flame. To	avoid thermal
Incompatible Materials	: In	compatible with str	ong acids	and oxidizing agents.	Avoid contact



MATERIAL SAFETY DATA SHEET

M1426M NEUT II 195A P599848

Version Number 1.1 Revision Date 02/12/2003 Page 4 of 6 Print Date *11/10/2011*

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), hydrogen chloride (HCl), other hazardous materials, and
smoke are all possible. Prolonged heating may result in product
degradation. As a general rule of thumb, degradation begins to occur
after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),
and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

M1426M NEUT II 195A P599848

rsion Number 1.1 vision Date 02/12/2003				Pri	Page 5 int Date 11/10/2	
Persistence and degradability	:	: Not readily biodegradable.				
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.					
Bioaccumulation Potential	:	No data available	2.			
Additional advice	:	No data available	·.			
	1.	3. DISPOSAL CO	NSIDERATION	IS		
Product	:	generator of wast classification, tra	recycling is prefer e material has the nsportation and di l, state/provincial	responsibility for sposal in accord	ance with	
Contaminated packaging : Recycling is preferred when possible. The generator of waste ma has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provinci and local regulations.				n, transportation		
	1	4. TRANSPORT	INFORMATION	N		
			1.2			
U.S. DOT Classification	:	Refer to specific	-			
ICAO/IATA : Refer to specific regulation.						
IMO / IMDG	:	: Refer to specific regulation.				
	15	. REGULATORY	INFORMATIO	DN		
US Regulations:						
OSHA Status	:	Classified as haza	ardous based on co	omponents.		
TSCA Status	:	All components Inventory.	of this product are	listed on or exen	npt from the TSCA	
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 30)2)			
Chemical Name		CAS-No.	% in Product	RQ for component	RQ for Mixture/Prod uct	
Arsenic		7440-38-2	0.0011	001 lbs	90,909 LB	
California Proposition	:	WARNING! Th	is product contains	s a chemical kno	wn to the State of	



MATERIAL SAFETY DATA SHEET

M1426M NEUT II 195A P599848

Version Number 1.1 Revision Date 02/12/2003		Page 6 of 6 Print Date <i>11/10/2011</i>
65	California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
SARA Title III Section 302 Extr	em	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	ic (Chemicals:
	N	ot applicable
Canadian Regulations:		
WHMIS Classification	:	D2A
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined.
China IECS	:	Not determined.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.