



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

M1426 MEDIUM GRAY 8247

Version Number 1.1
Revision Date 09/17/2004

Page 1 of 7
Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION
8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : Product Stewardship (770) 590-3500 x.3563
Emergency telephone number : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**

Product name : M1426 MEDIUM GRAY 8247
Product code : FO00002992
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|-----------|----------|
| Antimony trioxide | 1309-64-4 | 0.1 - 1 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion : May be harmful if swallowed.
Eyes : May cause eye/skin irritation.
Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions : None known.

Aggravated by Exposure:

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****M1426 MEDIUM GRAY 8247**Version Number 1.1
Revision Date 09/17/2004Page 2 of 7
Print Date 11/16/2011**4. FIRST AID MEASURES**

- Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
- Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
- Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
- Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : No data available
- Flammable Limits
Upper explosion limit : No data available
Lower explosion limit : No data available
- Autoignition temperature : Not applicable
- Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.
- Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
- Unusual Fire/Explosion Hazards : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
- Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

- Handling : Heat only in areas with appropriate exhaust ventilation. Processing

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

M1426 MEDIUM GRAY 8247

Version Number 1.1
Revision Date 09/17/2004

Page 3 of 7
Print Date 11/16/2011

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye/Face Protection : Safety glasses with side-shields.
- Hand protection : Protective gloves.
- Skin and body protection : Long sleeved clothing.
- Additional Protective Measures : Safety shoes.
- General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

| Components | Value | Exposure time | Exposure type | List: |
|-------------------|-----------|------------------------------|---------------|---------|
| Antimony trioxide | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : liquid
- Appearance : Viscous, liquid
- Color : GREY
- Odor : Very faint
- Melting point/range : Not applicable
- Boiling Point: : Not applicable
- Water solubility : Immiscible
- Evaporation rate : Not established
- Specific Gravity: : Not determined
- Bulk density : Not applicable
- Vapor pressure : Not determined
- Vapour density : Not determined
- pH : Not applicable

10. STABILITY AND REACTIVITY

- Stability : Stable.
- Hazardous Polymerization : Will not occur.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

M1426 MEDIUM GRAY 8247

Version Number 1.1
Revision Date 09/17/2004

Page 4 of 7
Print Date 11/16/2011

- Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
- Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
- Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|-----------|-------------------|--------------------------------|------------------------------------|
| 1309-64-4 | Antimony trioxide | Systemic effects sensitizer | Eyes, Respiratory system. Skin. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-------------------|-----------|----------------|---------|
| 1309-64-4 | Antimony trioxide | Oral LD50 | > 34,600 mg/kg | rat |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|-----------|-------------------|------|------|-----|
| 1309-64-4 | Antimony trioxide | no | 2B | no |

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

M1426 MEDIUM GRAY 8247

Version Number 1.1
Revision Date 09/17/2004

Page 5 of 7
Print Date 11/16/2011

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.
Environmental Toxicity : Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential : No data available
Additional advice : No data available

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.
ICAO/IATA (air) : Refer to specific regulation.
IMO / IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

| Chemical Name | CAS-No. | % in Product | RQ for component | RQ for Mixture/Product |
|---------------|-----------|--------------|------------------|------------------------|
| Arsenic | 7440-38-2 | 0.0011 | 001 lbs | 90,909 LB |

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

M1426 MEDIUM GRAY 8247

Version Number 1.1
Revision Date 09/17/2004

Page 6 of 7
Print Date 11/16/2011

California Proposition 65 : WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Not applicable
Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight % | NPRI ID# |
|-------------------|-----------|----------|----------|
| Antimony trioxide | 1309-64-4 | 0.36 | 17 |

WHMIS Classification : D2A

DSL : DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

M1426 MEDIUM GRAY 8247

Version Number 1.1
Revision Date 09/17/2004

Page 7 of 7
Print Date 11/16/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.