

MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Page 1 of 9
Revision Date 03/30/2014 Print Date 4/9/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone : 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : P1260DNPCM ADOBE CREAM

Product code : FO00003099
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|---|------------|----------------|
| Nickel antimony yellow rutile (C.I. Pigment | 8007-18-9 | 0.1 - 1 |
| Yellow 53) | | |
| Silica, cristobalite | 14464-46-1 | 0.1 - 1 |
| Naphthalene | 91-20-3 | 0.1 - 1 |
| Silica, amorphous | 7631-86-9 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye and skin irritation.



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Page 2 of 9
Revision Date 03/30/2014 Print Date 4/9/2014

Skin : Experience shows no unusual dermatitis hazard from routine handling.

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye

irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists

seek medical attention.

5. FIREFIGHTING MEASURES

Flash point : no data available

Flammable Limits

Upper explosion limit : no data available
Lower explosion limit : no data available
Auto-ignition temperature : Not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting

Procedures

Fullface self-contained breathing apparatus (SCBA) used in positive

pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are

all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or

the soil. Should not be released into the environment.

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Page 3 of 9
Revision Date 03/30/2014 Print Date 4/9/2014

binder, universal binder, sawdust). Package all material in

appropriate container for disposal.

7. HANDLING AND STORAGE

Handling : Heat only in areas with appropriate exhaust ventilation. Processing

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective

Measures

Safety shoes

General Hygiene : Handle in accordance with good industrial hygiene and safety Considerations : wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Revision Date 03/30/2014 Page 4 of 9 Print Date 4/9/2014

| Components | Value | Exposure time | Exposure type | List: |
|----------------------|---------------|------------------------------|------------------------|-----------|
| Nickel antimony | 0.015 | Recommended exposure | as Ni | NIOSH |
| yellow rutile (C.I. | mg/m3 | limit (REL): | | |
| Pigment Yellow 53) | | | | |
| | 1 mg/m3 | PEL: | as Ni | OSHA Z1 |
| | 1 mg/m3 | Time Weighted Average | as Ni | OSHA Z1A |
| | | (TWA): | | |
| | 0.2 mg/m3 | Time Weighted Average | Inhalable fraction. as | ACGIH |
| | 0.7 / 0 | (TWA): | Ni | , ggyy |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| | 0.5 mg/m3 | Recommended exposure | as Sb | NIOSH |
| | 0.5 mg/m3 | limit (REL): | as 50 | NIOSII |
| | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average | as Sb | OSHA Z1A |
| | 0.3 mg/m3 | (TWA): | 45 50 | OSIMIZM |
| | 0.5 mg/m3 | Time Weighted Average | as Sb | MX OEL |
| | | (TWA): | | |
| Silica, amorphous | 6 mg/m3 | Recommended exposure | | NIOSH |
| | | limit (REL): | | |
| | 0.8 mg/m3 | Time Weighted Average | | Z3 |
| | | (TWA): | | |
| | 10 mg/m3 | Time Weighted Average | Inhalable particulate. | MX OEL |
| | | (TWA): | | |
| | 3 mg/m3 | Time Weighted Average | Respirable dust. | MX OEL |
| 0'1' ' 1 1' | 0.025 | (TWA): | D 111 C 1 | A COUL |
| Silica, cristobalite | 0.025 | Time Weighted Average | Respirable fraction. | ACGIH |
| | mg/m3 | (TWA): | D ' 1 . 1 4 | OCHA 71 A |
| | 0.05 | Time Weighted Average (TWA): | Respirable dust. | OSHA Z1A |
| | mg/m3 0.05 | Time Weighted Average | Respirable. | Z3 |
| | mg/m3 | (TWA): | Respirable. | 2.3 |
| | 0.15 | Time Weighted Average | Total dust. | Z3 |
| | mg/m3 | (TWA): | Total dust. | 23 |
| | 0.05 | Time Weighted Average | | MX OEL |
| | mg/m3 | (TWA): | | |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average | | ACGIH |
| | | (TWA): | | |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average | Total dust. | OSHA Z1A |
| | | (TWA): | | |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit | as Ti | MX OEL |
| | 20 1118/1113 | (STEL): | as 11 | WIX OEL |
| Naphthalene | 10 ppm | Time Weighted Average | | ACGIH |
| 1 apinimiene | 10 ppin | (TWA): | | 1100111 |
| | 15 ppm | Short Term Exposure Limit | | ACGIH |
| | | (STEL): | | |



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Page 5 of 9
Revision Date 03/30/2014 Print Date 4/9/2014

| 10 ppm 50 mg/m3 | Recommended exposure limit (REL): | NIOSH |
|--------------------|-----------------------------------|-----------|
| 15 ppm 75 mg/m3 | Short Term Exposure Limit (STEL): | NIOSH |
| 10 ppm 50 mg/m3 | PEL: | OSHA Z1 |
| 10 ppm 50 mg/m3 | Time Weighted Average (TWA): | OSHA Z1A |
| 15 ppm 75 mg/m3 | Short Term Exposure Limit (STEL): | OSHA Z1A |
| 10 ppm 50 mg/m3 | Time Weighted Average (TWA): | MX OEL |
| 15 ppm 75 mg/m3 | Short Term Exposure Limit (STEL): | MX OEL |
| 5 ppm | Time Weighted Average (TWA): | ACGIH NIC |

9. PHYSICAL AND CHEMICAL PROPERTIES

Evapouration rate Not established Form : liquid viscous, liquid Specific Gravity Appearance Not determined WHITE Bulk density Colour Not applicable Odour : very faint Vapour pressure Not determined Melting point/range not applicable Vapour density Not determined Boiling Point: not applicable Not applicable pН

Water solubility : immiscible

10. STABILITY AND REACTIVITY

Stability : The product is stable if stored and handled as prescribed.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents., Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and

smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400

°F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Revision Date 03/30/2014 Page 6 of 9 Print Date 4/9/2014

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|--|------------------|---|
| 8007-18-9 | Nickel antimony yellow rutile (C.I. Pigment Yellow 53) | Irritant | Eyes, Skin. |
| | | sensitizer | Skin. |
| 14464-46-1 | Silica, cristobalite | Systemic effects | Respiratory system. |
| | | Irritant | Eyes, Skin, Respiratory system. |
| 91-20-3 | Naphthalene | Irritant | Eyes. |
| | | Systemic effects | Eyes, Respiratory system, central nervous system (CNS). |
| | | Toxic | Refer to LC50 / LD50 Data on MSDS |
| 7631-86-9 | Silica, amorphous | Irritant | Eyes, Respiratory system. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|---------|---------------|-------------|-------------|---------|
| 91-20-3 | Naphthalene | LC50 | > 340 mg/m3 | rat |
| | | Oral LD50 | 490 mg/kg | rat |
| | | Dermal LD50 | > 20 gm/kg | rabbit |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|-------------------------------|------|------|-----|
| 8007-18-9 | Nickel antimony yellow rutile | no | 1 | no |
| | (C.I. Pigment Yellow 53) | | | |
| 14464-46-1 | Silica, cristobalite | no | 1 | no |
| 91-20-3 | Naphthalene | no | 2B | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Page 7 of 9
Revision Date 03/30/2014 Print Date 4/9/2014

Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney and muscle effects.

Additional Health Hazard Information:

Silica, cristobalite 14464-46-1 This material in its free releasable form may cause respiratory tract irritation. Long-term exposure may cause coughing, chest pain, diminished chest expansion and possibly silicosis, which is a scarring of the lungs.

12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential : no data available

Additional advice : no data available

13. DISPOSAL CONSIDERATIONS

Product : Where possible recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal,

state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the

TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Revision Date 03/30/2014 Page 8 of 9 Print Date 4/9/2014

not applicable

California Proposition

65

: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-No. | Weight percent |
|------------------------------|-----------|----------------|
| NICKEL COMPOUNDSNICKEL | 8007-18-9 | 0.10 - 1.00 |
| COMPOUNDS ANTIMONY COMPOUNDS | | |
| NAPHTHALENE | 91-20-3 | 0.10 - 1.00 |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

| Chemical Name | CAS-No. | Weight | NPRI ID# |
|---|---------------|-------------|----------|
| | | percent | |
| Bis (2-ethylhexyl) adipate | 103-23-1 | 1.00 - 5.00 | |
| Nickel antimony yellow rutile (C.I. Pigment | 8007-18-9 | 0.10 - 1.00 | |
| Yellow 53) | | | |
| | | 0.10 - 1.00 | |
| Zinc | 7440-66-6 | 0.10 - 1.00 | |
| 1,2,4-Trimethylbenzene | Not Available | 0.10 - 1.00 | |
| Naphthalene | 91-20-3 | 0.10 - 1.00 | |

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|---------------|--|
| 103-23-1 | |
| 7631-86-9 | |
| Not Available | |

DSL : All of the components of this product are listed on the Canadian



MATERIAL SAFETY DATA SHEET

P1260DNPCM ADOBE CREAM

Version Number 1.8 Revision Date 03/30/2014 Page 9 of 9 Print Date 4/9/2014

Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS : Not determined

China IECS : Not determined

Europe EINECS : Not determined

Japan ENCS : Not determined

Korea KECI : Not determined

Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.