### MATERIAL SAFETY DATA SHEET D149LTB LIGHT BLUE

Version Number 1.1 Revision Date 05/06/2005

Page 1 of 6 Print Date 11/17/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
:	D149LTB LIGHT BLUE
:	FO00003170
:	Mixture
:	Mixture
:	Industrial Applications
	::

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	471-34-1	1 - 5
Petroleum distillates, hydrotreated light	64742-53-6	1 - 5
naphthenic		
Titanium dioxide	13463-67-7	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

# MATERIAL SAFETY DATA SHEET D149LTB LIGHT BLUE

Version Number 1.1 Revision Date 05/06/2005 Page 2 of 6 Print Date 11/17/2011

Medical Conditions Aggravated by Exposure:	: None known.						
	4. FIRST AID MEASURES						
nhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.							
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.						
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.						
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.						
	5. FIRE-FIGHTING MEASURES						
Flash point	: No data available						
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>						
	6. ACCIDENTAL RELEASE MEASURES						
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.						
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.						
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.						
	7. HANDLING AND STORAGE						



## MATERIAL SAFETY DATA SHEET D149LTB LIGHT BLUE

Version Number 1.1 Revision Date 05/06/2005	Page 3 of 6 Print Date 11/17/2011
	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue.
	Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	No personal respiratory protective equipment normally required.
Eye/Face Protection	Safety glasses with side-shields.
Hand protection	Protective gloves.
Skin and body protection	Long sleeved clothing.
Additional Protective Measures	Safety shoes.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components Valu		Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Petroleum distillates,	500 ppm	PEL:	Vapor.	OSHA Z1
hydrotreated light	2,000			
naphthenic	mg/m3			
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range liquid
Viscous, liquid
BLUE
Very faint
Not applicable

Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density Not established
Not determined
Not applicable
Not determined
Not determined



## MATERIAL SAFETY DATA SHEET **D149LTB LIGHT BLUE**

Version Number 1.1 Revision Date 05/06/2005 Page 4 of 6 Print Date 11/17/2011

Boiling Point: Water solubility	: Not applicable pH : Not applicable : Immiscible
	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).</li> </ul>

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ	
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.	
64742-53-6 Petroleum distillates, hydrotreated light naphthenic		Irritant	Eyes, Skin.	
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.	

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No. Chemical Name		Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.

PolyOne.

## MATERIAL SAFETY DATA SHEET D149LTB LIGHT BLUE

Version Number 1.1 Revision Date 05/06/2005 Page 5 of 6 Print Date 11/17/2011

<b>Bioaccumulation Potential</b>	:	No data available				
Additional advice	:	No data available				
13. DISPOSAL CONSIDERATIONS						
Product	:	Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	1	4. TRANSPORT INFORMATION				
U.S. DOT Classification	:	Refer to specific regulation.				
ICAO/IATA (air)	:	Refer to specific regulation.				
IMO / IMDG (maritime)	:	Refer to specific regulation.				
	15	. REGULATORY INFORMATION				
US Regulations:						
OSHA Status	:	Classified as hazardous based on components.				
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous S	Subs	stances (40 CFR 302)				
Not applicable						
California Proposition 65	:	Not applicable				
SARA Title III Section 302 Extr Not applicable	em	ely Hazardous Substance				
SARA Title III Section 313 Tox	ic C	Chemicals:				
Not applicable						

PolyOne.

## MATERIAL SAFETY DATA SHEET **D149LTB LIGHT BLUE**

Version Number 1.1			Deia		e 6 of 6
Revision Date 05/06/2005			Prin	t Date 11/1	7/2011
Canadian Regulations:					
National Pollutant Release Chemical Name	se Inventory (NPRI)	CAS-No.	Weight %	NPRI ID#	
1,2,4-Trimethylbenzene		95-63-6	0.14	223	
WHMIS Classification	: D2B				
WHMIS Ingredient Discle	osure List				
CAS-No. 95-63-6					
DSL	: All components of Substances List (D)			Domestic	
National Inventories:					
Australia AICS	: Not determined				
China IECS	: Not determined				
Europe EINECS	: Not determined				
Japan ENCS	: Not determined				
Korea KECI	: Not determined				
Philippines PICCS	: Not determined				
	16. OTHER INFO	ORMATION			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.