

MATERIAL SAFETY DATA SHEET

D2314 WHITE-70

Version Number 1.0 Revision Date 10/16/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

| NON-EMERGENCY TELEPHONE | : | Product Stewardship, (314) 771-1800 |
|-------------------------------|---|--|
| Emergency telephone number | : | CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
| Product name | : | D2314 WHITE-70 |
| Product code | : | FO00003245 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % | |
|------------------|------------|----------|--|
| Titanium dioxide | 13463-67-7 | 1 - 5 | |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Skin contact, Ingestion |
|---|--|
| Acute exposure | |
| Inhalation | : Inhalation of airborne droplets may cause irritation of the respiratory tract. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : May cause eye/skin irritation. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |



MATERIAL SAFETY DATA SHEET

D2314 WHITE-70

| sion Date 10/16/2002 | Print Date 11/6/ |
|-----------------------------------|--|
| | 4. FIRST AID MEASURES |
| | 4. FIK51 AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases doubt, seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice. |
| Eyes | : Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : No data available. |
| Flammable Limits | |
| Upper explosion limit | : No data available. |
| Lower explosion limit | : No data available. |
| Autoignition temperature | : Not applicable. |
| Suitable extinguishing media | : Carbon dioxide blanket, dry powder, foam, Water spray. |
| Special Fire Fighting | : Fullface self-contained breathing apparatus (SCBA) used in positive |
| Procedures | pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| | , ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize |

MATERIAL SAFETY DATA SHEET



D2314 WHITE-70 Page 3 of 6 Version Number 1.0 Print Date 11/6/2011 Revision Date 10/16/2002 accumulation of these materials. : Keep containers dry and tightly closed to avoid moisture absorption Storage and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator may not be required. **Eye/Face Protection** Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) Value Components Exposure time Exposure type List: Titanium dioxide 10 mg/m3 Time Weighted Average Dust. ACGIH (TWA): Titanium dioxide 15 mg/m3 PEL: Total dust. OSHA Z1 9. PHYSICAL AND CHEMICAL PROPERTIES : Liquid Form Evaporation rate : Not established : Viscous, Liquid : Not determined Appearance Specific Gravity Color : WHITE Bulk density : Not applicable. Odor : Very faint Vapor pressure : Not determined Melting point/range : Not applicable Vapor density : Not determined Boiling Point: : Not applicable : Not applicable. pН Water solubility : Immiscible **10. STABILITY AND REACTIVITY**

| Stability | : | Stable. |
|--------------------------|---|--|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |



MATERIAL SAFETY DATA SHEET

D2314 WHITE-70

| vision Date 10/16/2002 | | | Page 4 c Print Date 11/6/20 |
|---|--|---|--|
| Incompatible Materials | | | oxidizing agents. Avoid contact I copolymers during processing. |
| Hazardous decomposition products | (NOx), hydro | gen chloride (HCl), oth | oxide (CO), oxides of nitrogen her hazardous materials, and eating may result in product |
| | degradation. after one hour | As a general rule of the | umb, degradation begins to occur ter 10 minutes at 204 °C (400 °F), °F). |
| | degradation. after one hour and within 5 r | As a general rule of the at 177 °C (350 °F), af | ter 10 minutes at 204 °C (400 °F), °F). |
| health data for the individuation <u>Toxicity Overview</u> | degradation. after one hour and within 5 r 11. TOXICOLOG evaluated as a whole for al components which co | As a general rule of the r at 177 °C (350 °F), aff minutes at 232 °C (450 ICAL INFORMATIO health effects. Expose omprise the mixture. | ter 10 minutes at 204 °C (400 °F), °F). |
| health data for the individuation <u>Toxicity Overview</u> | degradation. after one hour and within 5 r 11. TOXICOLOG evaluated as a whole for al components which co | As a general rule of the r at 177 °C (350 °F), aff minutes at 232 °C (450 ICAL INFORMATIO health effects. Expose omprise the mixture. | ter 10 minutes at 204 °C (400 °F), °F). ON ure effects listed are based on exist |

| Persistence and degradability | : Not readily biodegradable. |
|-------------------------------|--|
| Environmental Toxicity | : Environmental toxicity has not been established for this mixture as a whole. |
| Bioaccumulation Potential | : No data available. |
| Additional advice | : No data available. |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Refer to specific regulation. |
| | 4/6 |



MATERIAL SAFETY DATA SHEET

| D2314 | WHITE-70 |
|-------|----------|
| DZJ14 | |

| sion Number 1.0 ision Date 10/16/2002 | | Page 5 Print Date 11/6/2 |
|--|-----|---|
| ICAO/IATA | : | Refer to specific regulation. |
| IMO / IMDG | : | Refer to specific regulation. |
| | 15 | . REGULATORY INFORMATION |
| US Regulations: | | |
| OSHA Status | : | Classified as hazardous based on components. |
| TSCA Status | : | All components of this product are listed on the TSCA inventory or are exempt. |
| US. EPA CERCLA Hazardous | Sub | stances (40 CFR 302) |
| Not applicable | | |
| California Proposition 65 | : | WARNING! This product contains a chemical known in the State of California to cause cancer. |
| SARA Title III Section 302 Ext Not applicable | rem | ely Hazardous Substance |
| Canadian Regulations: | | |
| WHMIS Classification | : | D2B |
| DSL | : | Listed. |
| National Inventories: | | |
| Australia AICS | : | Not determined. |
| China IECS | : | Not determined. |
| Europe EINECS | : | Not determined. |
| Japan ENCS | : | Not determined. |
| Korea KECI | : | Listed. |
| Philippines PICCS | : | Not determined. |
| | | 16. OTHER INFORMATION |
| | | |
| | | |
| | | |



MATERIAL SAFETY DATA SHEET

D2314 WHITE-70

Version Number 1.0 Revision Date 10/16/2002 Page 6 of 6 Print Date 11/6/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.