

MATERIAL SAFETY DATA SHEET

D2383A BK ARDEN MATTE-60

Version Number 1.0 Revision Date 10/16/2002 Page 1 of 6 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	D2383A BK ARDEN MATTE-60
Product code	:	FO00003250
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

D2383A BK ARDEN MATTE-60

Version Number 1.0 Revision Date 10/16/2002 Page 2 of 6 Print Date 11/6/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
(5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize



MATERIAL SAFETY DATA SHEET

D2383A BK ARDEN MATTE-60

(TWA): black	ate 11/6/2
and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator may not be reference of the spirator	
Respiratory protection : Under normal handling conditions a respirator may not be re Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety Considerations : Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Components Value Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black Dalack 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance Color : NOT APPLICABLE Bulk density : Not dette Boiling Point/range Odor : Very faint Vapor gensure : Not dette Boiling Point/range Boiling Point: : Not applicable pH : Not app <td>bsorption</td>	bsorption
Eye/Face Protection : Safety glasses with side-shields. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Total dust. as carbon in the propriate exhaust ventilation. Pro black Carbon black 3.5 mg/m3 Time Weighted Average is a carbon in the propriate exhaust ventilation. Generance : Value Exposure time is a carbon in the propriate exhaust ventilation. Carbon black 3.5 mg/m3 PEL: Total dust. as carbon is black Carbon black : : Specific Gravity :: Not esta Appearance :: Viscous, Liquid Specific Gravity :: Not dett Boiling Point/range :: Not applicable Viscous, Liquid Specific Gravity :: Not dett Boiling Point:: Not applicable Udor <	
Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety Considerations : Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Components Value Exposure time Carbon black 3.5 mg/m3 Time Weighted Average Total dust, as carbon black Carbon black 3.5 mg/m3 PEL: Total dust, as carbon black Condect place Stability : Liquid Evaporation rate : Not esta Appearance Color : NOT APPLICABLE Bulk density : Not dett Boiling Point/range Boiling Point: : Not applicable Yapor density : Not dett Boiling Point/range Stability : Stable. : Stable. : Stable.	required.
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety. General Hygiene : Handle in accordance with good industrial hygiene and safety. Considerations : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Meat only in areas with appropriate exhaust ventilation. Pro black Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon of black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon of black O Stapearance : Liquid Evaporation rate : Not expo Odor : Wiscous, Liquid Specific Gravity : Not detc Boiling point/range : Not applicable Vapor density : Not detc Boiling Point: <td< td=""><td></td></td<>	
Additional Protective Measures : Safety shoes. Measures : Handle in accordance with good industrial hygiene and safety Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Pro back Components Value Exposure time Carbon black 3.5 mg/m3 Time Weighted Average Total dust. as carbon Carbon black 3.5 mg/m3 PEL: Total dust. as carbon Condext Stability : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Golor : Not applicable Vapor density : Not dete Boiling point: : Not applicable PH : Not applicable	
Measures Form Form Handle in accordance with good industrial hygiene and safety. Wash hands before breaks and at the end of workday. Engineering measures Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) Exposure time Exposure type Components Value Exposure time Exposure type Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black D Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black D PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance Color : NOT APPLICABLE Bulk density : Not app Odor : NOt applicable Vapor pressure : Not dett Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Stability : Stable.	
Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Pro appropriate exhaust ventilation at machinery. Exposure limit(s) 	
appropriate exhaust ventilation at machinery. Exposure limit(s) Components Value Exposure time Exposure type Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black C PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Odor : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Boiling point/range : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability : Stable.	ty practice
Components Value Exposure time Exposure type Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black C Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black C PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Boiling Point: : Not applicable PH : Not app Water solubility : Immiscible Not app Stability : Stable.	ovide
Carbon black 3.5 mg/m3 Time Weighted Average (TWA): Total dust. as carbon black Carbon black 3.5 mg/m3 PEL: Total dust. as carbon black Carbon black Output 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Boiling point/range : Not applicable pH : Not app Water solubility : Immiscible : Not app 10. STABILITY AND REACTIVITY Stability : Stable.	
Carbon black 3.5 mg/m3 PEL: Dack Ortal dust. as carbon black 9. PHYSICAL AND CHEMICAL PROPERTIES 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Melting point/range : Not applicable Vapor density : Not dete Boiling Point: : Not applicable pH : Not app Mater solubility : Immiscible 10. STABILITY AND REACTIVITY Stable.	List:
black 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Melting point/range : Not applicable Vapor density : Not dete Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability Stability : Stable.	ACGIH
Form : Liquid Evaporation rate : Not esta Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Melting point/range : Not applicable Vapor density : Not dete Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability : Stable. : Stable. : Stable.	OSHA Z1
Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Melting point/range : Not applicable Vapor density : Not dete Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability Stability : Stable.	
Appearance : Viscous, Liquid Specific Gravity : Not dete Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Melting point/range : Not applicable Vapor density : Not dete Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability Stability : Stable.	tablished
Color : NOT APPLICABLE Bulk density : Not app Odor : Very faint Vapor pressure : Not dete Melting point/range : Not applicable Vapor density : Not dete Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible . . IO. STABILITY AND REACTIVITY Stability : Stable.	
Odor : Very faint Vapor pressure : Not determinant Melting point/range : Not applicable Vapor density : Not determinant Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability : Stable.	
Melting point/range : Not applicable Vapor density : Not determining point: Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible Immiscible Immiscible Stability : Stable.	
Boiling Point: : Not applicable pH : Not app Water solubility : Immiscible : Immiscible : Immiscible 10. STABILITY AND REACTIVITY Stability : Stable.	
Water solubility : Immiscible 10. STABILITY AND REACTIVITY Stability : Stable.	
Stability : Stable.	plicable.
Hazardous Polymerization : Will not occur	
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid	id thermal

3/6



MATERIAL SAFETY DATA SHEET

D2383A BK ARDEN MATTE-60

Version Number 1.0 Revision Date 10/16/2002		Page 4 of 6 Print Date <i>11/6/2011</i>
		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

D2383A BK ARDEN MATTE-60

Version Number 1.0 Revision Date 10/16/2002 Page 5 of 6 Print Date 11/6/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OS Regulations.	
OSHA Status	: Classified as hazardous based on components.

5/6



MATERIAL SAFETY DATA SHEET

D2383A BK ARDEN MATTE-60

Version Number 1.0 Revision Date 10/16/2002 Page 6 of 6 Print Date 11/6/2011

US EDA CEDCI A Hazarda	and Sub	exempt.				
US. EPA CERCLA Hazardous Substances (40 CFR 302)						
Not applicable						
California Propositio 65	n :	WARNING! This product contains a chemical known in the State of California to cause cancer.				
Canadian Regulations:						
WHMIS Classification	on :	D2A				
DSL	:	Listed.				
National Inventories:						
Australia AICS	:	Not determined.				
China IECS	:	Not determined.				
Europe EINECS	:	Not determined.				
Japan ENCS	:	Not determined.				
Korea KECI	:	Listed.				
Philippines PICCS	:	Not determined.				
		16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.