

MATERIAL SAFETY DATA SHEET

D2680 BLACK

Version Number 1.0 Page 1 of 8
Revision Date 10/16/2002 Print Date 11/6/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION

2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY : Product Stewardship, (314) 771-1800

TELEPHONE

number

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident).

Product name : D2680 BLACK
Product code : FO00003282
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

| Components | CAS-No. | Weight % |
|-------------------|-----------|----------|
| Carbon black | 1333-86-4 | 0.1 - 1 |
| Vinyl acetate | 108-05-4 | 0.1 - 1 |
| Calcium carbonate | 1317-65-3 | 1 - 5 |
| Calcium oxide | 1305-78-8 | 1 - 5 |
| Resorcinol | 108-46-3 | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Inhalation of airborne droplets may cause irritation of the respiratory

tract.

Ingestion : May be harmful if swallowed. Eyes : May cause eye/skin irritation.

Skin : Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

D2680 BLACK

Version Number 1.0 Page 2 of 8 Revision Date 10/16/2002 Print Date 11/6/2011

Chronic exposure : Refer to Section 11 for Toxicological Information.

Medical Conditions

Aggravated by Exposure:

: None known.

4. FIRST AID MEASURES

Inhalation Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist, or in all cases of

doubt, seek medical advice.

: Do not induce vomiting without medical advice. When symptoms Ingestion

persist, or in all cases of doubt, seek medical advice.

Rinse immediately with plenty of water for at least 15 minutes. If eye Eyes

irritation persists, seek medical attention.

Skin Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available.

Flammable Limits

Upper explosion limit No data available. Lower explosion limit No data available. Autoignition temperature Not applicable.

Suitable extinguishing media Carbon dioxide blanket, dry powder, foam, Water spray.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, Methods for cleaning up

> universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper

disposal methods.

7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

D2680 BLACK

 Version Number 1.0
 Page 3 of 8

 Revision Date 10/16/2002
 Print Date 11/6/2011

Handling : Heat only in areas with appropriate exhaust ventilation. Processing

fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

accumulation of these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Store in a cool dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : Under normal handling conditions a respirator may not be required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

: Safety shoes.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)



MATERIAL SAFETY DATA SHEET

D2680 BLACK

Version Number 1.0 Page 4 of 8 Revision Date 10/16/2002 Print Date 11/6/2011

| Components | Value | Exposure time | Exposure type Lis | |
|-------------------|--------------------|-----------------------------------|--------------------------------|---------|
| Calcium carbonate | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | ACGIH |
| Calcium carbonate | 5 mg/m3 | PEL: | Respirable dust. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| Calcium oxide | 2 mg/m3 | Time Weighted Average (TWA): | Dust. | ACGIH |
| Calcium oxide | 5 mg/m3 | PEL: | Dust. | OSHA Z1 |
| Carbon black | 3.5 mg/m3 | Time Weighted Average (TWA): | Total dust. as carbon black | ACGIH |
| Carbon black | 3.5 mg/m3 | PEL: | Total dust. as carbon black | OSHA Z1 |
| Vinyl acetate | 10 ppm 35 mg/m3 | Time Weighted Average (TWA): | Total vapor and aerosol. | ACGIH |
| | 15 ppm 53 mg/m3 | Short Term Exposure Limit (STEL): | Total vapor and aerosol. | ACGIH |
| Resorcinol | 10 ppm 45 mg/m3 | Time Weighted Average (TWA): | Total dust. | ACGIH |
| | 20 ppm 90 mg/m3 | Short Term Exposure Limit (STEL): | Total dust. | ACGIH |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid Evaporation rate Not established Appearance : Viscous, Liquid Specific Gravity Not determined Color : BLACK Bulk density : Not applicable. : Very faint Vapor pressure Not determined Odor : Not applicable Melting point/range Vapor density Not determined Boiling Point: : Not applicable pН Not applicable.

Water solubility : Immiscible

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product

degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F),

and within 5 minutes at 232 $^{\circ}\text{C}$ (450 $^{\circ}\text{F}).$



MATERIAL SAFETY DATA SHEET

D2680 BLACK

Version Number 1.0 Revision Date 10/16/2002

Page 5 of 8 Print Date 11/6/2011

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u>
This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ | |
|-----------|-------------------|------------------|---------------------------------|--|
| 1333-86-4 | Carbon black | Systemic effects | Eyes, Respiratory system. | |
| 108-05-4 | Vinyl acetate | Irritant | Eyes, Respiratory system. | |
| | | Systemic effects | Eyes, Skin, Respiratory system. | |
| 1317-65-3 | Calcium carbonate | Irritant | Eyes, Skin. | |
| | | Systemic effects | Eyes, Skin, Respiratory system. | |
| 1305-78-8 | Calcium oxide | Irritant | Skin. | |
| | | Systemic effects | Eyes, Skin, Respiratory system. | |
| | | Corrosive | Skin. | |
| 108-46-3 | Resorcinol | Irritant | Eyes, Skin, Respiratory system. | |
| | | Systemic effects | blood and blood forming | |
| | | | system, Liver, Kidney, heart or | |
| | | | circulatory system. | |
| | | toxic | Refer to LC50 / LD50 Data on | |
| | | | MSDS | |

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|---------------|-------------|----------------|---------|
| 1333-86-4 | Carbon black | Oral LD50 | > 15,400 mg/kg | rat |
| | | Dermal LD50 | > 3 gm/kg | rabbit |
| 108-05-4 | Vinyl acetate | LC50 | 11400 mg/m3 | rat |
| | | Oral LD50 | 2,920 mg/kg | rat |
| | | Dermal LD50 | 2,335 mg/kg | rabbit |
| 108-46-3 | Resorcinol | Oral LD50 | 200 mg/kg | mouse |
| | | Dermal LD50 | 3,360 mg/kg | rabbit |

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|-----------|---------------|------|------|-----|
| 1333-86-4 | Carbon black | no | 2B | no |
| 108-05-4 | Vinyl acetate | no | 2B | no |

IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.



MATERIAL SAFETY DATA SHEET

D2680 BLACK

 Version Number 1.0
 Page 6 of 8

 Revision Date 10/16/2002
 Print Date 11/6/2011

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Resorcinol 108-46-3 May cause the formation of methemoglobin resulting in a reduced ability of the blood to carry oxygen: a symptom of this may be cyanosis (purplish blue coloration of the skin, lips and fingernails).

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Environmental toxicity has not been established for this mixture as a

whole.

Bioaccumulation Potential : No data available.

Additional advice : No data available.

13. DISPOSAL CONSIDERATIONS

Product : Where possible, recycling is preferred to disposal or incineration. The

generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.



MATERIAL SAFETY DATA SHEET

D2680 BLACK

Version Number 1.0 Page 7 of 8
Revision Date 10/16/2002 Print Date 11/6/2011

IMO / IMDG : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on the TSCA inventory or are

exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition : WARNING! This product contains a chemical known in the State of

65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance Not applicable

SARA Title III Section 313 Toxic Chemicals:

| Chemical Name | CAS-No. | Weight % |
|-----------------------|----------|----------|
| VINYL ACETATE MONOMER | 108-05-4 | 00.15 |
| VINYL ACETATE | | |

Canadian Regulations:

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

| CAS-No. |
|-----------|
| 1305-78-8 |
| 100-97-0 |
| 108-46-3 |

DSL : Listed.

National Inventories:

Australia AICS : Listed.

China IECS : Not determined.

Europe EINECS : Not determined.



MATERIAL SAFETY DATA SHEET

D2680 BLACK

 Version Number 1.0
 Page 8 of 8

 Revision Date 10/16/2002
 Print Date 11/6/2011

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.