

MATERIAL SAFETY DATA SHEET

D2853 BLACK

Version Number 1.1 Revision Date 07/07/2004

Page 1 of 7 Print Date *11/15/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	: :	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	D2853 BLACK
Product code	:	FO00003304
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Bisphenol A - Epichlorohydrin polymer	25068-38-6	1 - 5
Lead oxide sulfate (Pb4O3(SO4))	12202-17-4	1 - 5
Barium sulfate	7727-43-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	e: : Inhalation, Skin contact, Ingestion			
Acute exposure				
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.			
Ingestion	: May be harmful if swallowed.			
Eyes	: May cause eye/skin irritation.			
Skin	: Experience shows no unusual dermatitis hazard from routine handling.			
Chronic exposure	: Refer to Section 11 for Toxicological Information.			



MATERIAL SAFETY DATA SHEET **D2853 BLACK**

Version Number 1.1 Revision Date 07/07/2004 Page 2 of 7 Print Date 11/15/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide: of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **D2853 BLACK**

Version Number 1.1 Revision Date 07/07/2004		Page 3 of 7 Print Date 11/15/2011				
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.				
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8. EXPOS	SUI	RE CONTROLS / PERSONAL PROTECTION				
Respiratory protection	:	No personal respiratory protective equipment normally required.				
Eye/Face Protection	:	Safety glasses with side-shields.				
Hand protection	:	Protective gloves.				
Skin and body protection	:	Long sleeved clothing.				
Additional Protective Measures	:	Safety shoes.				
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Barium sulfate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Lead oxide sulfate (Pb4O3(SO4))	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	OSHA
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 BLACK
 Very faint
 Not applicable
 Not applicable
 Immiscible
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not established
 Not determined
 Not applicable
 Not determined
 Not determined
 Not determined
 Not applicable



MATERIAL SAFETY DATA SHEET **D2853 BLACK**

Version Number 1.1 Revision Date 07/07/2004

Page 4 of 7 Print Date *11/15/2011*

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25068-38-6	Bisphenol A -	Irritant	Skin.
	Epichlorohydrin polymer		
		sensitizer	Skin.
12202-17-4	Lead oxide sulfate	Systemic effects	reproductive system, central
	(Pb4O3(SO4))		nervous system (CNS).
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
25068-38-6	Bisphenol A -	Oral LD50	11,400 mg/kg	rat
	Epichlorohydrin polymer	Dermal LD50	> 6,000 mg/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No. Chemical M	Name OSHA	IARC	NTP
--------------------	-----------	------	-----



MATERIAL SAFETY DATA SHEET

D2853 BLACK

Version Number 1.1 Revision Date 07/07/2004 Page 5 of 7 Print Date 11/15/2011

	Lead oxide sulfate Pb4O3(SO4))	no	2B	no
	cations: wn to be a human carcinoge onably anticipated to be a h			
	D3(SO4)) 12202-17-4 Sy bdominal pain, anemia, pa			
Persistence and degradabi				
Environmental Toxicity	: Environmental to whole.	oxicity has not been e	stablished for th	is mixture as a
Bioaccumulation Potentia	l : No data availabl	e		
Additional advice	: No data availabl	e		
	13. DISPOSAL CO	ONSIDERATIONS		
Product	generator of was classification, tra	recycling is preferred te material has the res ansportation and dispo al, state/provincial and	sponsibility for posal in accordance	proper waste be with
Contaminated packaging	has the responsil	ferred when possible. bility for proper waste accordance with appli- ions.	classification, t	ransportation
	14. TRANSPORT	INFORMATION		
U.S. DOT Classification	: Refer to specific	regulation.		
U.S. DOT Classification ICAO/IATA (air)	: Refer to specific : Refer to specific	-		

15. REGULATORY INFORMATION



MATERIAL SAFETY DATA SHEET **D2853 BLACK**

Version Number 1.1 Revision Date 07/07/2004			Print Da	Page 6 of 7 te 11/15/2011
US Regulations:				
OSHA Status :	Classified as hazardous	s based on compon	ents.	
TSCA Status :	All components of this Inventory.	product are listed	on or exempt from	m the TSCA
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)			
Not applicable				
California Proposition : 65	WARNING! This pro- California to cause can chemical known to the other reproductive harn	cer., WARNING! State of California	This product co	ntains a
SARA Title III Section 302 Extrem	ely Hazardous Substance	e		
Not applicable				
SARA Title III Section 313 Toxic C	Chemicals:			
Chemical Name		CAS-No.	Weight %	
LEAD COMPOUNDS, INC	DRGANIC	12202-17-4	1.44	
Canadian Regulations:				
N. C. I. D. H. G. G. D. L. G. T				
National Pollutant Release In Chemical Name	iventory (NPRI)	CAS-No.	Weight % NPI	RI ID#
Lead oxide sulfate (Pb4O3(SO	4))	12202-17-4	1.44 246	5
WHMIS Classification : WHMIS Ingredient Disclosu CAS-No. 12202-17-4	2			
DSL :	All components of this Substances List (DSL)		e Canadian Dom	estic
National Inventories:				
Australia AICS :	Not determined			



MATERIAL SAFETY DATA SHEET **D2853 BLACK**

Version Number 1.1 Revision Date 07/07/2004

Page 7 of 7 Print Date 11/15/2011

China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.