

MATERIAL SAFETY DATA SHEET

DB3053B YELLOW

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3053B YELLOW
Product code	:	FO00003813
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

DB3053B YELLOW

Version Number 1.0 Page 2 of 6 Revision Date 06/11/2002 Print Date 11/5/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist, or in all cases of doubt, seek medical advice. Eyes Rinse immediately with plenty of water for at least 15 minutes. If eye : irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point No data available. : Flammable Limits Upper explosion limit No data available. : Lower explosion limit No data available. : Autoignition temperature Not applicable. : Carbon dioxide blanket, dry powder, foam, Water spray. Suitable extinguishing media : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under : Hazards fire conditions. 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, Methods for cleaning up : universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Heat only in areas with appropriate exhaust ventilation. Processing ÷ fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize



MATERIAL SAFETY DATA SHEET

DB3053B YELLOW

sion Number 1.0 ision Date 06/11/2002				Print I	Page 3 Date 11/5/2
	a	ccumulation of these mat	erials.		
Storage		Leep containers dry and tind contamination. Store			absorption
8. E	XPOSURE	CONTROLS / PERSO	NAL PROTECTI	ON	
Respiratory protection	: U	Inder normal handling co	nditions a respirato	or is not req	uired.
Eye/Face Protection	: S	afety glasses with side-sh	iields.		
Hand protection	: P:	rotective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with Vash hands before breaks			afety practice
Engineering measures		leat only in areas with ap ppropriate exhaust ventil			Provide
Exposure limit(s)					T
Components Calcium carbonate	Value 10 mg/m3	Exposure time Time Weighted Avera	Exposur age Total		List: ACGIH
Calcium caroonate	10 Ing/115	(TWA):		uusi.	ACOM
Calcium carbonate	5 mg/m3	PEL:	Respirab		OSHA Z1
	15 mg/m3	PEL:	Total	dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES		
Form	: Liqui	id E	Evaporation rate	: Not	established
Appearance			pecific Gravity		determined
Color			Bulk density		applicable.
Odor			apor pressure		determined
Melting point/range			apor density		determined
Boiling Point: Water solubility	: Not a : Imm		θH	: Not	applicable.
water solubility	: Imm	iscible			
	10. S	STABILITY AND REA	CTIVITY		
Stability	: S	table.			
Hazardous Polymerization	1 : W	Vill not occur.			
Conditions to avoid	: K	Leep away from oxidizing	g agents and open f	lame. To a	void thermal



MATERIAL SAFETY DATA SHEET

DB3053B YELLOW

Version Number 1.0 Revision Date 06/11/2002		Page 4 of 6 Print Date 11/5/2011
		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
	: Not regulated for transportation.



MATERIAL SAFETY DATA SHEET

DB3053B YELLOW

sion Number 1.0 vision Date 06/11/2002		Page 5 o Print Date 11/5/20
Classification (Non-bulk ground)		
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
65 Canadian Regulations:		California to cause cancer.
65 Canadian Regulations: WHMIS Classification	:	California to cause cancer. D2A
65 Canadian Regulations:	:	California to cause cancer. D2A
65 Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No.	:	California to cause cancer. D2A
65 Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 75-01-4	: closu:	California to cause cancer. D2A re List
65 Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 75-01-4 DSL	: closu:	California to cause cancer. D2A re List
65 Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 75-01-4 DSL National Inventories:	: Plosu:	California to cause cancer. D2A re List Listed.
65 Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 75-01-4 DSL National Inventories: Australia AICS	: closu : :	California to cause cancer. D2A re List Listed. Not determined.
65 Canadian Regulations: WHMIS Classification WHMIS Ingredient Disc CAS-No. 75-01-4 DSL National Inventories: Australia AICS China IECS	: closu: : :	California to cause cancer. D2A re List Listed. Not determined. Listed.



MATERIAL SAFETY DATA SHEET

DB3053B YELLOW

Version Number 1.0 Revision Date 06/11/2002 Page 6 of 6 Print Date 11/5/2011

Philippines PICCS

: Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.