

MATERIAL SAFETY DATA SHEET

DB3347 BLACK

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 7 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DB3347 BLACK
Product code	:	FO00003895
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Calcium oxide	1305-78-8	1 - 5
Lead oxide sulfate (Pb4O3(SO4))	12202-17-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

DB3347 BLACK





Version Number 1.0 Page 2 of 7 Revision Date 06/11/2002 Print Date 11/5/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation : overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. : Do not induce vomiting without medical advice. When symptoms Ingestion persist, or in all cases of doubt, seek medical advice. Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point No data available. · Flammable Limits No data available. Upper explosion limit : Lower explosion limit No data available. : Autoignition temperature Not applicable. : Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in positive Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under : Hazards fire conditions. 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not • be allowed to enter drains, water courses or the soil. Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, : universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling : Heat only in areas with appropriate exhaust ventilation. Processing

MATERIAL SAFETY DATA SHEET



DB3347 BLACK Page 3 of 7 Version Number 1.0 Print Date 11/5/2011 Revision Date 06/11/2002 fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator is not required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures Heat only in areas with appropriate exhaust ventilation. Provide : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium oxide	2 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
Calcium oxide	5 mg/m3	PEL:	Dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average (TWA):	Total dust. as carbon black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Lead oxide sulfate	0.05	Time Weighted Average	as Pb	ACGIH
(Pb4O3(SO4))	mg/m3	(TWA):		
Lead oxide sulfate (Pb4O3(SO4))	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	OSHA
	0.03 mg/m3	OSHA Action level:	as Pb	OSHA
Lead oxide sulfate (Pb4O3(SO4))	0.15 mg/m3	Time Weighted Average (TWA):	Dust and fume. as Pb	MX OEL
	0.45 mg/m3	Short Term Exposure Limit (STEL):	Dust and fume. as Pb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

MATERIAL SAFETY DATA SHEET

DB3347 BLACK

PolyOne.

Version Number 1.0 Revision Date 06/11/2002		Page 4 of 7 Print Date 11/5/2011
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Liquid Evaporation r Viscous, Liquid Specific Grav BLACK Bulk density Very faint Vapor pressuut Not applicable Vapor density Not applicable pH Immiscible 	ity : Not determined : Not applicable. re : Not determined
	10. STABILITY AND REACTIVITY	
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from oxidizing agents and decomposition, do not overheat.	open flame. To avoid thermal
Incompatible Materials	: Incompatible with strong acids and oxi with acetal homopolymers and acetal c	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monox (NOx), hydrogen chloride (HCl), other smoke are all possible. Prolonged heat degradation. As a general rule of thum after one hour at 177 °C (350 °F), after and within 5 minutes at 232 °C (450 °F)	hazardous materials, and ting may result in product ab, degradation begins to occur 10 minutes at 204 °C (400 °F),

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
12202-17-4	Lead oxide sulfate (Pb4O3(SO4))	Systemic effects	reproductive system, central nervous system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit



MATERIAL SAFETY DATA SHEET

DB3347 BLACK

Version Number 1.0 Revision Date 06/11/2002 Page 5 of 7 Print Date 11/5/2011

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no
12202-17-4	Lead oxide sulfate (Pb4O3(SO4))	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Lead oxide sulfate (Pb4O3(SO4)) 12202-17-4 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with



MATERIAL SAFETY DATA SHEET

B3347 BLACK	Daga
sion Number 1.0 vision Date 06/11/2002	Page e Print Date 11/5/
	applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or a
	exempt.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Propositior 65	: WARNING! This product contains a chemical known in the State o California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
SARA Title III Section 313 T	oxic Chemicals:
Chemical Nan LEAD COMP	e CAS-No. Weight % DUNDS, INORGANIC 12202-17-4 1.99
Canadian Regulations:	
WHMIS Classificatio	n : D2A
WHMIS Ingredient Di	sclosure List

MATERIAL SAFETY DATA SHEET



DB3347 BLACK

Page 7 of 7 Version Number 1.0 Revision Date 06/11/2002 Print Date 11/5/2011 CAS-No. 1305-78-8 1333-86-4 12202-17-4 75-01-4 DSL : Listed. National Inventories: Australia AICS : Listed. China IECS : Listed. Europe EINECS : Not determined. Japan ENCS Not determined. : Korea KECI : Listed. Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.