

MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

Version Number 1.0 Revision Date 08/26/2002 Page 1 of 7 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DM150DOPO OPAQUE ORANGE
Product code	:	FO00004098
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Lead chromate	7758-97-6	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

Version Number 1.0 Revision Date 08/26/2002 Page 2 of 7 Print Date 11/5/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	:	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	::	No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize



MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

			Print	Page 3 Date 11/5/2
	a	ccumulation of these materials.		
Storage		Keep containers dry and tightly nd contamination. Store in a co		e absorption
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: U	Under normal handling conditio	ns a respirator may not	be required.
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	Protective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		safety practice
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide
Exposure limit(s)				
-	Value	Exposure time	Exposure type	List:
Exposure limit(s) Components Lead chromate	Value 0.012 mg/m3	Exposure time Time Weighted Average (TWA):	Exposure type Dust. as Cr	List: ACGIH
Components	0.012	Time Weighted Average		
Components	0.012 mg/m3 0.05	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL:	Dust. as Cr	ACGIH ACGIH
Components Lead chromate	0.012 mg/m3 0.05 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA):	Dust. as Cr as Pb	ACGIH ACGIH
Components Lead chromate Lead chromate	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average	Dust. as Cr as Pb as Cr	ACGIH ACGIH OSHA Z1
Components Lead chromate Lead chromate	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level:	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb	ACGIH ACGIH OSHA Z1 OSHA
Components Lead chromate Image: Components Lead chromate <	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3 9. PHYSIC	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level:	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb PERTIES	ACGIH ACGIH OSHA Z1 OSHA OSHA
Components Lead chromate Lead chromate Lead chromate	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3 9. PHYSIC : Liqu	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level:	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb PERTIES	ACGIH ACGIH OSHA Z1 OSHA OSHA t established
Components Lead chromate Lead chromate Lead chromate Form Appearance	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3 9. PHYSIO : Liqu : Visc	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level: CAL AND CHEMICAL PRO id Evapor Specifi	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb PERTIES ration rate : Not c Gravity : Not	ACGIH ACGIH OSHA Z1 OSHA OSHA t established t determined
Components Lead chromate Lead chromate Lead chromate Form Appearance Color	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3 9. PHYSIC : Liqu : Visc : ORA	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level: CAL AND CHEMICAL PRO id Evapor ous, Liquid NGE Bulk do	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb PERTIES ration rate : Not c Gravity : Not ensity : Not	ACGIH ACGIH OSHA Z1 OSHA OSHA OSHA
Components Lead chromate Lead chromate Lead chromate Form Appearance Color Odor	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3 9. PHYSIO : Liqu : Visc : ORA : Very	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level: CAL AND CHEMICAL PRO id Evapor ous, Liquid NGE Bulk do faint	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb PERTIES ration rate : Not c Gravity : Not ensity : Not pressure : Not	ACGIH ACGIH OSHA Z1 OSHA OSHA OSHA
Components Lead chromate Lead chromate Lead chromate Form Appearance Color	0.012 mg/m3 0.05 mg/m3 1 mg/m3 0.05 mg/m3 0.03 mg/m3 9. PHYSIO : Liqu : Visc : ORA : Very : Not	Time Weighted Average (TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): OSHA Action level: CAL AND CHEMICAL PRO id Evapor ous, Liquid NGE Bulk do faint	Dust. as Cr as Pb as Cr Dust. as Pb Dust. as Pb Dust. as Pb PERTIES ation rate : Not c Gravity : Not ensity : Not pressure : Not density : Not	ACGIH ACGIH OSHA Z1 OSHA OSHA OSHA

10. STABILITY AND REACTIVITY



MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

Version Number 1.0 Revision Date 08/26/2002		Page 4 of 7 Print Date <i>11/5/2011</i>
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7758-97-6	Lead chromate	Systemic effects	central nervous system,
			reproductive system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
7758-97-6	Lead chromate	no	no	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.



MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

Version Number 1.0 Revision Date 08/26/2002 Page 5 of 7 Print Date 11/5/2011

Additional Health Hazard Information:

Lead chromate 7758-97-6 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

Environme whole. No data av No data av 3. DISPOS Where pos generator classificati applicable Recycling has the res and dispos and local n 14. TRANS	vailable. vailable. AL CONSIDE ssible, recyclin of waste mater ion, transportate federal, state/j is preferred wisponsibility for sal in accordan regulations. PORT INFOF	ERATIONS ag is preferred to distrial has the responsition and disposal in provincial and local then possible. The g r proper waste class and the possible of the second second the second second second second second the second s	
whole. No data av No data av 3. DISPOS Where pos generator classificati applicable Recycling has the res and dispos and local n 14. TRANS	vailable. vailable. AL CONSIDE ssible, recyclin of waste mater ion, transportate federal, state/j is preferred wisponsibility for sal in accordan regulations. PORT INFOF	ERATIONS ag is preferred to dis rial has the responsi tion and disposal in provincial and local hen possible. The g r proper waste class ace with applicable f RMATION	sposal or incineration. Th ibility for proper waste a accordance with l regulations. generator of waste materia ification, transportation
No data av 3. DISPOS Where pos generator of classificati applicable Recycling has the res and dispos and local n 14. TRANS	vailable. AL CONSIDE ssible, recyclin of waste mater ion, transportate federal, state/j is preferred wisponsibility for sal in accordan regulations. PORT INFOF ated for transpon	ng is preferred to dis rial has the responsi tion and disposal in provincial and local then possible. The g r proper waste class the with applicable to RMATION	ibility for proper waste accordance with l regulations. generator of waste materia ification, transportation
3. DISPOSA Where pos generator of classificati applicable Recycling has the res and dispos and local n 14. TRANSI	AL CONSIDE ssible, recyclin of waste mater ion, transportate federal, state/j is preferred with sponsibility for sal in accordan regulations. PORT INFOF	ng is preferred to dis rial has the responsi tion and disposal in provincial and local then possible. The g r proper waste class the with applicable to RMATION	ibility for proper waste accordance with l regulations. generator of waste materia ification, transportation
Where pos generator classificati applicable Recycling has the res and dispos and local n 14. TRANS	ssible, recyclin of waste mater ion, transporta federal, state/j is preferred wisponsibility for sal in accordan regulations.	ng is preferred to dis rial has the responsi tion and disposal in provincial and local then possible. The g r proper waste class the with applicable to RMATION	ibility for proper waste accordance with l regulations. generator of waste materia ification, transportation
generator of classification applicable Recycling has the resonand dispose and local normal for the second 14. TRANS	of waste mater ion, transportate federal, state/j is preferred wisponsibility for sal in accordan regulations.	rial has the responsi tion and disposal in provincial and local then possible. The g r proper waste class the with applicable f RMATION	ibility for proper waste accordance with l regulations. generator of waste materia ification, transportation
has the res and dispos and local r 14. TRANS	sponsibility for sal in accordan regulations. PORT INFOF ated for transpo	r proper waste class ice with applicable f	ification, transportation
Not regula	ated for transpo		
-	-	ortation.	
Not regula			
	ated for transpo	ortation.	
Not regula	ated for transpo	ortation.	
5. REGULA	TORY INFO	RMATION	
Classified	as hazardous b	based on componen	nts.
All compo exempt.	onents of this p	roduct are listed on	the TSCA inventory or an
ostances (40	CFR 302)		
No.	% in Product	RQ for component	nt RQ for
08	Classified All compo exempt. stances (40	Classified as hazardous I All components of this p exempt. stances (40 CFR 302)	stances (40 CFR 302)



MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

Lead sulfate7446-14-20.0196010 lbs51,020 LBCalifornia Proposition 65:WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.SARA Title III Section 313 Toxic Chemicals: <a href="mailto:CAS-No. Weight % CAS-No. Weight % LEAD COMPOUNDS, INORGANIC Table CAS-No. Weight % Lead Compounds, INORGANIC Totor Chemicals:
65 California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm. SARA Title III Section 313 Toxic Chemicals: <u>Chemical Name</u> <u>CAS-No.</u> Weight % CHROMIUM VI COMPOUNDS IEAD COMPOUNDS, INORGANIC LEAD COMPOUNDS, INORGANIC
Chemical NameCAS-No.Weight %CHROMIUM VI COMPOUNDS7758-97-600.35LEAD COMPOUNDS, INORGANIC11LEAD COMPOUNDS, INORGANIC7446-14-200.01
CHROMIUM VI COMPOUNDS LEAD COMPOUNDS, INORGANIC7758-97-600.35LEAD COMPOUNDS, INORGANIC7446-14-200.01
LEAD COMPOUNDS, INORGANICLEAD COMPOUNDS, INORGANIC7446-14-200.01
LEAD COMPOUNDS, INORGANIC 7446-14-2 00.01
Canadian Regulations:
WHMIS Classification : D2A
WHMIS Ingredient Disclosure List
CAS-No. 7758-97-6
DSL : Listed.
National Inventories:
Australia AICS : Not determined.
China IECS : Not determined.
Europe EINECS : Not determined.
Japan ENCS : Not determined.
Korea KECI : Not determined.
Philippines PICCS : Not determined.
16. OTHER INFORMATION
6/7



MATERIAL SAFETY DATA SHEET

DM150DOPO OPAQUE ORANGE

Version Number 1.0 Revision Date 08/26/2002 Page 7 of 7 Print Date 11/5/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.