

MATERIAL SAFETY DATA SHEET

DM150DOPW OPAQ WHITE 72 DUR-S

Version Number 1.0 Revision Date 03/03/2003 Page 1 of 6 Print Date *11/10/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DM150DOPW OPAQ WHITE 72 DUR-S
Product code	:	FO00004100
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

DM150DOPW OPAQ WHITE 72 DUR-S

Version Number 1.0 Revision Date 03/03/2003 Page 2 of 6 Print Date 11/10/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.	eye
Skin	: Wash off with soap and plenty of water. If skin irritation persists s medical attention.	eek
	5. FIRE-FIGHTING MEASURES	
Flash point	: No data available.	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. 	
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under the statement of t	
Hazards	fire conditions.	
	. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should r be allowed to enter drains, water courses or the soil.	iot
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid bind universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for prope disposal methods.	
	7. HANDLING AND STORAGE	_
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize	5



MATERIAL SAFETY DATA SHEET

DM150DOPW OPAQ WHITE 72 DUR-S

					e 11/10/2
	a	ccumulation of these mater	ials.		
Storage		eep containers dry and tight do not contamination. Store in		moisture a	bsorption
8. H	XPOSURE	CONTROLS / PERSON	AL PROTECTION		
Respiratory protection	: U	nder normal handling conc	litions a respirator n	nay not be	required.
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: P	: Protective gloves.			
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety pract Wash hands before breaks and at the end of workday.				ety practice
Engineering measures		eat only in areas with appr ppropriate exhaust ventilati		ilation. P	rovide
Exposure limit(s)					
Components	Value	Exposure time	Exposure t	ype	List:
					List.
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):			ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL:		t.	
	15 mg/m3	(TWA):	e Dust. Total dus	t.	ACGIH
Titanium dioxide	15 mg/m3 9. PHYSIC	(TWA): PEL: CAL AND CHEMICAL F	e Dust. Total dus PROPERTIES		ACGIH OSHA Z1
Titanium dioxide	15 mg/m3 9. PHYSIC : Liqu	(TWA): PEL: CAL AND CHEMICAL F	e Dust. Total dus PROPERTIES aporation rate	: Not es	ACGIH OSHA Z1
Titanium dioxide	15 mg/m3 9. PHYSIC : Liqu : Visco	(TWA): PEL: CAL AND CHEMICAL F id Eva bus, Liquid Spe	e Dust. Total dus ROPERTIES aporation rate ecific Gravity	: Not es : Not de	ACGIH OSHA Z1 stablished etermined
Titanium dioxide	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI	(TWA): PEL: CAL AND CHEMICAL F id Eva ous, Liquid Spe TE Bu	E Dust. Total dus Total dus ROPERTIES aporation rate ecific Gravity lk density	: Not es : Not de : Not ap	ACGIH OSHA Z1
Titanium dioxide Form Appearance Color	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI : Very	(TWA): PEL: CAL AND CHEMICAL F id Eva ous, Liquid Spe TE Bu faint Va	e Dust. Total dus ROPERTIES aporation rate ecific Gravity	: Not es : Not de : Not ap : Not de	ACGIH OSHA Z1 stablished etermined oplicable.
Titanium dioxide Form Appearance Color Odor	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI : Very : Not a	(TWA): PEL: CAL AND CHEMICAL F id Eva ous, Liquid Spe TE Bu faint Va	e Dust. Total dus PROPERTIES aporation rate ecific Gravity lk density por pressure por density	: Not es : Not de : Not ar : Not de : Not de	ACGIH OSHA Z1 stablished etermined oplicable. etermined
Titanium dioxide Form Appearance Color Odor Melting point/range	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI : Very : Not a	(TWA): PEL: CAL AND CHEMICAL F id Eva bus, Liquid Spe TE Bu faint Va applicable Va applicable pH	e Dust. Total dus PROPERTIES aporation rate ecific Gravity lk density por pressure por density	: Not es : Not de : Not ar : Not de : Not de	ACGIH OSHA Z1 stablished etermined oplicable. etermined etermined
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI : Very : Not a : Imm	(TWA): PEL: CAL AND CHEMICAL F id Eva bus, Liquid Spe TE Bu faint Va applicable Va applicable pH	e Dust. Total dus PROPERTIES aporation rate ecific Gravity lk density por pressure por density	: Not es : Not de : Not a : Not de : Not de	ACGIH OSHA Z1 stablished etermined oplicable. etermined etermined
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI : Very : Not a : Not a : Imm 10. S	(TWA): PEL: CAL AND CHEMICAL F id Eva ous, Liquid Spe TE Bu faint Va applicable Va applicable pH iscible	e Dust. Total dus PROPERTIES aporation rate ecific Gravity lk density por pressure por density	: Not es : Not de : Not a : Not de : Not de	ACGIH OSHA Z1 stablished etermined oplicable. etermined etermined
Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	15 mg/m3 9. PHYSIC : Liqu : Visco : WHI : Very : Not a : Not a : Imm 10. S : S	(TWA): PEL: CAL AND CHEMICAL F id Eva bus, Liquid Spa TE Bu faint Va applicable PH iscible State	e Dust. Total dus PROPERTIES aporation rate ecific Gravity lk density por pressure por density	: Not es : Not de : Not a : Not de : Not de	ACGIH OSHA Z1 stablished etermined oplicable. etermined etermined



MATERIAL SAFETY DATA SHEET

DM150DOPW OPAQ WHITE 72 DUR-S

ersion Number 1.0			Page 4 of Print Date 11/10/201		
evision Date 03/03/2003			Plint Date 11/10/201		
Incompatible Materials			oxidizing agents. Avoid contact l copolymers during processing.		
Hazardous decomposition products	(NOx), hydro smoke are all degradation. after one hour	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).			
	11. TOXICOLOG	ICAL INFORMATIO	DN		
health data for the individual <u>Toxicity Overview</u>	aluated as a whole for components which co	health effects. Exposi mprise the mixture.	are effects listed are based on existin		
health data for the individual <u>Toxicity Overview</u>	aluated as a whole for components which co	health effects. Exposi mprise the mixture.			

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.



MATERIAL SAFETY DATA SHEET

DM150DOPW OPAQ WHITE 72 DUR-S

sion Date 03/03/2003					int Date 11/10/2
ICAO/IATA	:	Refer to specific	c regulation.		
IMO / IMDG	:	Refer to specific	c regulation.		
	15	S. REGULATOR	Y INFORMATIO	N	
US Regulations:					
OSHA Status	:	: Classified as hazardous based on components.			
TSCA Status	:	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardou	is Sub	stances (40 CFR	302)		
Chemical Name		CAS-No.	% in Product	RQ for component	RQ for Mixture/Prod uct
Vinyl chloride monom	er	75-01-4	0.0009	001 lbs	111,111 LB
California Proposition 65 SARA Title III Section 302 E		California to ca		s a chemical kno	wn to the State of
65		California to ca	use cancer.	s a chemical kno	wn to the State of
65 SARA Title III Section 302 E	Extrem	California to ca ely Hazardous Su	use cancer.	s a chemical kno	wn to the State of
65 SARA Title III Section 302 E Not applicable	Öxtrem Öoxic C	California to ca ely Hazardous Su	use cancer.	s a chemical kno	wn to the State of
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T	Öxtrem Öoxic C	California to ca ely Hazardous Su Chemicals:	use cancer.	s a chemical kno	wn to the State of
65 SARA Title III Section 302 E Not applicable	Öxtrem Öoxic C	California to ca ely Hazardous Su Chemicals: ot applicable	use cancer.	s a chemical kno	wn to the State of
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Canadian Regulations:	Öxtrem Öoxic C	California to ca ely Hazardous Su Chemicals: ot applicable D2B All component	use cancer.	on the Canadian	
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Canadian Regulations: WHMIS Classification DSL	Coxic C No n :	California to ca ely Hazardous Su Chemicals: ot applicable D2B All component	use cancer. Ibstance s of this product are	on the Canadian	
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Canadian Regulations: WHMIS Classification DSL	Coxic C No n :	California to ca ely Hazardous Su Chemicals: ot applicable D2B All component	use cancer. Ibstance s of this product are (DSL) or are exem	on the Canadian	
65 SARA Title III Section 302 E Not applicable SARA Title III Section 313 T Canadian Regulations: WHMIS Classification DSL National Inventories:	Öxic C No n : :	California to ca ely Hazardous Su Chemicals: ot applicable D2B All component Substances List	use cancer. Ibstance s of this product are (DSL) or are exem	on the Canadian	



MATERIAL SAFETY DATA SHEET

DM150DOPW OPAQ WHITE 72 DUR-S

Version Number 1.0 Revision Date 03/03/2003 Page 6 of 6 Print Date 11/10/2011

Japan ENCS	:	Not determined.

Korea KECI : Not determined.

Philippines PICCS : Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.