MATERIAL SAFETY DATA SHEET DM475BK BLACK HT #9250-002

Version Number 1.1 Revision Date 05/27/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	DM475BK BLACK HT #9250-002
Product code :	F000004205
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Trimethylopropane trimethacrylate	3290-92-4	10 - 30
Calcium oxide	1305-78-8	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET DM475BK BLACK HT #9250-002

Version Number 1.1 Revision Date 05/27/2004 Page 2 of 6 Print Date 11/14/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET DM475BK BLACK HT #9250-002

sion Number 1.1 ision Date 05/27/2004				Print D	Page 3 ate 11/14/	
Handling	fı P	ime condensates may c	ontain o , ducts,	iate exhaust ventilation. combustible or toxic resi and other surfaces to mi	due.	
Storage	: K		tightly	closed to avoid moisture	absorption	
8. E	XPOSURE	CONTROLS / PERS	ONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory	protecti	ve equipment normally r	equired.	
Eye/Face Protection	: S	afety glasses with side	-shields			
Hand protection	: P	rotective gloves.				
Skin and body protection	: L	ong sleeved clothing.				
Additional Protective Measures	: S	afety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures		leat only in areas with a ppropriate exhaust vent		iate exhaust ventilation. at machinery.	Provide	
Exposure limit(s)						
Components	Value	Value Exposure time		Exposure type	List:	
Calcium carbonate	5 mg/m3	PEL:		Respirable fraction.	OSHA Z	
	15 mg/m3	PEL:		Total dust.	OSHA Z	
Calcium oxide	2 mg/m3	2 mg/m3 Time Weighted Ave (TWA):		Dust.	ACGIH	
	5 mg/m3	PEL:		Dust.	OSHA Z	
	9. PHYSIC	CAL AND CHEMICA	L PRC	PERTIES		
Form Appearance Color Odor Melting point/range	: Visco : BLA : Very : Not a	 liquid Evaporation Viscous, liquid Specific Gr. BLACK Bulk densite Very faint Vapor presses Not applicable Vapour den pH Immiscible 		ic Gravity: : Not ensity : Not pressure : Not r density : Not	established determined applicable determined determined	
Boiling Point: Water solubility				: Not	applicable	
	10. 5	STABILITY AND RE	ACTIV	VITY		
		3/6				

MATERIAL SAFETY DATA SHEET DM475BK BLACK HT #9250-002

Version Number 1.1 Revision Date 05/27/2004 Page 4 of 6 Print Date 11/14/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
3290-92-4	Trimethylopropane trimethacrylate	Irritant	Eyes, Skin.
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available
Additional advice	:	No data available

13. DISPOSAL CONSIDERATIONS

Product

: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET DM475BK BLACK HT #9250-002

ion Number 1.1 sion Date 05/27/2004		Page 5 Print Date 11/14/2
		applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Sub	stances (40 CFR 302)
Not applicable		
California Proposition	:	WARNING! This product contains a chemical known to the State of
65		California to cause cancer.
SARA Title III Section 302 Ex	trem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 To	oxic C	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Rele	ase Iı	
Chemical Name		CAS-No. Weight % NPRI ID# 557-05-1 0.32 241
Zinc stearate		

PolyOne.

MATERIAL SAFETY DATA SHEET DM475BK BLACK HT #9250-002

Version Number 1.1 Revision Date 05/27/2004 Page 6 of 6 Print Date 11/14/2011

	WHMIS Classification	:	All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this
			product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.
Na	ational Inventories:		
	Australia AICS	:	Not determined
	China IECS	:	Not determined
	Europe EINECS	:	Not determined
	Japan ENCS	:	Not determined
	Korea KECI	:	Not determined
	Philippines PICCS	:	Not determined
			16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.