

MATERIAL SAFETY DATA SHEET

DM568G GREEN

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 6 Print Date 11/5/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DM568G GREEN
Product code	:	FO00004262
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Lead oxide sulfate (Pb4O3(SO4))	12202-17-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

DM568G GREEN

ion Number 1.0 sion Date 06/11/2002	Page 2 Print Date 11/5/2
	4. FIRST AID MEASURES
	7. FIRST AID WILASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits	
Upper explosion limit	: No data available.
Lower explosion limit	: No data available.
Autoignition temperature	: Not applicable.
Suitable extinguishing media	: Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting	Eullface self contained breathing apparatus (SCPA) used in positive
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

MATERIAL SAFETY DATA SHEET



DM568G GREEN Version Number 1.0 Page 3 of 6 Print Date 11/5/2011 Revision Date 06/11/2002 accumulation of these materials. : Keep containers dry and tightly closed to avoid moisture absorption Storage and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator is not required. **Eye/Face Protection** Safety glasses with side-shields. : Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s)

Components Value Exposure time Exposure type Lead oxide sulfate 0.05 Time Weighted Average as Pb (Pb4O3(SO4)) mg/m3 (TWA): Time Weighted Average Lead oxide sulfate 0.05 as Pb (Pb4O3(SO4)) mg/m3 (TWA): 0.03 OSHA Action level: as Pb mg/m3 Lead oxide sulfate 0.15 Time Weighted Average Dust and fume. as Pb (TWA):

9. PHYSICAL AND CHEMICAL PROPERTIES

Short Term Exposure Limit

(STEL):

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

(Pb4O3(SO4))

: Liquid : Viscous, Liquid : GREEN : Very faint : Not applicable : Not applicable : Immiscible

mg/m3

0.45

mg/m3

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН

Dust and fume. as Pb

: Not established : Not determined : Not applicable. : Not determined : Not determined : Not applicable.

List:

ACGIH

OSHA

OSHA

MX OEL

MX OEL

10. STABILITY AND REACTIVITY

MATERIAL SAFETY DATA SHEET





Version Number 1.0 Revision Date 06/11/2002		Page 4 of 6 Print Date <i>11/5/2011</i>
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12202-17-4	Lead oxide sulfate	Systemic effects	reproductive system, central
	(Pb4O3(SO4))		nervous system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
12202-17-4	Lead oxide sulfate (Pb4O3(SO4))	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Lead oxide sulfate (Pb4O3(SO4)) 12202-17-4 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".



MATERIAL SAFETY DATA SHEET

DM568G GREEN

ision Date 06/11/2002	Print Date 11/5/
	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or an exempt.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	



MATERIAL SAFETY DATA SHEET

DM568G GREEN

on Number 1.0 ion Date 06/11/2002		Print Date	2age 11/5
65 California to caus	e cancer., WARN n the State of Cal	a chemical known in the S ING! This product contain fornia to cause birth defec	ns a
SARA Title III Section 313 Toxic Chemicals:			
Chemical Name	CAS-No.	Weight %	
LEAD COMPOUNDS, INORGANIC	12202-17-4	2.62	
Canadian Regulations: WHMIS Classification : D2A			
WHMIS Ingredient Disclosure List			
CAS-No. 1305-78-8 12202-17-4 1310-73-2 75-01-4			
DSL : Listed.			
National Inventories:			
Australia AICS : Listed.			
China IECS : Listed.			
Europe EINECS : Not determined.			
Japan ENCS : Not determined.			
Korea KECI : Not determined.			
Philippines PICCS : Listed.			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.