

F216C YELLOW FM

Version Number 1.7 Page 1 of 18 Revision Date 03/03/2015 Print Date 03/04/2015

SAFETY DATA SHEET

F216C YELLOW FM

Section 1. Identification

GHS product identifier F216C YELLOW FM

Chemical name Mixture CAS number Mixture FO00004447 Other means of identification **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

Supplier's details POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

CARCINOGENICITY - Category 1A

Supplemental label elements None known. Hazards not otherwise classified None known.



F216C YELLOW FM

Version Number 1.7 Page 2 of 18 Revision Date 03/03/2015 Print Date 03/04/2015

Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO00004447

CAS number/other identifiers

Ingredient name	%	CAS number
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters,	5 - 10	68515-48-0
C9-rich		
Lead chromate	1 - 5	7758-97-6
Chrome yellow (Lead chromate pigment)	0.1 - 1	1344-37-2
Titanium dioxide	0.1 - 1	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,



F216C YELLOW FM

Version Number 1.7 Page 3 of 18 Revision Date 03/03/2015 Print Date 03/04/2015

belt or waistband.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated

> clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Wash out mouth with water. Remove dentures if any. Remove victim Ingestion

> to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing

such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact No known significant effects or critical hazards. No known significant effects or critical hazards. Inhalation No known significant effects or critical hazards. Skin contact Ingestion No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eve contact No specific data. Inhalation No specific data. Skin contact No specific data. **Ingestion** No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

No specific treatment. Specific treatments

Protection of first-aiders No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation. Wash contaminated clothing



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 4 of 18 Print Date 03/04/2015

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway,

sewer or drain.

Hazardous thermal decomposition products

May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. But on appropriate personal protective equipment.

inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of

any information in Section 8 on suitable and unsuitable materials. See

also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil,



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 5 of 18 Print Date 03/04/2015

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8).

Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage,

Store in accordance with local regulations. Store in original container



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015

Page 6 of 18 Print Date 03/04/2015

including any incompatibilities

protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
Lead chromate	ACGIH TLV (2012-03-05) Calculated as Cr		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 0.012 mg/m3		
	ACGIH TLV (1994-09-01) Calculated as Pb		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 0.05 mg/m3		
	OSHA PEL (2006-11-27) Calculated as Cr		
	PEL: Permissible Exposure Level 0.005 mg/m3		
	OSHA PEL Z2 (2006-11-27)		
	Ceiling 0.001 mg/m3		
	NIOSH REL (2010-09-01) Calculated as Cr		
	Time Weighted Average (TWA) 0.0002 mg/m3		
	OSHA PEL 1989 (1989-03-01) Calculated as CrO3		
	Ceiling 0.1 mg/m3		
	OSHA PEL 1989 (1989-03-01) Calculated as Pb		
	PEL: Permissible Exposure Level 0.075 mg/m3		
Chrome yellow (Lead chromate pigment)	OSHA PEL (2006-11-27) Calculated as Cr		
Chrome yenow (Lead enromate pigment)	PEL: Permissible Exposure Level 0.005 mg/m3		
	NIOSH REL (2010-09-01) Calculated as Cr		
	Time Weighted Average (TWA) 0.0002 mg/m3		
	OSHA PEL 1989 (1989-03-01) Calculated as Pb		
	PEL: Permissible Exposure Level 0.075 mg/m3		
	ACGIH TLV (1995-05-23) Calculated as Pb		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 0.05 mg/m3		
	ACGIH TLV (1994-09-01) Calculated as Cr		
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:		
	Permissible Exposure Level 0.05 mg/m3		
	6/18		



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 7 of 18 Print Date 03/04/2015

Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<u>Individual protection measures</u>	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 8 of 18 Print Date 03/04/2015

different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe working limits

of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state liquid [liquid] Color YELLOW Odor Not available. **Odor threshold** Not available. Not available. pН Not available. **Melting point** Not available. **Boiling** point Not available. Flash point **Burning time** Not available. **Burning** rate Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.SolubilityNot available.Solubility in waterNot available.Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 9 of 18 Print Date 03/04/2015

Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich					
	LD50 Oral	Rat	10,000 mg/kg	-	
Lead chromate					
Chrome yellow (Lead chromat	e pigment)				
Titanium dioxide					
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	

Conclusion/Summary : Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,2-Benzenedicarboxylic	Eyes - Mild	Rabbit			-
acid, di-C8-10-branched	irritant				
alkyl esters, C9-rich					

Conclusion/Summary

Skin : Mixture.Not fully tested.



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 10 of 18 Print Date 03/04/2015

Eyes: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Classification			
Product/ingredient	OSHA	IARC	NTP
name			
Lead chromate	+	1	Known to be a human carcinogen. Reasonably
			anticipated to be a human carcinogen.
Chrome yellow (Lead	+	1	
chromate pigment)			
Titanium dioxide		2B	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of :

Not available.

exposure



F216C YELLOW FM

Version Number 1.7 Page 11 of 18 Revision Date 03/03/2015 Print Date 03/04/2015

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Mixture.Not fully tested.

General : No known significant effects or critical hazards.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 12 of 18 Print Date 03/04/2015

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide			
	Acute LC50 1,000,000 μg/l Marine water	Fish - Mummichog	96 h
	Acute LC50 1,000 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 5.5 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 10 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 35.9 mg/l Fresh water	Aquatic plants - Green algae	72 h
	Acute EC50 5.83 mg/l Fresh water	Aquatic plants - Green algae	72 h

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic	8.8	3.00	low
acid, di-C8-10-branched			
alkyl esters, C9-rich			
Chrome yellow (Lead		3,600.00	high
chromate pigment)			
Titanium dioxide		352.00	low

Mobility in soil



F216C YELLOW FM

Version Number 1.7 Page 13 of 18 Revision Date 03/03/2015 Print Date 03/04/2015

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Consult mode specific transport rules

IMO/IMDG (maritime) : Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: The

following components are listed: Chrome yellow (Lead chromate

pigment)

Lead chromate

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-

Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 14 of 18 Print Date 03/04/2015

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Listed Lead chromate

Lead sulfate

United States - TSCA 5(a)2 - Proposed significant new use rules: Listed Lead chromate Lead sulfate

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Listed Lead chromate

Chrome yellow (Lead chromate pigment)

United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined

United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-,branched

United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed 1,2-Benzenedicarboxylic acid, butyl phenylmethylester

Lead chromate

Chrome yellow (Lead chromate pigment)

Lead sulfate

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 15 of 18 Print Date 03/04/2015

Clean Air Act Section 112(b) : Listed

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I : Not listed

Substances

Clean Air Act Section 602 Class II : Not listed

Substances

DEA List I Chemicals (Precursor : Not listed

Chemicals)

DEA List II Chemicals (Essential: Not listed

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
1,2-Benzenedicarboxylic acid,	85-68-7	100 lb(s)
butyl phenylmethylester		45.4 kg
Lead sulfate	7446-14-2	
		10 lb(s)
		4.54 kg

SARA 311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
1,2-Benzenedicarboxylic acid, di- C8-10-branched alkyl esters, C9- rich	5 - 10	АН
Lead chromate	1 - 5	СН
Chrome yellow (Lead chromate pigment)	0.1 - 1	СН
Titanium dioxide	0.1 - 1	СН

SARA 313

	Product name	CAS number	%
Form R - Reporting	Lead chromate	7758-97-6	1 - 5
requirements			
	Chrome yellow (Lead	1344-37-2	0.1 - 1



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 16 of 18 Print Date 03/04/2015

	chromate pigment)			
	Lead sulfate	7446-14-2	0 - 0.1	
Supplier notification	Lead chromate	7758-97-6	1 - 5	
	Chrome yellow (Lead chromate pigment)	1344-37-2	0.1 - 1	
	Lead sulfate	7446-14-2	0 - 0.1	

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:

1,2-Benzenedicarboxylic acid, butyl phenylmethylester

Lead chromate

New York : The following components are listed:

1,2-Benzenedicarboxylic acid, butyl phenylmethylester

New Jersey : The following components are listed:

Ethene, chloro-, homopolymer

1,2-Benzenedicarboxylic acid, butyl phenylmethylester

Lead chromate

Chrome yellow (Lead chromate pigment)

Titanium dioxide

Pennsylvania : The following components are listed:

1,2-Benzenedicarboxylic acid, butyl phenylmethylester

Lead chromate

Chrome yellow (Lead chromate pigment)

Titanium dioxide

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : All components are listed or exempted.

International regulations



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 17 of 18 Print Date 03/04/2015

International lists : Australia inventory (AICS): Not determined.

Taiwan inventory (CSNN): Not determined.

Malaysia Inventory (EHS Register): Not determined. EINECS: All components are listed or exempted.

Japan inventory: Not determined.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components

are listed or exempted.

Philippines inventory (PICCS): All components are listed or

exempted.

Chemical Weapons Convention

List Schedule I Chemicals

Chemical Weapons Convention

List Schedule II Chemicals

Chemical Weapons Convention

List Schedule III Chemicals

Not listed

Not listed

Not listed

Section 16. Other information

History

Date of printing: 03/04/2015Date of issue/Date of revision: 03/03/2015Date of previous issue: 03/13/2014

Version : 1.7

Key to abbreviations: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

 $IMDG = International \ Maritime \ Dangerous \ Goods$

 $LogPow = logarithm\ of\ the\ octanol/water\ partition\ coefficient$

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.



F216C YELLOW FM

Version Number 1.7 Revision Date 03/03/2015 Page 18 of 18 Print Date 03/04/2015

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.