MATERIAL SAFETY DATA SHEET

FB322 BLACK L-3380

Version Number 1.2 Revision Date 05/16/2005

Page 1 of 6 Print Date 11/18/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	FB322 BLACK L-3380
Product code :	FO00004489
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Azodicarbonamide	123-77-3	1 - 5
Oxirane,	25085-99-8	5 - 10
2,2'-[(1-methylethylidene)bis(4,1-phenylene		
oxymethylene)]bis-, homopolymer		
Calcium carbonate	1317-65-3	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

FB322 BLACK L-3380

Version Number 1.2 Revision Date 05/16/2005 Page 2 of 6 Print Date 11/18/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET FB322 BLACK L-3380

Version Number 1.2 Revision Date 05/16/2005 Page 3 of 6 Print Date 11/18/2011

	7.	HANDLING AND STORA	GE	
Handling	fı P	leat only in areas with approp ume condensates may contain eriodically clean hoods, duct ccumulation of these materia	a combustible or toxic resi s, and other surfaces to mi	due.
Storage		Leep containers dry and tightlend contamination. Store in a		e absorption
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	lo personal respiratory protec	tive equipment normally 1	required.
Eye/Face Protection	: S	afety glasses with side-shield	ls.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with goo Vash hands before breaks and		afety practi
Engineering measures		leat only in areas with approp ppropriate exhaust ventilation		Provide
				Provide
Exposure limit(s)	aj	ppropriate exhaust ventilation	n at machinery.	
Exposure limit(s) Components	aj Value	ppropriate exhaust ventilation Exposure time	at machinery.	List:
Exposure limit(s)	aj	ppropriate exhaust ventilation	n at machinery.	List: OSHA 2
Exposure limit(s) Components	aj Value 5 mg/m3 15 mg/m3	ppropriate exhaust ventilation Exposure time PEL:	at machinery. Exposure type Respirable fraction. Total dust.	List: OSHA 2
Exposure limit(s) Components Calcium carbonate	aj Value 5 mg/m3 15 mg/m3 9. PHYSIC	ppropriate exhaust ventilation Exposure time PEL: PEL: CAL AND CHEMICAL PR	A at machinery. Exposure type Respirable fraction. Total dust. OPERTIES	List: OSHA 2 OSHA 2
Exposure limit(s) Components Calcium carbonate Form	ay Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquio	ppropriate exhaust ventilation Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not	List: OSHA Z OSHA Z established
Exposure limit(s) Components Calcium carbonate Form Appearance	Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco	ppropriate exhaust ventilation Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap ous, liquid Spec	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not	List: OSHA Z OSHA Z established determined
Exposure limit(s) Components Calcium carbonate Form Appearance Color	aj Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : BLA	ppropriate exhaust ventilation Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap ous, liquid Spec CK Bulk	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not	List: OSHA 2 OSHA 2 established determined applicable
Exposure limit(s) Components Calcium carbonate Form Appearance Color Odor	Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : BLA : Very	Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap ous, liquid Spec CK Bulk y faint Vapo	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not	List: OSHA Z OSHA Z established determined applicable determined
Exposure limit(s) Components Calcium carbonate Form Appearance Color Odor Melting point/range	Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : BLA : Very : Not a	Exposure time PEL: PEL: Output Out	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not our density : Not our density : Not	List: OSHA 2 OSHA 2 established determined determined determined
Exposure limit(s) Components Calcium carbonate Form Appearance Color Odor Melting point/range Boiling Point:	Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : BLA : Very : Not a	Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap ous, liquid Spec CK Bulk faint Vapo applicable Vapo applicable pH	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not our density : Not our density : Not	List: OSHA 2 OSHA 2 established determined determined determined
Exposure limit(s) Components Calcium carbonate Form Appearance Color Odor Melting point/range Boiling Point:	Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : BLA : Very : Not a : Not a : Imm	Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap ous, liquid Spec CK Bulk faint Vapo applicable Vapo applicable pH	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not . .	List: OSHA 2 OSHA 2 established
	aj Value 5 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : BLA : Very : Not a : Not a : Imm 10. S	Exposure time PEL: PEL: CAL AND CHEMICAL PR d Evap ous, liquid Spec CK Bulk y faint Vapo applicable pH iscible pH	Exposure type Respirable fraction. Total dust. OPERTIES oration rate : Not ific Gravity: : Not density : Not or pressure : Not . .	List: OSHA Z OSHA Z established determined determined determined



MATERIAL SAFETY DATA SHEET FB322 BLACK L-3380

Version Number 1.2 Revision Date 05/16/2005 Page 4 of 6 Print Date 11/18/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
123-77-3	Azodicarbonamide	sensitizer	Respiratory system.
25085-99-8			Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
123-77-3	Azodicarbonamide	LC50	200 mg/l	rat
		Oral LD50	> 6,400 mg/kg	rat
		Dermal LD50	> 2,000 mg/kg	rabbit

Additional Health Hazard Information:

Azodicarbonamide 123-77-3 Sensitizer to the respiratory system with repeated minimal inhalation. While no chronic health problems have been identified, individuals with respiratory problems should avoid inhalation exposure to this material.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

PolyOne.

MATERIAL SAFETY DATA SHEET **FB322 BLACK L-3380**

Version Number 1.2 Revision Date 05/16/2005 Page 5 of 6 Print Date 11/18/2011

Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a
Environmental Toxicity	whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E Not applicable	Extremely Hazardous Substance

PolyOne

MATERIAL SAFETY DATA SHEET **FB322 BLACK L-3380**

Version Number 1.2 Revision Date 05/16/2005 Page 6 of 6 Print Date 11/18/2011

SARA Title III Section 313 Toxic Chemicals:				
Not applicable Canadian Regulations:				
National Pollutant Release	se Iı	nventory (NPRI)		
Not applicable				
WHMIS Classification	:	D2A		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Not determined		
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.