PolvOne

### MATERIAL SAFETY DATA SHEET G409A ORANGE T.C

Version Number 1.3 Revision Date 01/21/2008

Page 1 of 8 Print Date 12/3/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:		Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	G409A ORANGE T.C
Product code	:	FO00004700
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Lead chromate	7758-97-6	0.1 - 1
Titanium dioxide	13463-67-7	0.1 - 1
Calcium carbonate	1317-65-3	1 - 5
Calcium oxide	1305-78-8	1 - 5

#### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

## MATERIAL SAFETY DATA SHEET **G409A ORANGE T.C**

Version Number 1.3 Revision Date 01/21/2008 Page 2 of 8 Print Date 12/3/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, Water spray, Dry powder, Foam.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

PolyOne.

# MATERIAL SAFETY DATA SHEET **G409A ORANGE T.C**

Version Number 1.3 Revision Date 01/21/2008 Page 3 of 8 Print Date 12/3/2011

Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EX	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

PolyOne

## MATERIAL SAFETY DATA SHEET G409A ORANGE T.C

Version Number 1.3 Revision Date 01/21/2008 Page 4 of 8 Print Date 12/3/2011

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average		MX OEL
		(TWA):		
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Calcium oxide	2 mg/m3	Time Weighted Average (TWA):		ACGIH
	5 mg/m3	PEL:		OSHA Z1
	2 mg/m3	Time Weighted Average (TWA):		MX OEL
Lead chromate	0.012 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.05 mg/m3	Time Weighted Average (TWA):	as Pb	ACGIH
	0.005	Time Weighted Average		OSHA
	mg/m3	(TWA):		
	0.0025	OSHA Action level:		OSHA
	mg/m3			
	0.1 mg/m3	Ceiling Limit Value:		OSHA Z2
	0.01	Time Weighted Average		MX OEL
	mg/m3	(TWA):		
	1 mg/m3	PEL:	as Cr	OSHA Z1
	0.05	Time Weighted Average		OSHA
	mg/m3	(TWA):		
	0.03	OSHA Action level:		OSHA
	mg/m3			
	0.15	Time Weighted Average	Dust and fume. as Pb	MX OEL
	mg/m3	(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- liquid
  Viscous, liquid
  ORANGE
  Very faint
  Not applicable
  Not applicable
  Immiscible

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH Not established
Not determined
Not applicable
Not determined
Not determined
Not applicable

#### **10. STABILITY AND REACTIVITY**

P<u>olyOne</u>

### MATERIAL SAFETY DATA SHEET G409A ORANGE T.C

Version Number 1.3 Revision Date 01/21/2008 Page 5 of 8 Print Date 12/3/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7758-97-6	Lead chromate	Systemic effects	central nervous system (CNS),
			reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.
		Corrosive	Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

1	CAS-No.	Chemical Name	Route	Value	Species
	7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
7758-97-6	Lead chromate	yes	1	no

PolyOne.

## MATERIAL SAFETY DATA SHEET **G409A ORANGE T.C**

Version Number 1.3 Revision Date 01/21/2008 Page 6 of 8 Print Date 12/3/2011

13463-67-7 Titani	um d	ioxide	no	2B	no
IARC Carcinogen Classification 1 - The component is carcinoge 2A - The component is probability 2B - The component is possible	enic ly ca	rcinogenic to humans			
NTP Carcinogen Classification 1 - The component is known to 2 - The component is reasonab	be a		an carcinogen.		
Additional Health Hazard In Lead chromate 7758-97-6 S with abdominal pain, anemia	Syste	mic effects include 1			
	12	2. ECOLOGICAL II	NFORMATION		
Persistence and degradability	:	Not readily biodegra	adable.		
Environmental Toxicity	:	Environmental toxic whole.	city has not been o	established for t	his mixture as a
<b>Bioaccumulation</b> Potential	:	No data available			
Additional advice	:	No data available			
	1	3. DISPOSAL CON	SIDERATIONS		
Product	:	Where possible recy generator of waster classification, transp applicable federal, s	naterial has the re portation and disp	sponsibility for osal in accordar	proper waste
Contaminated packaging	:	Recycling is preferr material has the resp transportation and d state/provincial and	ponsibility for pro isposal in accorda	per waste classi ance with applic	fication,
	1	4. TRANSPORT IN	FORMATION		
U.S. DOT Classification	:	Refer to specific reg	gulation.		
ICAO/IATA (air)	:	Refer to specific reg	gulation.		
IMO / IMDG (maritime)	:	Refer to specific reg	gulation.		
	15	. REGULATORY I	NFORMATION		

PolyOne.

# MATERIAL SAFETY DATA SHEET **G409A ORANGE T.C**

ersion Number 1.3 evision Date 01/21/2008					Р	P rint Date	age 7 of 8 12/3/2011
OSHA Status :	Classified as haz	ardous b	ased on co	omponents	5.		
TSCA Status :	All components TSCA Inventory		roduct are	listed on	or exei	mpt from th	e
US. EPA CERCLA Hazardous Sub	stances (40 CFR 3	802)					
Not applicable							
California Proposition : 65	WARNING! Th California to cau chemical known other reproductiv	to the St	r., WARN	ING! Thi	is prod	uct contains	s a
SARA Title III Section 302 Extreme	ely Hazardous Su	bstance					
Unless specific chemicals are identi	fied under this sec	ction, this	s product is	s Not App	olicable	e under this	regulation
SARA Title III Section 313 Toxic C	Themicele						
SAKA The III Section 515 Toxic C	Inennicais.						
Unless specific chemicals are identi Chemical Name	fied under this sec	ction, this	s product is CAS-No				regulation
CHROMIUM VI COMPOUNDS	SLEAD		7758-97-0		Weigh 0.10 -		
COMPOUNDSLEAD COMPOU		IC		-			
Canadian Regulations:							
Cunadian Regulations.							
National Pollutant Release In	nventory (NPRI)	CAGN		Waisht	0/		<u>и</u>
Chemical Name Lead chromate		CAS-N 7758-9		Weight 0.10 - 1		NPRI ID 235	#
		1100 2	, .	0.10 - 1		236	
WHMIS Classification : WHMIS Ingredient Disclosu CAS-No. 1305-78-8 7758-97-6							
DSL :	All of the comp	onents of	f this produ	uct are list	ted on t	the Canadia	n

PolyOne

## MATERIAL SAFETY DATA SHEET G409A ORANGE T.C

Version Number 1.3 Revision Date 01/21/2008 Page 8 of 8 Print Date 12/3/2011

Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.