

MATERIAL SAFETY DATA SHEET

G681 TAN

Version Number 1.0 Revision Date 06/10/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	G681 TAN
Product code	:	FO00004705
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET

G681 TAN

sion Date 06/10/2002	Print Date 11/4/2
	4. FIRST AID MEASURES
Inhalation	 Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases or doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize

MATERIAL SAFETY DATA SHEET



sion Date 06/10/2002				Print	Page 3 /4/Date 11
	ac	ccumulation of these mater	ials.		
Storage		eep containers dry and tight ad contamination. Store in			e absorption
8. E	XPOSURE	CONTROLS / PERSON	AL PROTECTI	ON	
Respiratory protection	: U	nder normal handling cond	litions a respirato	or is not req	uired.
Eye/Face Protection	: S	afety glasses with side-shie	elds.	-	-
Hand protection		rotective gloves.			
-					
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: Sa	afety shoes.			
General Hygiene Considerations		andle in accordance with g Vash hands before breaks a			afety practic
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					
<u></u>					
	Value	Exposure time	Exposu	e type	List:
Components Calcium carbonate	Value 10 mg/m3	Exposure time Time Weighted Average (TWA):	Exposur e Total		
Components	10 mg/m3		e Total	dust.	ACGIH
Components Calcium carbonate		Time Weighted Average (TWA):		dust. le dust.	ACGIH OSHA Z
Components Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3	Time Weighted Average (TWA): PEL: PEL:	e Total Respirab Total	dust. le dust.	ACGIH OSHA Z
Components Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F	e Total Respirab Total PROPERTIES	dust. le dust. dust.	ACGIH OSHA Z OSHA Z
Components Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F	e Total Respirab Total PROPERTIES	dust. le dust. dust. : Not	ACGIH OSHA Z OSHA Z established
Components Calcium carbonate Calcium carbonate Form Appearance	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Evants	e Total Respirab Total PROPERTIES aporation rate ecific Gravity	dust. le dust. dust. : Not : Not	ACGIH OSHA Z OSHA Z established determined
Components Calcium carbonate Calcium carbonate Form Appearance Color	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Eva bus, Liquid Spa Bu	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density	dust. le dust. dust. : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable.
Components Calcium carbonate Calcium carbonate Form Appearance Color Odor	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Eva bus, Liquid Spe Bu faint Va	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure	dust. le dust. dust. : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined
Components Calcium carbonate Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very : Not a	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Events ous, Liquid Spents But faint Va upplicable Va	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure por density	dust. le dust. dust. : Not : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined determined
Components Calcium carbonate Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very : Not a : Not a	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Event bus, Liquid Spen Bui faint Va upplicable Va upplicable pH	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure por density	dust. le dust. dust. : Not : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined
Components Calcium carbonate Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very : Not a	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Event bus, Liquid Spen Bui faint Va upplicable Va upplicable pH	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure por density	dust. le dust. dust. : Not : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined determined
Components Calcium carbonate Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very : Not a : Not a : Immi	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Event bus, Liquid Spen Bui faint Va upplicable Va upplicable pH	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure por density	dust. le dust. dust. : Not : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined determined
Components Calcium carbonate Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very : Not a : Not a : Immi 10. S	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F id Events bus, Liquid Spectrum faint Va upplicable Va upplicable pH iscible	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure por density	dust. le dust. dust. : Not : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined determined
Components Calcium carbonate Calcium carbonate Calcium carbonate Calcium carbonate	10 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Liqui : Visco : TAN : Very : Not a : Not a : Immi 10. S : St	Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F ad Eva bus, Liquid Spe Bu faint Va upplicable Va upplicable pH iscible	e Total Respirab Total PROPERTIES aporation rate ecific Gravity lk density por pressure por density	dust. le dust. dust. : Not : Not : Not : Not : Not	ACGIH OSHA Z OSHA Z established determined applicable. determined determined



MATERIAL SAFETY DATA SHEET

G681 TAN

Version Number 1.0 Revision Date 06/10/2002		Page 4 of 6 Print Date 11/4/2011
		decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.


Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G.	: Not regulated for transportation.



MATERIAL SAFETY DATA SHEET

G681 TAN		
Version Number 1.0 Revision Date 06/10/2002		Page 5 of 6 Print Date 11/4/2011
Classification (Non-bulk ground)		
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous S	ub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Not applicable Canadian Regulations:		
WHMIS Classification	:	D2A
WHMIS Ingredient Disclo	osu	re List
CAS-No. 128-37-0 1309-37-1 107-13-1 75-01-4		
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
		5/6

MATERIAL SAFETY DATA SHEET



Version Number 1.0 Revision Date 06/10/2002

ŀ	bh	vOn	<i>e</i> .
-			

Page 6 of 6

Print Date 11/4/2011

Korea KECI : Listed.

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.