

MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

Version Number 1.0 Revision Date 05/21/2003 Page 1 of 7 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE HCC-13628 YELLOW
Product code	:	FO00004784
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Barium sulfate	7727-43-7	1 - 5
Chrome yellow (Lead chromate pigment)	1344-37-2	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Prolonged



MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

Version Number 1.0 Revision Date 05/21/2003		Page 3 of 7 Print Date 11/11/2011
		heating may result in product degradation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXI	POSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		



MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

Version Number 1.0 Revision Date 05/21/2003 Page 4 of 7 Print Date *11/11/2011*

Components	Value	Exposure time	Exposure type	List:
Barium sulfate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Barium sulfate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Chrome yellow (Lead chromate pigment)	1 mg/m3	PEL:		OSHA Z1
Chrome yellow (Lead chromate pigment)	0.05 mg/m3	Time Weighted Average (TWA):		OSHA
	0.03 mg/m3	OSHA Action level:		OSHA
		Ceiling Limit Value:		OSHA Z2
	0.01 mg/m3	Time Weighted Average (TWA):		ACGIH
Chrome yellow (Lead chromate pigment)	0.05 mg/m3	Time Weighted Average (TWA):		ACGIH
Chrome yellow (Lead chromate pigment)	_	Reference:		OSHA
Chrome yellow (Lead chromate pigment)	0.01 mg/m3	Time Weighted Average (TWA):		MX OEL
Chrome yellow (Lead chromate pigment)	0.15 mg/m3	Time Weighted Average (TWA):	Dust and fume. as Pb	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	:Liquid	Evaporation rate	Not establishedNot determined
Appearance	:Liquid, Viscous liquid	Specific Gravity	
Color Odor Melting point/range Boiling Point: Water solubility	dispersion : YELLOW : Very faint : Not applicable : Not applicable : Immiscible	Bulk density Vapor pressure Vapor density pH	 Not applicable. Not determined Heavier than air. Not determined

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

Version Number 1.0 Revision Date 05/21/2003 Page 5 of 7 Print Date 11/11/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7727-43-7	Barium sulfate	Irritant	Respiratory system.
		Systemic effects	Eyes, Respiratory system.
1344-37-2	Chrome yellow (Lead	Systemic effects	central nervous system,
	chromate pigment)		reproductive system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1344-37-2	Chrome yellow (Lead	no	1	no
	chromate pigment)			

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Chrome yellow (Lead chromate pigment) 1344-37-2 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

	12. ECOLOGICAL INFORMATION			
Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.			
Bioaccumulation Potential	: No data available.			
Additional advice	: No data available.			
	13. DISPOSAL CONSIDERATIONS			
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with			



MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

ion Number 1.0 sion Date 05/21/2003				Print Date	Page 6 11/11/2
		applicable federal, stat	e/provincial and lo	ocal regulations.	
Contaminated packaging	:	Recycling is preferred has the responsibility t and disposal in accord and local regulations.	for proper waste cl	assification, transpo	rtation
	1	4. TRANSPORT INF	ORMATION		
U.S. DOT Classification	:	Refer to specific regul	ation.		
ΙCΑΟ/ΙΑΤΑ	:	Refer to specific regul			
IMO / IMDG	:	Refer to specific regul			
	15	. REGULATORY INI	ORMATION		
US Regulations:					
OSHA Status	:	Classified as hazardou	s based on compo	nents.	
TSCA Status	:	All components of thi Inventory.	s product are listed	on or exempt from	he TSCA
US. EPA CERCLA Hazardous	Sub	-			
Not applicable					
California Proposition 65	:	WARNING! This pro California to cause can chemical known to the other reproductive har	ncer., WARNING! State of Californi	This product conta	ins a
SARA Title III Section 302 Ex	trem	ely Hazardous Substanc	e		
Not applicable					
SARA Title III Section 313 To:	xic C	hemicals:			
Chemical Name			CAS-No.	Weight %	
CHROMIUM VI COM COMPOUNDS, INOR			1344-37-2	66.75	



MATERIAL SAFETY DATA SHEET

STAN-TONE HCC-13628 YELLOW

Version Number 1.0 Revision Date 05/21/2003 Page 7 of 7 Print Date 11/11/2011

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1344-37-2	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Listed.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.