MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

Version Number 1.2 Revision Date 08/15/2003

Page 1 of 8 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	STAN-TONE HCC-23240 GOLD PEARL
Product code	:	FO00004992
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Ethyl benzene	100-41-4	0.1 - 1
Iron oxide	1309-37-1	1 - 5
1,2,4-Trimethylbenzene	95-63-6	5 - 10
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Combustible. Vapors may be irritating to eyes and respiratory tract. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

Version Number 1.2 Revision Date 08/15/2003 Page 2 of 8 Print Date 11/12/2011

Medical Conditions	: None known.			
Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.			
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Between 100 °F and 200 °F			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. No data available. Carbon dioxide blanket, dry powder, foam, water spray. 			
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.			
Unusual Fire/Explosion Hazards	 May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. 			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Contain and collect spillage with non-combustible absorbent materia (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Package all material in appropriate container for disposa Refer to Section 13 of this MSDS for proper disposal methods.			



MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

Version Number 1.2 Revision Date 08/15/2003 Page 3 of 8 Print Date 11/12/2011

		7. HANDLING AND STORAGE
Handling		Combustible liquid. Keep away from flames, hot surfaces, and sources of ignition. Use only in an area with appropriate ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Store below 140 deg F (60 deg C). Keep containers dry and tightly closed to avoid moisture absorption and contamination.
8. EXF	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	Under normal handling conditions a respirator may not be required. Airborne contaminant levels should be maintained below the occupational exposure guidelines.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. Ensure adequate ventilation, especially in confined areas.
Engineering measures	:	Provide general and/or local exhaust ventilation to control airborne contaminant levels below the exposure guidelines.



MATERIAL SAFETY DATA SHEET **STAN-TONE HCC-23240 GOLD PEARL**

Version Number 1.2

Revision Date 08/15/2003

Page 4 of 8 Print Date 11/12/2011

Components	Value	Exposure time	Exposure type	List:
Ethyl benzene	100 ppm	Time Weighted Average	Vapor and aerosol.	ACGIH
	434 mg/m3	(TWA):		
	125 ppm	Short Term Exposure Limit	Vapor and aerosol.	ACGIH
	543 mg/m3	(STEL):		
	100 ppm	PEL:	Vapor and aerosol.	OSHA Z1
	435 mg/m3			
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average	Respirable fraction.	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
1,2,4-Trimethylbenzen	25 ppm 123	Time Weighted Average	Vapor.	ACGIH
e	mg/m3	(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility

: Liquid
: Viscous, Liquid
: YELLOW
: Very faint
: Not applicable
: No data available.
: Immiscible

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH Not established
Not determined
Not applicable.
Not determined
Not determined
Not determined

10. STABILITY AND REACTIVITY

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

Version Number 1.2 Revision Date 08/15/2003 Page 5 of 8 Print Date 11/12/2011

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
100-41-4	Ethyl benzene	Irritant	Eyes, Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, central nervous system.
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
95-63-6	1,2,4-Trimethylbenzene	Systemic effects	central nervous system.
		Irritant	Eyes, Skin.
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-41-4	Ethyl benzene	Oral LD50	3,500 mg/kg	rat
		Dermal LD50	17800 ul/kg	rabbit
95-63-6	1,2,4-Trimethylbenzene	Oral LD50	5,000 mg/kg	rat

Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
100-41-4	Ethyl benzene	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	:	No data available.
Additional advice	:	No data available.



MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

ion Number 1.2 sion Date 08/15/2003				Page 6 Print Date 11/12/2
Product	genera classif	tor of waste mater ication, transportat	g is preferred to dispo- ial has the responsibi- tion and disposal in ac provincial and local re	cordance with
Contaminated packaging	has the and dis	e responsibility for	hen possible. The ger proper waste classifice ce with applicable fec	
	14. TRA	NSPORT INFOR	RMATION	
U.S. DOT Classification	: Refer	to specific regulati	on.	
ICAO/IATA	: Refer	to specific regulati	on.	
IMO / IMDG	: Refer t	to specific regulati	on.	
	15. REGU	JLATORY INFO	RMATION	
US Regulations:				
OSHA Status	: Classif	fied as hazardous t	based on components.	
TSCA Status	: All co Invent		product are listed on or	exempt from the TSCA
US. EPA CERCLA Hazard	lous Substances	(40 CFR 302)		
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Xylenes (o-, m-, p- isomers)	1330-20-7	0.7161	100 lbs	13,965 LB
California Proposit 65 SARA Title III Section 302			ntain a substance liste	d by California Prop 65
Not applicable				
	3 Toxic Chemica	ls:		
SARA Title III Section 313	o rome enemieu			
SARA Title III Section 312 Chemical Name 1,2,4-TRIMETHY				Veight % .63

MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

Version Number 1.2 Revision Date 08/15/2003 Page 7 of 8 Print Date 11/12/2011

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
Ethyl benzene	100-41-4	0.11	111
Xylenes (o-, m-, p- isomers)	1330-20-7	0.71	240
Cumene	98-82-8	0.35	73
1,2,4-Trimethylbenzene	95-63-6	7.63	233

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
100-41-4
1309-37-1
12001-26-2
1330-20-7
95-63-6

DSL

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.



MATERIAL SAFETY DATA SHEET STAN-TONE HCC-23240 GOLD PEARL

Version Number 1.2 Revision Date 08/15/2003 Page 8 of 8 Print Date 11/12/2011