

MATERIAL SAFETY DATA SHEET

## M2962C WHITE

Version Number 1.0 Revision Date 10/15/2003 Page 1 of 7 Print Date 11/12/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	M2962C WHITE
Product code	:	FO00005637
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Magnesium carbonate	546-93-0	5 - 10
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	5 - 10
Calcium carbonate	1317-65-3	30 - 60

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



## MATERIAL SAFETY DATA SHEET M2962C WHITE

Version Number 1.0 Revision Date 10/15/2003 Page 2 of 7 Print Date 11/12/2011

Medical Conditions : None known.			
Aggravated by Exposure:			
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: No data available		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available</li> <li>No data available</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>		
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.</li> </ul>		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.		
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		



## MATERIAL SAFETY DATA SHEET **M2962C WHITE**

Version Number 1.0 Revision Date 10/15/2003 Page 3 of 7 Print Date 11/12/2011

	7.	HANDLING AND STORA	GE		
Handling	f P	: Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.			
Storage		Keep containers dry and tightly nd contamination. Store in a c		absorption	
8. E	XPOSURE	<b>CONTROLS / PERSONAL</b>	PROTECTION		
Respiratory protection	: U	Under normal handling condition	ons a respirator may not b	e required.	
Eye/Face Protection	: S	Safety glasses with side-shields.			
Hand protection	: P	Protective gloves.			
Skin and body protection	: L	Long sleeved clothing.			
Additional Protective Measures	: S	Safety shoes.			
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
		1	Respirable fraction.		

Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Magnesium carbonate	10 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Petroleum distillates, hydrotreated light naphthenic	500 ppm 2,000 mg/m3	PEL:	Vapor.	OSHA Z1
Quartz	0.05 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1

## 9. PHYSICAL AND CHEMICAL PROPERTIES



# MATERIAL SAFETY DATA SHEET

# M2962C WHITE

Version Number 1.0						
Revision Da	te 10/15/2003					

Hazardous Polymerization

Page 4 of 7 Print Date *11/12/2011* 

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	<ul> <li>liquid</li> <li>Viscous, liquid</li> <li>WHITE</li> <li>Very faint</li> <li>Not applicable</li> <li>Not applicable</li> <li>Inmiscible</li> </ul>	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapour density pH	<ul> <li>Not established</li> <li>Not determined</li> <li>Not applicable</li> <li>Not determined</li> <li>Not determined</li> <li>Not applicable</li> </ul>
Stability	<b>10. STABILITY AN</b> : Stable.	DREACTIVITY	

: Will not occur.

Conditions to avoid	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents. Avoid contact
		with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).
----------------------------------	---	---

## 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
546-93-0	Magnesium carbonate	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
64742-53-6	Petroleum distillates, hydrotreated light naphthenic	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

	CAS-No.	Chemical Name	OSHA	IARC	NTP
--	---------	---------------	------	------	-----



## MATERIAL SAFETY DATA SHEET

## M2962C WHITE

Version Number 1.0 Revision Date 10/15/2003 Page 5 of 7 Print Date 11/12/2011

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

## Additional Health Hazard Information:

**Quartz** 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	N
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
-	



## MATERIAL SAFETY DATA SHEET M2962C WHITE

Version Number 1.0 Revision Date 10/15/2003			Prin	Page 6 of 7 t Date 11/12/2011	
OSHA Status :	Classified as hazardou	s based on compor	nents.		
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)				
Not applicable					
California Proposition : 65	WARNING! This pro California to cause car chemical known to the other reproductive har	cer., WARNING! State of California	This produ	ct contains a	
SARA Title III Section 302 Extrem	ely Hazardous Substanc	e			
Not applicable					
SARA Title III Section 313 Toxic C	Chemicals:				
Not applicable Canadian Regulations: National Pollutant Release In	ventory (NPRI)				
Chemical Name		CAS-No.	Weight %	NPRI ID#	
Misc00005- Misc Zinc Cpd's		Not Available	0.24	241	
	D2A				
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:					
Australia AICS :	Not determined				
China IECS :	Not determined				
Europe EINECS :	Not determined				
Japan ENCS :	Not determined				
Korea KECI :	Not determined				
Philippines PICCS :	Not determined				



MATERIAL SAFETY DATA SHEET

# M2962C WHITE

Version Number 1.0 Revision Date 10/15/2003 Page 7 of 7 Print Date 11/12/2011

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.