

MATERIAL SAFETY DATA SHEET

MBX4010D ASIAN 75 DURO

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800		
Emergency telephone number		CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).		
Product name	:	MBX4010D ASIAN 75 DURO		
Product code	:	FO00005901		
Chemical Name	:	Mixture		
CAS-No.	:	Mixture		
Product Use	:	Industrial Applications		

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	Inhalation, Skin contact, Ingestion				
Acute exposure					
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.				
Ingestion	: May be harmful if swallowed.				
Eyes	: May cause eye/skin irritation.				
Skin	: Experience shows no unusual dermatitis hazard from routine handling.				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				
Medical Conditions Aggravated by Exposure:	: None known.				



MATERIAL SAFETY DATA SHEET

MBX4010D ASIAN 75 DURO

Version Number 1.0 Revision Date 06/11/2002 Page 2 of 5 Print Date 11/4/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	:	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:::::::::::::::::::::::::::::::::::::::	No data available. No data available. Not applicable. Carbon dioxide blanket, dry powder, foam, Water spray. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. A(CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize



MATERIAL SAFETY DATA SHEET

MBX4010D ASIAN 75 DURO

		Print Date 1	ge 3 1/4/2
	accumulation of the	se materials.	
Storage		and tightly closed to avoid moisture absorpt Store in a cool dry place.	ion
8. EXI	POSURE CONTROLS / PI	ERSONAL PROTECTION	
Respiratory protection	: Under normal hand	ing conditions a respirator is not required.	
Eye/Face Protection	: Safety glasses with	side-shields.	
Hand protection	: Protective gloves.		
Skin and body protection	: Long sleeved clothi	ng.	
Additional Protective Measures	: Safety shoes.		
General Hygiene Considerations		e with good industrial hygiene and safety pra breaks and at the end of workday.	ctice
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.		
T T1 1 1			
	us components above regula	tory thresholds in this product.	
			ned ole. ned ned
9 Form Appearance Color Odor Melting point/range Boiling Point:	 PHYSICAL AND CHEM Liquid Viscous, Liquid TAN Very faint Not applicable Not applicable 	IICAL PROPERTIES Evaporation rate : Not establish Specific Gravity : Not determi Bulk density : Not applicah Vapor pressure : Not determi Vapor density : Not determi pH : Not applicah	ned ole. ned ned
9 Form Appearance Color Odor Melting point/range Boiling Point:	 PHYSICAL AND CHEM Liquid Viscous, Liquid TAN Very faint Not applicable Not applicable Immiscible 	IICAL PROPERTIES Evaporation rate : Not establish Specific Gravity : Not determi Bulk density : Not applicah Vapor pressure : Not determi Vapor density : Not determi pH : Not applicah	ned ole. ned ned
9 Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 PHYSICAL AND CHEM Liquid Viscous, Liquid TAN Very faint Not applicable Not applicable Immiscible 10. STABILITY AND	IICAL PROPERTIES Evaporation rate : Not establish Specific Gravity : Not determi Bulk density : Not applicah Vapor pressure : Not determi Vapor density : Not determi pH : Not applicah	ned ole. ned ned
9 Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	 PHYSICAL AND CHEM Liquid Viscous, Liquid TAN Very faint Not applicable Not applicable Immiscible 10. STABILITY AND Stable. Will not occur. 	IICAL PROPERTIES Evaporation rate : Not establish Specific Gravity : Not determi Bulk density : Not applical Vapor pressure : Not determi Vapor density : Not determi pH : Not applical OREACTIVITY idizing agents and open flame. To avoid the	ned hed hed ble.
9 Form Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	 PHYSICAL AND CHEM Liquid Viscous, Liquid TAN Very faint Not applicable Not applicable Inmiscible 10. STABILITY AND Stable. Will not occur. Keep away from ox decomposition, do r Incompatible with s 	IICAL PROPERTIES Evaporation rate : Not establish Specific Gravity : Not determi Bulk density : Not applical Vapor pressure : Not determi Vapor density : Not determi pH : Not applical OREACTIVITY idizing agents and open flame. To avoid the	rmal

Version Number 1.0



Page 4 of 5

MATERIAL SAFETY DATA SHEET

MBX4010D ASIAN 75 DURO

sion Date 06/11/2002	Print Date 11/4/2
products	(NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F) and within 5 minutes at 232 °C (450 °F).
	11. TOXICOLOGICAL INFORMATION
There are no known hazardous	components above regulatory thresholds in this product.
	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.
Bioaccumulation Potential	: No data available.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory



MATERIAL SAFETY DATA SHEET

MBX4010D ASIAN 75 DURO

Version Number 1.0 Revision Date 06/11/2002 Page 5 of 5 Print Date 11/4/2011

TSCA Status

: All components of this product are listed on the TSCA inventory or are exempt.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product
Sodium hydroxide	1310-73-2	0.64	1,000lbs	155,159 LB
(Na(OH))			,	,

California Proposition	:	WARNING! This product contains a chemical known in the State of
65		California to cause cancer.

Canadian Regulations:

WHMIS Classification	:	Not controlled.
DSL	:	Listed.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Not determined.
Philippines PICCS	:	Not determined.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.