

MATERIAL SAFETY DATA SHEET

MM166W WHITE

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MM166W WHITE
Product code	:	FO00005932
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium oxide	1305-78-8	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

MM166W WHITE





Version Number 1.0 Page 2 of 6 Revision Date 06/11/2002 Print Date 11/4/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Move to fresh air in case of accidental inhalation of fumes from Inhalation : overheating or combustion. When symptoms persist, or in all cases of doubt, seek medical advice. : Do not induce vomiting without medical advice. When symptoms Ingestion persist, or in all cases of doubt, seek medical advice. Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point No data available. · Flammable Limits No data available. Upper explosion limit : Lower explosion limit No data available. : Autoignition temperature Not applicable. : Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam, Water spray. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in positive Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under : Hazards fire conditions. 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not • be allowed to enter drains, water courses or the soil. Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, : universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling

: Heat only in areas with appropriate exhaust ventilation. Processing





MM166W WHITE Page 3 of 6 Version Number 1.0 Print Date 11/4/2011 Revision Date 06/11/2002 fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Store in a cool dry place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : Under normal handling conditions a respirator is not required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Calcium oxide	2 mg/m3	Time Weighted Average (TWA):	Dust.	ACGIH
Calcium oxide	5 mg/m3	PEL:	Dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Liquid
 : Viscous, Liquid
 : WHITE
 : Very faint
 : Not applicable
 : Not applicable
 : Immiscible
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not established
 Not determined
 Not applicable.
 Not determined
 Not determined
 Not determined
 Not applicable.



MATERIAL SAFETY DATA SHEET

MM166W WHITE

Version Number 1.0 Revision Date 06/11/2002 Page 4 of 6 Print Date 11/4/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1305-78-8	Calcium oxide	Irritant	Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
		Corrosive	Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Environmental toxicity has not been established for this mixture as a whole.
: No data available.
: No data available.
13. DISPOSAL CONSIDERATIONS
: Where possible, recycling is preferred to disposal or incineration. Th
-



MATERIAL SAFETY DATA SHEET

MM166W WHITE		
Version Number 1.0 Revision Date 06/11/2002		Page 5 of 6 Print Date 11/4/2011
		generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known in the State of California to cause cancer.
Canadian Regulations:		
WHMIS Classification	:	D2A
WHMIS Ingredient Disc	losu	ure List
CAS-No.		
128-37-0 103-23-1		
<u>1305-78-8</u> <u>14808-60-7</u>		
11000 00 /		
		5/6

MATERIAL SAFETY DATA SHEET

MM166W WHITE

Version Number 1.0 Revision Date 06/11/2002

557-05-1 75-91-2 75-01-4	
DSL	: Listed.
National Inventories:	
Australia AICS	: Not determined.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Not determined.
Philippines PICCS	: Not determined.
-	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



Page 6 of 6

Print Date 11/4/2011