

## AM100 BLACK

Version Number 1.1 Page 1 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

# SAFETY DATA SHEET

#### AM100 BLACK

## **Section 1. Identification**

**GHS** product identifier AM100 BLACK

Chemical name Mixture CAS number Mixture Other means of identification FO00006458 **Product type** liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial applications. Plastics.

Supplier's details POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

**Emergency telephone number** 

(with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

or accident). CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire,

exposure or accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

**OSHA/HCS** status This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

FLAMMABLE LIQUIDS - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

#### **GHS** label elements



### AM100 BLACK

Version Number 1.1 Page 2 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Hazard pictograms

**(N)** 

 $\diamondsuit$ 

Signal word : Danger

**Hazard statements** : Highly flammable liquid and vapour.

Causes serious eye irritation. May cause drowsiness or dizziness.

#### **Precautionary statements**

**General** : Not applicable.

**Prevention**: Wear protective gloves. Wear eye or face protection. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid

breathing vapor. Wash hands thoroughly after handling.

**Response**: IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If

eye irritation persists: Get medical attention.

Storage : Store in a well-ventilated place. Keep cool.

**Disposal**: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

**Supplemental label elements**: None known. **Hazards not otherwise classified**: None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: FO00006458

#### **CAS** number/other identifiers



## AM100 BLACK

Version Number 1.1 Page 3 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Ingredient name	%	CAS number
Methyl ethyl ketone	60 - 100	78-93-3
Carbon black	1 - 5	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Flush contaminated skin with plenty of water. Remove contaminated Skin contact clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. Wash out mouth with water. Remove dentures if any. Remove victim **Ingestion** to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention



## AM100 BLACK

Version Number 1.1 Page 4 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause

drowsiness or dizziness.

**Skin contact** : No known significant effects or critical hazards.

**Ingestion**: Can cause central nervous system (CNS) depression. Irritating to

mouth, throat and stomach.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures



## AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015

Page 5 of 18 Print Date 09/26/2015

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Do not use water jet.

Specific hazards arising from the chemical

Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fireexposed containers cool.

Special protective equipment for fire-fighters

For emergency responders

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without For non-emergency personnel

> suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Avoid dispersal of spilled material and runoff and contact with soil, **Environmental precautions** 

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and materials for containment and cleaning up



## AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015 Page 6 of 18 Print Date 09/26/2015

**Small spill** 

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a



## AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015 Page 7 of 18 Print Date 09/26/2015

well-ventilated place. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 590 mg/m3 200 ppm
	Short Term Exposure Limit value for a 15-minute reference
	period expressed in parts per million or in mg/m3. 885 mg/m3 300
	ppm
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 590 mg/m3 200 ppm
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 590 mg/m3 200 ppm
	Short Term Exposure Limit value for a 15-minute reference
	period expressed in parts per million or in mg/m3. 885 mg/m3 300
	ppm ACGIH TLV (1994-09-01)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 590 mg/m3 200 ppm
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level
	885 mg/m3 300 ppm
	over mg me coo from
Carbon black	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 3.5 mg/m3
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 3.5 mg/m3
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 3.5 mg/m3
	Time Weighted Average (TWA)
	ACGIH TLV (2010-12-06)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 3 mg/m3 Form: Inhalable fraction



AM	11	$\Delta$	DI	Λ	$\boldsymbol{\cap}$	V
AIV	11	UU	DL	.А	U	N

Version Number 1.1 Revision Date 09/25/2015 Page 8 of 18 Print Date 09/26/2015

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

**Body protection** 

cannot be accurately estimated.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks



### AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015 Page 9 of 18 Print Date 09/26/2015

involved and should be approved by a specialist before handling this

product.

**Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits

of the selected respirator.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state
Color
BLACK
Odor
Not available.
Odor threshold
pH
Not available.

Flash point : Closed cup: -9 °C (15.80 °F)

Burning time: Not available.Burning rate: Not available.Evaporation rate: Not available.Flammability (solid, gas): Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure

Vapor density

Relative density

Solubility

Solubility in water

Partition coefficient: n
Not available.

Not available.

Not available.

Not available.

Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or

its ingredients.



### AM100 BLACK

Version Number 1.1 Page 10 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not

pressurize, cut, weld, braze, solder, drill, grind or expose containers to

heat or sources of ignition.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure		
Methyl ethyl ketone						
	LD50 Oral	Rat	2,737 mg/kg	-		
	LC50 Inhalation	Rat	24 mg/l	8 h		
	LD50 Dermal	Rabbit	6,480 mg/kg	-		
Carbon black				•		
	LD50 Oral	Rat	15,400 mg/kg	-		

**Conclusion/Summary**: Mixture. Not fully tested.

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Methyl ethyl ketone	Skin - Moderate irritant	Rabbit		24 hrs	-

**Conclusion/Summary** 

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

#### Sensitization



## AM100 BLACK

Version Number 1.1 Page 11 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

**Conclusion/Summary** 

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary**: Mixture.Not fully tested.

Carcinogenicity

**Conclusion/Summary** : Mixture.Not fully tested.

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Carbon black		2B	

#### **Reproductive toxicity**

**Conclusion/Summary**: Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture. Not fully tested.

**Specific target organ toxicity (single exposure)** 

Product/ingredient name	Category	Route of exposure	Target organs
Methyl ethyl ketone	Category 3		Narcotic effects

#### **Specific target organ toxicity (repeated exposure)**

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely routes of :

Not available.

exposure

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : Can cause central nervous system (CNS) depression. May cause

drowsiness or dizziness.

**Skin contact** : No known significant effects or critical hazards.



#### AM100 BLACK

Version Number 1.1 Page 12 of 18 Revision Date 09/25/2015 Print Date 09/26/2015

**Ingestion** : Can cause central nervous system (CNS) depression., Irritating to

mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

#### **Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate effects: Not available.Potential delayed effects: Not available.

Potential chronic health effects

**Conclusion/Summary** : Mixture. Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**



## AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015 Page 13 of 18 Print Date 09/26/2015

Route	ATE value
Oral	4,554.2 mg/kg

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Methyl ethyl ketone			
	Acute LC50 3,220,000 μg/l Fresh	Fish - Fathead minnow	96 h
	water		
	Acute LC50 5,600 mg/l Fresh	Fish - Western	96 h
	water	mosquitofish	
	Acute EC50 5,091,000 μg/l Fresh	Aquatic invertebrates.	48 h
	water	Water flea	
	Acute EC50 > 500,000 μg/l Marine	Aquatic plants - Diatom	96 h
	water		
	Acute EC50 > 500 mg/l Fresh	Aquatic plants - Green	96 h
	water	algae	
Carbon black			
	Acute EC50 37.563 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Water flea	
	Acute LC50 61.547 mg/l Fresh	Aquatic invertebrates.	48 h
	water	Water flea	

Conclusion/Summary : Not available.

Persistence and degradability

**Conclusion/Summary** : Not available.

**Bioaccumulative potential** 

F			
Product/ingredient name	LogPow	BCF	Potential
Methyl ethyl ketone	0.29	-	low

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

: Not available.

Other adverse effects : No known significant effects or critical hazards.



## AM100 BLACK

 Version Number 1.1
 Page 14 of 18

 Revision Date 09/25/2015
 Print Date 09/26/2015

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Acute hazardous waste "P" List: Not listed

#### United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS#	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	

## **Section 14. Transport information**

U.S. DOT Classification

Proper Shipping Name: Resin solution

Technical Name:

Hazard Class / Division 3

UN Number UN1866
Packing Group II
Label Required 3

ICAO/IATA Consult mode specific transport rules

IMO/IMDG (maritime) Consult mode specific transport rules



## AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015 Page 15 of 18 Print Date 09/26/2015

## Section 15. Regulatory information

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed Diisononyl

phthalate

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Not listed

**United States - TSCA 8(c) - Significant adverse reaction (SAR):** 

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Not listed

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

Substances

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

Not listed

Not listed

Not listed

Not listed



## AM100 BLACK

Page 16 of 18 Version Number 1.1 Revision Date 09/25/2015 Print Date 09/26/2015

**DEA List II Chemicals (Essential** 

Chemicals)

Listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Methyl ethyl ketone	78-93-3	5,000 lb(s)
		2,270 kg
		2,270 kg
		5,000 lb(s)

#### SARA 311/312

Fire hazard Classification

Immediate (acute) health hazard

#### **Composition/information on ingredients**

Name	%	Classification
Methyl ethyl ketone	60 - 100	F, AH
Carbon black	1 - 5	СН

### **SARA 313**

Not applicable.

**State regulations** 

Massachusetts The following components are listed:

Methyl ethyl ketone

Carbon black

The following components are listed: **New York** 

Methyl ethyl ketone

The following components are listed: **New Jersey** 

Methyl ethyl ketone

Isopropanol

Carbon black

Pennsylvania The following components are listed:

Methyl ethyl ketone

Isopropanol

Carbon black



### AM100 BLACK

Version Number 1.1 Page 17 of 18 Print Date 09/26/2015 Revision Date 09/25/2015

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

**United States inventory (TSCA 8b)**: All components are listed or exempted.

**Canada inventory** All components are listed or exempted.

**International regulations** 

**International lists Australia inventory (AICS):** All components are listed or exempted.

**Taiwan inventory (CSNN):** All components are listed or exempted.

Malaysia Inventory (EHS Register): Not determined. **EINECS:** All components are listed or exempted.

**Japan inventory:** All components are listed or exempted.

**China inventory (IECSC):** All components are listed or exempted.

**Korea inventory:** All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components

are listed or exempted.

Philippines inventory (PICCS): All components are listed or

exempted.

**Chemical Weapons Convention** 

**List Schedule I Chemicals** 

**Chemical Weapons Convention** 

**List Schedule II Chemicals** 

**Chemical Weapons Convention** 

**List Schedule III Chemicals** 

Not listed

Not listed

Not listed

## **Section 16. Other information**

**History** 

**Date of printing** 09/26/2015 Date of issue/Date of revision 09/25/2015 Date of previous issue 01/08/2003

Version 1.1

**Key to abbreviations** ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)



## AM100 BLACK

Version Number 1.1 Revision Date 09/25/2015 Page 18 of 18 Print Date 09/26/2015

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.