

#### MATERIAL SAFETY DATA SHEET

## PX-20415-B GOLD PLASTISOL

Version Number 1.0 Revision Date 06/11/2002 Page 1 of 7 Print Date 11/5/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 2700 Papin Street, St. Louis, MO 63103

NON-EMERGENCY TELEPHONE	:	Product Stewardship, (314) 771-1800
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PX-20415-B GOLD PLASTISOL
Product code	:	FO00006529
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	0.1 - 1
Calcium carbonate	471-34-1	1 - 5

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

# PX-20415-B GOLD PLASTISOL

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist, or in all cases doubt, seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist, or in all cases of doubt, seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If exirct irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available.
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>No data available.</li> <li>No data available.</li> <li>Not applicable.</li> <li>Carbon dioxide blanket, dry powder, foam, Water spray.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation. Processing



### MATERIAL SAFETY DATA SHEET

# PX-20415-B GOLD PLASTISOL

Version Number 1.0 Revision Date 06/11/2002	Page 3 of 7 Print Date 11/5/2011
Storage :	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.
8. EXPOSU	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection :	Under normal handling conditions a respirator is not required.
Eye/Face Protection :	Safety glasses with side-shields.
Hand protection :	Protective gloves.
Skin and body protection :	Long sleeved clothing.
Additional Protective : Measures	Safety shoes.
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

#### Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	Total dust. as Cr	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	PEL:	Total dust. as Cr	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	0.5 mg/m3	Time Weighted Average (TWA):	Dust. as Sb	ACGIH
Rutile, antimony chromium buff	0.5 mg/m3	PEL:	Total dust. as Sb	OSHA Z1
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	MX OEL

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### MATERIAL SAFETY DATA SHEET

## PX-20415-B GOLD PLASTISOL

Version Number 1.0 Revision Date 06/11/2002

Poh	vOne.
-	

Appearance: YColor: YOdor: YMelting point/range: IBoiling Point:: I	Liquid Viscous, Liquid YELLOW Very faint Not applicable Not applicable Immiscible	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
water solubility : 1	minisciple	

Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents. Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).</li> </ul>

**10. STABILITY AND REACTIVITY** 

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

Page 4 of 7 Print Date 11/5/2011

Not established

: Not determined

: Not applicable. : Not determined

: Not determined

: Not applicable.

:



MATERIAL SAFETY DATA SHEET

# PX-20415-B GOLD PLASTISOL

Version Number 1.0

Revision Date 06/11/2002

Page 5 of 7 Print Date 11/5/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
68186-90-3	Rutile, antimony chromium buff	no	3	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL INFORMATION		
Persistence and degradability	: Not readily biodegradable.		
Environmental Toxicity	: Environmental toxicity has not been established for this mixture as a whole.		
Bioaccumulation Potential	: No data available.		
Additional advice	: No data available.		
	13. DISPOSAL CONSIDERATIONS		
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.		
	14. TRANSPORT INFORMATION		
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.		
ICAO/IATA	: Not regulated for transportation.		
	5/7		



### MATERIAL SAFETY DATA SHEET

# PX-20415-B GOLD PLASTISOL

MO / IMDG	: Not re	gulated for transpo	ortation.		
15. REGULATORY INFORMATION					
US Regulations:					
OSHA Status	: Classit	fied as hazardous l	based on components.		
TSCA Status	: All con exemp		roduct are listed on the	e TSCA inventory or a	
JS. EPA CERCLA Hazard	lous Substances	(40 CFR 302)			
Chemical Name	CAS-No.	% in Product	RQ for component	RQ for Mixture/Product	
Xylenes (o-, m-, p- isomers)	1330-20-7	0.06	100lbs	161,290 LB	
California Proposit 65		NING! This produ rnia to cause cance	ict contains a chemica er.	l known in the State o	
65				l known in the State o	
65	Califo			l known in the State o	
65 Canadian Regulations:	Califo tion : D2B			l known in the State o	
65 Canadian Regulations: WHMIS Classifica WHMIS Ingredient CAS-No. 1305-78-8 14808-60-	Califor tion : D2B Disclosure List			l known in the State o	
65 Canadian Regulations: WHMIS Classifica WHMIS Ingredient CAS-No. 1305-78-8 14808-60- 68186-90- 8052-41-3 1330-20-7 95-63-6	Califor tion : D2B Disclosure List			l known in the State o	
65 Canadian Regulations: WHMIS Classifica WHMIS Ingredient CAS-No. 1305-78-8 14808-60- <sup>2</sup> 68186-90-2 8052-41-3 1330-20-7	Califor tion : D2B Disclosure List	rnia to cause cance		l known in the State o	
65 Canadian Regulations: WHMIS Classifica WHMIS Ingredient CAS-No. 1305-78-8 14808-60- 68186-90-3 8052-41-3 1330-20-7 95-63-6 75-01-4 DSL	Califor tion : D2B Disclosure List	rnia to cause cance		l known in the State o	
65 Canadian Regulations: WHMIS Classifica WHMIS Ingredient CAS-No. 1305-78-8 14808-60- 68186-90-2 8052-41-3 1330-20-7 95-63-6 75-01-4 DSL	Califor tion : D2B Disclosure List	rnia to cause cance		l known in the State o	
65 Canadian Regulations: WHMIS Classifica WHMIS Ingredient CAS-No. 1305-78-8 14808-60-7 68186-90-7 8052-41-3 1330-20-7 95-63-6 75-01-4 DSL National Inventories:	Califor tion : D2B Disclosure List	rnia to cause cance		l known in the State c	



#### MATERIAL SAFETY DATA SHEET

## PX-20415-B GOLD PLASTISOL

Version Number 1.0 Revision Date 06/11/2002 Page 7 of 7 Print Date 11/5/2011

Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.