MATERIAL SAFETY DATA SHEET S1010 CRYSTAL CLEAR

Version Number 2.3 Revision Date 12/11/2006

Page 1 of 7 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone:Emergency telephone:number		Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S1010 CRYSTAL CLEAR
Product code	:	FO00006799
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30 - 60
phenylmethylester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET S1010 CRYSTAL CLEAR

Version Number 2.3 Revision Date 12/11/2006 Page 2 of 7 Print Date 11/25/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET S1010 CRYSTAL CLEAR

ersion Number 2.3 Page 3 evision Date 12/11/2006 Print Date 11/25/2						
Handling	: H	Heat only in areas with approp	riate exhaust ventilation.	Processing		
	P	fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.				
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	No personal respiratory protect	tive equipment normally r	required.		
Eye/Face Protection	: S	Safety glasses with side-shields.				
Hand protection	: P	Protective gloves.				
Skin and body protection	: I	ong sleeved clothing.				
Additional Protective Measures	: S	Safety shoes.				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Silica, amorphous,	20 mppcf	PEL:	Total dust.	Z3		

Components	value	Exposure time	Exposure type	List.
Silica, amorphous,	20 mppcf	PEL:	Total dust.	Z3
fumed, crystal-free				
	0.8 mg/m3	Time Weighted Average		Z3
		(TWA):		
	10 mg/m3	Time Weighted Average	Inhalable particulate.	MX OEL
		(TWA):		
	3 mg/m3	Time Weighted Average	Respirable dust.	MX OEL
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 NO PIGMENT
 Very faint
 Not applicable
 Not applicable
 Immiscible
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not established
 Not determined
 Not applicable
 Not determined
 Not determined
 Not determined
 Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET S1010 CRYSTAL CLEAR

Version Number 2.3 Revision Date 12/11/2006 Page 4 of 7 Print Date 11/25/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Oral LD50 Dermal LD50	2,330 mg/kg > 10 gm/kg	rat rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET **S1010 CRYSTAL CLEAR**

Version Number 2.3 Revision Date 12/11/2006 Page 5 of 7 Print Date 11/25/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
IARC Carcinogen Classification 1 - The component is carcinoge 2A - The component is probabl 2B - The component is possible	enic to humans. ly carcinogenic to huma			
NTP Carcinogen Classification	с.			
 The component is known to The component is reasonable 	be a human carcinogen			
	12. ECOLOGICAL	INFORMATION		
Persistence and degradability	: Not readily biode	gradable.		
Environmental Toxicity	: Environmental to: whole.	xicity has not been e	established for this	s mixture as a
Bioaccumulation Potential	: No data available			
Additional advice	: No data available			
	13. DISPOSAL CO	NSIDERATIONS		
Product	generator of waster classification, tran	e waterial has the re sportation and disp state/provincial an	sponsibility for pr osal in accordance	oper waste with
Contaminated packaging	has the responsibi	rred when possible. lity for proper waste cordance with appli ons.	e classification, tra	ansportation
	14. TRANSPORT	INFORMATION		
U.S. DOT Classification Proper Shipping Name: Technical Name:	Environmentally haza	rdous substances, li	quid, n.o.s.	
Hazard Class / Division UN Number	9 UN3082			
Packing Group	III			
Label Required	9			
Hazardous Substance Reportable quantity:	Butyl benzyl phthalate 289 LB	2		
ICAO/IATA (air)	Refer to specific regul	ation.		
IMO / IMDG (maritime)	Refer to specific regul	ation.		

MATERIAL SAFETY DATA SHEET S1010 CRYSTAL CLEAR

Version Number 2.3 Revision Date 12/11/2006

Page 6 of 7 Print Date 11/25/2011

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status

: All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for
			Mixture/Product
1,2-Benzenedicarb	85-68-7	100 lbs	289 LB
oxylic acid, butyl			
phenylmethylester			

California Proposition:WARNING! This product contains a chemical known to the State of
California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
1-Methyl-2-pyrrolidone	872-50-4	0.10 - 1.00	164
1,2-Benzenedicarboxylic acid, butyl	85-68-7	30.00 - 60.00	37
phenylmethylester			

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.

PolyOne

MATERIAL SAFETY DATA SHEET S1010 CRYSTAL CLEAR

Version Number 2.3 Revision Date 12/11/2006 Page 7 of 7 Print Date 11/25/2011

112945-52-5 85-68-7		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Not determined
China IECS	:	Not determined
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Not determined
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.