MATERIAL SAFETY DATA SHEET **S1980 SILVER GLITTER**

Version Number 1.4 Revision Date 12/11/2006

Page 1 of 7 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 8155 Cobb Center Drive, Kennesaw, GA 30152

Telephone Emergency telephone number	:	Product Stewardship (770) 590-3500 x.3563 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	S1980 SILVER GLITTER
Product code	:	FO00006836
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10 - 30
phenylmethylester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: May cause eye/skin irritation.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **S1980 SILVER GLITTER**

Version Number 1.4 Revision Date 12/11/2006 Page 2 of 7 Print Date 11/25/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: No data available
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 No data available No data available Not applicable Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxide of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET S1980 SILVER GLITTER

Version Number 1.4 Revision Date 12/11/2006			Print D	Page 3 of 7 ate 11/25/2011		
Handling	fı P	leat only in areas with appropri ume condensates may contain of eriodically clean hoods, ducts,	combustible or toxic resident and other surfaces to mi	due.		
Storage	: K	accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.				
8.1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally r	equired.		
Eye/Face Protection	: S	Safety glasses with side-shields.				
Hand protection	: P	Protective gloves.				
Skin and body protection	: L	Long sleeved clothing.				
Additional Protective Measures	: S	Safety shoes.				
General Hygiene Considerations		Iandle in accordance with good Vash hands before breaks and a		afety practice.		
Engineering measures	neering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Silica, amorphous, fumed, crystal-free	20 mppcf					
•	0.8 mg/m3	Time Weighted Average (TWA):		Z3		

(TWA): 10 mg/m3 Time Weighted Average	ge Inhalable particulate.	MX OEL
(TWA):		
3 mg/m3 Time Weighted Average (TWA):	ge Respirable dust.	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- liquid
 Viscous, liquid
 GREY
 Very faint
 Not applicable
 Not applicable
 Immiscible
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not established
 Not determined
 Not applicable
 Not determined
 Not determined
 Not determined
 Not applicable

PolyOne

MATERIAL SAFETY DATA SHEET S1980 SILVER GLITTER

Version Number 1.4 Revision Date 12/11/2006 Page 4 of 7 Print Date 11/25/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating may result in product degradation. As a general rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F).

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
112945-52-5	Silica, amorphous, fumed, crystal-free	Irritant	Eyes, Respiratory system.
85-68-7	1,2-Benzenedicarboxylic acid, butyl phenylmethylester	Irritant	Eyes, Skin.
		Systemic effects	Liver, reproductive system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat
85-68-7	1,2-Benzenedicarboxylic	Oral LD50	2,330 mg/kg	rat
	acid, butyl	Dermal LD50	> 10 gm/kg	rabbit
	phenylmethylester			

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET **S1980 SILVER GLITTER**

Version Number 1.4 Revision Date 12/11/2006 Page 5 of 7 Print Date 11/25/2011

CAS-No.	Chemical Name	OSHA	IARC	NTP
IARC Carcinogen Classification	me.			
1 - The component is carcinoge				
2A - The component is probab		ns.		
2B - The component is possibly	y carcinogenic to human	s.		
NTP Carcinogen Classification				
1 - The component is known to				
2 - The component is reasonab	Ty anticipated to be a nul	man carcinogen.		
	12. ECOLOGICAL	INFORMATION		
Persistence and degradability	: Not readily biodeg	gradable.		
Environmental Toxicity	: Environmental tox	cicity has not been e	established for this	mixture as a
	whole.			
Bioaccumulation Potential	: No data available			
Additional advice	: No data available			
	13. DISPOSAL CO	NSIDERATIONS		
Product		cycling is preferred		
		e material has the re asportation and disp		
		, state/provincial an		
	applicable leaderal	, state, provinciar an	a local logalation	•
Contaminated packaging		rred when possible.		
		lity for proper wast		
		cordance with appli	cable federal, state	e/provincial
	and local regulation	ons.		
	14. TRANSPORT I	NFORMATION		
U.S. DOT Classification				
Proper Shipping Name:	Environmentally hazar	rdous substances, li	quid, n.o.s.	
Technical Name:	•			
Hazard Class / Division	9			
UN Number	UN3082			
Packing Group	III			
Label Required	9			
Hazardous Substance	Butyl benzyl phthalate			
Reportable quantity:	350 LB			
ICAO/IATA (air)	Refer to specific regul	ation.		
IMO / IMDG (maritime)	Refer to specific regul	ation.		
	···· ·································			

MATERIAL SAFETY DATA SHEET S1980 SILVER GLITTER

Version Number 1.4 Revision Date 12/11/2006

Page 6 of 7 Print Date 11/25/2011

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status

: All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component	RQ for
		_	Mixture/Product
1,2-Benzenedicarb	85-68-7	100 lbs	350 LB
oxylic acid, butyl			
phenylmethylester			

California Proposition:WARNING! This product contains a chemical known to the State of
California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
1,2-Benzenedicarboxylic acid, butyl	85-68-7	10.00 - 30.00	37
phenylmethylester			

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
112945-52-5	
112745-52-5	

PolyOne

MATERIAL SAFETY DATA SHEET S1980 SILVER GLITTER

Version Number 1.4 Revision Date 12/11/2006 Page 7 of 7 Print Date 11/25/2011

85-68-7 DSL	:	All components of this product are on the Canadian Domestic	
		Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Not determined	
China IECS	:	Not determined	
Europe EINECS	:	Listed	
Japan ENCS	:	Not determined	
Korea KECI	:	Not determined	
Philippines PICCS	:	Not determined	

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.